

Prüfbericht-Nr.: <i>Test Report No.:</i>	50087662 001	Auftrags-Nr.: <i>Order No.:</i>	1160035819	Seite 1 von 131 <i>Page 1 of 131</i>
Kunden-Referenz-Nr.: <i>Client Reference No.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	26.05.2017	
Auftraggeber: <i>Client:</i>	NINGBO BAKELON ELECTRICAL APPLIANCE CO., LTD.			
Prüfgegenstand: <i>Test item:</i>	Sandwich maker			
Bezeichnung / Typ-Nr.: <i>Identification / Type No.:</i>	See page 2			
Auftrags-Inhalt: <i>Order content:</i>	Type test			
Prüfgrundlage: <i>Test specification:</i>	EN 60335-1:2012+A11 EN 60335-2-9:2003+A1+A2+A12+A13 EN 62233:2008 AfPS GS 2014:01 Par. 3.1			
Wareneingangsdatum: <i>Date of receipt:</i>	26.05.2017			
Prüfmuster-Nr.: <i>Test sample No.:</i>	A000564372			
Prüfzeitraum: <i>Testing period:</i>	26.05.2017 – 28.07.2017			
Ort der Prüfung: <i>Place of testing:</i>	TÜV Rheinland /CCIC (Ningbo) Co., Ltd.			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland /CCIC (Ningbo) Co., Ltd.			
Prüfresultat*: <i>Test result*:</i>	Pass			
geprüft von / tested by:	kontrolliert von / reviewed by:			
<i>9.8.2017</i> Sagan Sheng/PE	<i>[Signature]</i>	<i>10.08.2017</i> William Gui/ TC	<i>[Signature]</i>	
Datum <i>Date</i>	Name / Stellung <i>Name / Position</i>	Unterschrift <i>Signature</i>	Datum <i>Date</i>	Name / Stellung <i>Name / Position</i>
Sonstiges / Other:				
Attachment 1: PAHs risk analysis filled by manufacturer (3 pages)				
Attachment 2: PAHs risk analysis filled by GS test center (3 pages)				
Attachment 3: LFGB list. (1 page)				
Attachment 4: Test equipment list (10 pages)				
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>		Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>		
* Legende:	1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)	2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	3 = befriedigend N/A = nicht anwendbar	4 = ausreichend N/T = nicht getestet
Legend:	1 = very good P(ass) = passed a.m. test specification(s)	2 = good F(ail) = failed a.m. test specification(s)	3 = satisfactory N/A = not applicable	4 = sufficient N/T = not tested
<p>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</p> <p><i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i></p>				



<p>TEST REPORT IEC 60335-2-9 Safety of household and similar electrical appliances Part 2: Particular requirements for grills, toasters and similar cooking appliances</p>	
Report Number	50087662 001
Date of issue	See cover page
Total number of pages.....	See cover page
Applicant's name.....	NINGBO BAKELON ELECTRICAL APPLIANCE CO., LTD.
Address	NO. 88 XIANTAN ROAD, LANGXIA VILLAGE, LANGXIA STREET YUYAO CITY, ZHEJIANG 315480 P. R. China
Test specification:	
Standard	IEC 60335-2-9:2002 (Fifth edition) + A1:2004 + A2:2006 in conjunction with IEC 60335-1:2010 (Fifth Edition)
Test procedure	GS mark and CE LVD
Non-standard test method.....	N/A
Test Report Form No.....	IEC60335_2_9J
Test Report Form(s) Originator.....	LCIE
Master TRF	Dated 2013-11
<p>Copyright © 2013 Worldwide System for Conformity Testing and Certification of Electrotechnical Equipment and Components (IECEE), Geneva, Switzerland. All rights reserved.</p> <p>This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.</p> <p>If this Test Report Form is used by non-IECEE members, the IECEE/IEC logo and the reference to the CB Scheme procedure shall be removed.</p> <p>This report is not valid as a CB Test Report unless signed by an approved CB Testing Laboratory and appended to a CB Test Certificate issued by an NCB in accordance with IECEE 02.</p>	
Test item description	Sandwich maker
Trade Mark	N/A
Manufacturer.....	Same as applicant
Model/Type reference	ZM-200, ZM-200B, ZM-201, ZM-202B, ZM-206, ZM-206B, ZM-207, ZM-207B, ZM-208, ZM-208B, ZM-227, ZM-227B, ZM-228, ZM-228B, ZM-228C, ZM-228D, ZM-267, ZM-267B, ZM-268B, ZM-258B, ZM-259, ZM-259B, ZM-269B, ZM-707, ZM-707B, ZM-707C
Ratings	AC 220-240V; 50/60Hz; Class I 1400W for ZM-258B, ZM-259, ZM-259B; 1200W for ZM-269B; 800W for ZM-268B, ZM-267, ZM-267B; 750W for other models

Testing procedure and testing location:		
<input checked="" type="checkbox"/>	Testing Laboratory:	TÜV Rheinland /CCIC (Ningbo) Co., Ltd.
Testing location/ address.....:		3F Building C13, R&D Park, No.32 , Lane 299 Guanghua Road, National Hi-Tech Zone, Ningbo, 315048, P. R. China
<input type="checkbox"/>	Associated Testing Laboratory:	N/A
Testing location/ address.....:		
Tested by (name + signature).....:		See cover page
Approved by (name + signature).....:		See cover page
<hr/>		
<input type="checkbox"/>	Testing procedure: TMP	N/A
Testing location/ address.....:		
Tested by (name + signature).....:		
Approved by (name + signature).....:		
<hr/>		
<input type="checkbox"/>	Testing procedure: WMT	N/A
Testing location/ address.....:		
Tested by (name + signature).....:		
Witnessed by (name + signature)		
Approved by (name + signature).....:		
<hr/>		
<input type="checkbox"/>	Testing procedure: SMT	N/A
Testing location/ address.....:		
Tested by (name + signature).....:		
Approved by (name + signature).....:		
Supervised by (name + signature) ...:		
<hr/>		

List of Attachments (including a total number of pages in each attachment):

See cover page

Summary of testing: Pass

ZM-227, ZM-258B, ZM-707B, ZM-267, ZM-259B, ZM-707C, ZM-259B, ZM-269B and ZM-259 were subjected to all the tests, ZM-227B was subjected to the tests of clause 10, 11, 11.Z102 and 13, ZM-707 was subjected to tests of clause 10, 11, 11.Z102 and 19; ZM-200B was subjected to tests of clause 10 and 11.Z102; ZM-206B and ZM-206 were subjected to tests of clause 10, 11 and 11.Z102; ZM-267B, ZM-259, ZM-207 and ZM-208 were subjected to tests of clause 10 and 11.Z102; all models were subjected to construction check. EK1AG2 rev.9 was taken into consideration.

Foreseeable use was considered. Currently neither a safeguard clause procedure has been invoked nor is an increase in accidents known for this/these product(s).

Tests performed (name of test and test clause):

All the tests mentioned above

Testing location:

TÜV Rheinland / CCIC (Ningbo) Co., Ltd.

3F Building C13, R&D Park, No.32 , Lane 299
Guanghua Road, National Hi-Tech Zone, Ningbo,
315048, P. R. China

Summary of compliance with National Differences
List of countries addressed: DE

EUROPEAN GROUP DIFFERENCES

Explanation of used codes: DE=GERMANY

**The product fulfils the requirements of EN 60335-1:2012+A11;
EN 60335-2-9:2003+A1+A2+A12+A13; EN 62233:2008; AfPS GS 2014:01 Par. 3.1 (insert standard number and edition and delete the text in parenthesis or delete the whole sentence if not applicable)**

Copy of marking plate

The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective NCBs that own these marks.



Marking plate for other models were same as the above one except for model name and rated power input.

Marking plate for other models were same as the above one except for model name.







Remark: Manufacture or/and his importer shall ensure product bears label requirements in article 6 and article 8 of the 2014/35/EU relate to name, batch number, post address prior place the product into EU market.

Test item particulars	
Classification of installation and use	Portable appliance
Supply Connection	Type Y attachment (non-detachable cord with plug)
.....	
Possible test case verdicts:	
- test case does not apply to the test object.....	N/A
- test object does meet the requirement	P (Pass)
- test object does not meet the requirement.....	F (Fail)
Testing	
Date of receipt of test item	See cover page
Date (s) of performance of tests	See cover page
General remarks:	
<p>The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory. "(See Enclosure #)" refers to additional information appended to the report. "(See appended table)" refers to a table appended to the report.</p>	
<p>Throughout this report a <input checked="" type="checkbox"/> comma / <input type="checkbox"/> point is used as the decimal separator.</p>	
Manufacturer's Declaration per sub-clause 4.2.5 of IEC 60335-1:	
The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has been provided	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> Not applicable
When differences exist; they shall be identified in the General product information section.	
Name and address of factory (ies)	Same as manufacturer

General product information:

Sandwich maker is intended for household use only. All models are fitted with a fixed thermostat in top cover and a thermal link in bottom enclosure.

Differences between these models refer to below table:

Model name	Rated power input	Shape of heating element	Metal cover on top cover	Detachable working plate
ZM-206	750W		No	No
ZM-206B			Yes	
ZM-207			No	
ZM-207B			Yes	
ZM-208			No	
ZM-208B			Yes	
ZM-201			No	
ZM-227			No	
ZM-227B			Yes	
ZM-202B			Yes	
ZM-228			No	
ZM-228C			Yes	
ZM-200			No	
ZM-200B			Yes	
ZM-228B			No	
ZM-228D	Yes			
ZM-267B	800W		No	Yes
ZM-268B			Yes	
ZM-267			No	
ZM-259	1400W		No	No
ZM-259B			Yes	
ZM-258B			Yes	
ZM-269B	1200W		Yes	Yes
ZM-707	750W		No	No
ZM-707B			Yes	
ZM-707C			Yes	

Remark:

- ZM-259B had four graphic patterns in heating plates, other models only had two graphic patterns in heating plate.
- The cover of ZM-267, ZM-267B, ZM-268B had two open position, other models had only one open position.

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
5	GENERAL CONDITIONS FOR THE TESTS		P
	Tests performed according to clause 5, e.g. nature of supply, sequence of testing, etc.		P
5.2	See Note (IEC 60335-2-9)		P
5.3	If it is evident from the construction of the appliance that the test of one function will produce more favourable results than another, this function is not tested. (IEC 60335-2-9)		N/A
5.6	If two or more cooking functions can be performed simultaneously, they are tested at the same time. (IEC 60335-2-9)		N/A
5.101	Induction hotplates are operated as specified for motor-operated appliances. Other appliances are tested as specified for heating appliances, even if they incorporate motors (IEC 60335-2-9)		N/A
6	CLASSIFICATION		P
6.1	Protection against electric shock: Class 0, 0I, I, II, III.....:	Class I	P
6.2	Protection against harmful ingress of water	IP20	N/A
	Appliances intended for outdoor use shall be at least IPX4 (IEC 60335-2-9)		N/A
7	MARKING AND INSTRUCTIONS		P
7.1	Rated voltage or voltage range (V).....:	AC 220-240V	P
	Symbol for nature of supply, or.....:		N/A
	Rated frequency (Hz)	50/60Hz	P
	Rated power input (W), or	See page 2	P
	Rated current (A)		N/A
	Manufacturer's or responsible vendor's name, trademark or identification mark.....:	NINGBO BAKELON ELECTRICAL APPLIANCE CO., LTD.	P
	Model or type reference.....:	See page 2	P
	Symbol IEC 60417-5172, for class II appliances		N/A
	IP number, other than IPX0.....:		N/A
	Symbol IEC 60417-5180, for class III appliances, unless		N/A
	the appliance is operated by batteries only		N/A
	Do not immerse beyond this level (IEC 60335-2-9)		N/A
	Hot surface (IEC 60335-2-9)		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Symbol IEC 60417-5036, for the enclosure of electrically-operated water valves in external hose-sets for connection of an appliance to the water mains, if the working voltage exceeds extra-low voltage		N/A
7.2	Warning for stationary appliances for multiple supply		N/A
	Warning placed in vicinity of terminal cover		N/A
7.3	Range of rated values marked with the lower and upper limits separated by a hyphen	AC 220-240V	P
	Different rated values marked with the values separated by an oblique stroke		N/A
7.4	Appliances adjustable for different rated voltages, the voltage setting is clearly discernible		N/A
	Requirement met if frequent changes are not required and the rated voltage to which the appliance is to be adjusted is determined from a wiring diagram		N/A
7.5	Appliances with more than one rated voltage or one or more rated voltage ranges, marked with rated input or rated current for each rated voltage or range, unless		N/A
	the power input is related to the arithmetic mean value of the rated voltage range		P
	Relation between marking for upper and lower limits of rated power input or rated current and voltage is clear		N/A
7.6	Correct symbols used		P
	Symbol for nature of supply placed next to rated voltage		N/A
	Symbol for class II appliances placed unlikely to be confused with other marking		N/A
	Units of physical quantities and their symbols according to international standardized system		P
7.7	Connection diagram fixed to appliances to be connected to more than two supply conductors and appliances for multiple supply, unless		N/A
	correct mode of connection is obvious		N/A
7.8	Except for type Z attachment, terminals for connection to the supply mains indicated as follows:		P
	- marking of terminals exclusively for the neutral conductor (letter N)		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	- marking of protective earthing terminals (symbol IEC 60417-5019)		P
	- marking not placed on removable parts		P
7.9	Marking or placing of switches which may cause a hazard		N/A
7.10	Indications of switches on stationary appliances and controls on all appliances by use of figures, letters or other visual means		N/A
	This applies also to switches which are part of a control		N/A
	If figures are used, the off position indicated by the figure 0		N/A
	The figure 0 indicates only OFF position, unless no confusion with the OFF position		N/A
7.11	Indication for direction of adjustment of controls		N/A
7.12	Instructions for safe use provided		P
	Details concerning precautions during user maintenance		P
	The instructions state that:		P
	- the appliance is not to be used by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction	Replaced by EN 60335-2-9/A13	N/A
	- children being supervised not to play with the appliance	Replaced by EN 60335-2-9/A13	N/A
	For a part of class III construction supplied from a detachable power supply unit, the instructions state that the appliance is only to be used with the unit provided		N/A
	Instructions for class III appliances state that it must only be supplied at SELV, unless		N/A
	it is a battery-operated appliance, the battery being charged outside the appliance		N/A
	Appliance with inlet and intended to be immersed for cleaning, instruction sheet including in substance: (IEC 60335-2-9)		N/A
	- remove connector before cleaning		N/A
	- dry appliance inlet before re-use		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	The instructions for use for appliances intended to be used with a connector incorporating a thermostat shall state that only the appropriate connector must be used (IEC 60335-2-9)		N/A
	Instructions for appliances for outdoor use (IEC 60335-2-9):		N/A
	The appliance is suitable for outdoor use (IEC 60335-2-9)		N/A
	The supply cord should be regularly examined for signs of damage, and if the cord is damaged, the appliance must not be used (IEC 60335-2-9)		N/A
	The appliance must be supplied through a residual current device (RCD) having a rated residual operating current not exceeding 30mA (IEC 60335-2-9)		N/A
	The appliance is to be connected to a socket-outlet having an earthing contact (class I) (IEC 60335-2-9)		N/A
	The temperature of accessible surfaces may be high when the appliance is operating (IEC 60335-2-9)		N/A
	If symbol IEC 60417-5041 (DB: 2002-10) is marked on appliances, the instructions shall state that the surfaces are liable to get hot during use (IEC 60335-2-9)		N/A
	The instructions shall state that the appliances are not intended to be operated by means of an external timer or separate remote-control system (IEC 60335-2-9)		P
	Instructions for use		P
	For oven: The temperature of the door or the outer surface may be high when the appliance is operating(IEC 60335-2-9)		N/A
	For toaster: Bread may burn. Therefore toasters must not be used near or below curtains and other combustible materials. They must be watched(IEC 60335-2-9)		N/A
	For barbecue: WARNING: Charcoal or similar combustible fuels must not be used with this appliance. (IEC 60335-2-9)		N/A
	For barbecue: Maximum quantity of water to be poured into the appliance(IEC 60335-2-9)		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	If top surface of a hotplate is of glass-ceramic or similar material and protects live parts, warning : If the surface is cracked, switch off the appliance to avoid the possibility of electric shock (IEC 60335-2-9)		N/A
	For induction hotplates: Metallic objects such as knives, forks, spoons and lids not be placed on the hotplate since they can get hot....(IEC 60335-2-9).		N/A
	For breadmakers: maximum quantities of flour and raising agent that may be used(IEC 60335-2-9)		N/A
7.12.1	Sufficient details for installation supplied		N/A
	For an appliance intended to be permanently connected to the water mains and not connected by a hose-set, this is stated		N/A
7.12.2	Stationary appliances not fitted with means for disconnection from the supply mains having a contact separation in all poles that provide full disconnection under overvoltage category III, the instructions state that means for disconnection must be incorporated in the fixed wiring in accordance with the wiring rules		N/A
7.12.3	Insulation of the fixed wiring in contact with parts exceeding 50 K during clause 11; instructions state that the fixed wiring must be protected		N/A
7.12.4	Instructions for built-in appliances:		N/A
	- dimensions of space		N/A
	- dimensions and position of supporting and fixing		N/A
	- minimum distances between parts and surrounding structure		N/A
	- minimum dimensions of ventilating openings and arrangement		N/A
	- connection to supply mains and interconnection of separate components		N/A
	- allow disconnection of the appliance after installation, by accessible plug or a switch in the fixed wiring, unless		N/A
	a switch complying with 24.3		N/A
7.12.5	Replacement cord instructions, type X attachment with a specially prepared cord		N/A
	Replacement cord instructions, type Y attachment		P
	Replacement cord instructions, type Z attachment		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
7.12.6	Caution in the instructions for appliances incorporating a non-self-resetting thermal cut-out that is reset by disconnection of the supply mains, if this cut-out is required to comply with the standard		N/A
7.12.7	Instructions for fixed appliances stating how the appliance is to be fixed		N/A
7.12.8	Instructions for appliances connected to the water mains:		N/A
	- max. inlet water pressure (Pa)		N/A
	- min. inlet water pressure, if necessary (Pa)		N/A
	Instructions concerning new and old hose-sets for appliances connected to the water mains by detachable hose-sets		N/A
7.13	Instructions and other texts in an official language	German and English version	P
7.14	Marking clearly legible and durable, rubbing test as specified		P
	The height of the triangle used with symbol IEC 60417-5041(DB:2002-10) shall be at least 12mm (IEC 60335-2-9)		N/A
7.15	Markings on a main part		P
	Marking clearly discernible from the outside, if necessary after removal of a cover		P
	For portable appliances, cover can be removed or opened without a tool		N/A
	For stationary appliances, name, trademark or identification mark and model or type reference visible after installation		N/A
	For fixed appliances, name, trademark or identification mark and model or type reference visible after installation according to the instructions		N/A
	Indications for switches and controls placed on or near the components. Marking not on parts which can be positioned or repositioned in such a way that the marking is misleading		N/A
	The marking specified for hot surfaces shall be visible when the appliance is operated as in normal used (IEC 60335-2-9)		N/A
7.16	Marking of a possible replaceable thermal link or fuse link clearly visible with regard to replacing the link		N/A
8	PROTECTION AGAINST ACCESS TO LIVE PARTS		P

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
8.1	Adequate protection against accidental contact with live parts		P
8.1.1	Requirement applies for all positions, detachable parts removed		P
	Lamps behind a detachable cover not removed, if conditions met		N/A
	Insertion or removal of lamps, protection against contact with live parts of the lamp cap		N/A
	Use of test probe B of IEC 61032, with a force not exceeding 1 N: no contact with live parts		P
	Use of test probe B of IEC 61032 through openings, with a force of 20N: no contact with live parts		P
	For toasters having a crumb tray : use of test probe 41 of IEC 61032 : no contact through crumb tray with live parts that are disconnected by double pole switch using (IEC 60335-2-9)		N/A
8.1.2	Use of test probe 13 of IEC 61032, with a force not exceeding 1 N, through openings in class 0 appliances and class II appliances/constructions: no contact with live parts		P
	Test probe 13 also applied through openings in earthed metal enclosures having a non-conductive coating: no contact with live parts		P
8.1.3	For appliances other than class II, use of test probe 41 of IEC 61032, with a force not exceeding 1 N: no contact with live parts of visible glowing heating elements		N/A
8.1.4	Accessible part not considered live if:		N/A
	- safety extra-low a.c. voltage: peak value not exceeding 42.4 V		N/A
	- safety extra-low d.c. voltage: not exceeding 42.4 V		N/A
	- or separated from live parts by protective impedance		N/A
	If protective impedance: d.c. current not exceeding 2 mA, and		N/A
	a.c. peak value not exceeding 0.7 mA		N/A
	- for peak values over 42.4 V up to and including 450 V, capacitance not exceeding 0,1 µF		N/A
	- for peak values over 450 V up to and including 15 kV, discharge not exceeding 45 µC		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	- for peak values over 15kV, the energy in the discharge not exceeding 350 mJ		N/A
8.1.5	Live parts protected at least by basic insulation before installation or assembly:		N/A
	- built-in appliances		N/A
	- fixed appliances		N/A
	- appliances delivered in separate units		N/A
8.2	Class II appliances and constructions constructed so that there is adequate protection against accidental contact with basic insulation and metal parts separated from live parts by basic insulation only		P
	Only possible to touch parts separated from live parts by double or reinforced insulation		P
9	STARTING OF MOTOR-OPERATED APPLIANCES		N/A
	Requirements and tests are specified in part 2 when necessary		N/A
10	POWER INPUT AND CURRENT		P
10.1	Power input at normal operating temperature, rated voltage and normal operation not deviating from rated power input by more than shown in table 1 ..:	(see appended table)	P
	Test carried out at upper and lower limits of the ranges for appliances with one or more rated voltage ranges, unless		N/A
	the rated power input is related to the arithmetic mean value		P
	Power input of induction hotplates measured separately (IEC 60335-2-9)		N/A
10.2	Current at normal operating temperature, rated voltage and normal operation not deviating from rated current by more than shown in table 2	(see appended table)	N/A
	Test carried out at upper and lower limits of the ranges for appliances with one or more rated voltage ranges, unless		N/A
	the rated current is related to the arithmetic mean value of the range		N/A
	Current input of induction hotplates measured separately (IEC 60335-2-9)		N/A
11	HEATING		P
11.1	No excessive temperatures in normal use		P

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Compliance for toasters is also checked by the test of 11. 101 (IEC 60335-2-9)		N/A
11.2	The appliance is held, placed or fixed in position as described.....:	Away from the test corner	P
	Radiant grills and raclette grills that are loaded from the front, rotary grills, ovens, breadmakers, cookers and hotplates are placed with their backs as near as possible to one of the walls of the test corner and away from the other wall (IEC 60335-2-9)		N/A
11.3	Temperature rises, other than of windings, determined by thermocouples		P
	Temperature rises of windings determined by resistance method, unless		N/A
	the windings are non-uniform or it is difficult to make the necessary connections		N/A
	If magnetic field of an induction hotplate unduly influences the results, temperature rises can be determined using platinum resistances or equivalent means (IEC 60335-2-9)		N/A
11.4	Heating appliances operated under normal operation at 1.15 times rated power input (W)	(see appended table)	P
	If the temperature rise limits are exceeded in appliances incorporating motors, transformers or electronic circuits, and if the power input is lower than the rated power input, the test is repeated with the appliance supplied at 1,06 times rated voltage (IEC 60335-2-9)		N/A
11.5	Motor-operated appliances operated under normal operation at most unfavourable voltage between 0.94 and 1.06 times rated voltage (V)		N/A
11.6	Combined appliances operated under normal operation at most unfavourable voltage between 0.94 and 1.06 times rated voltage (V)		N/A
11.7	Tests carried out in compliance with the paragraphs N° 1 to 11 (IEC 60335-2-9)		P
11.8	Temperature rises monitored continuously and not exceeding the values in table 3	(see appended table)	P
	If the temperature rise of a motor winding exceeds the value of table 3, or		N/A
	if there is doubt with regard to classification of insulation,		N/A
	tests of Annex C are carried out		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Sealing compound does not flow out		N/A
	Protective devices do not operate, except		P
	components in protective electronic circuits tested for the number of cycles specified in 24.1.4		N/A
	When an appliance connector incorporates a thermostat, the temperature rise limit for the pins of the inlet does not apply (IEC 60335-2-9)		N/A
	The temperature rise limits of motors, transformers, components of electronic circuit and parts directly influenced by them may be exceeded when the appliance is operated at 1,15 times rated power input (IEC 60335-2-9)		N/A
	Cheese used in sandwich toasting attachments doesn't flow into places where it can give rise to a hazard, such as reducing clearances or creepage distances below the values specified in Clause 29 (IEC 60335-2-9).		N/A
11.101	The toaster in which the bread is inserted through the top are operated for three cycles under normal operation at rated power input. (IEC 60335-2-9).		N/A
	The temperature rise of accessible surfaces of metallic sides that are at a height lower than 25mm below the top surface shall not exceed 90K (IEC 60335-2-9).		N/A
13	LEAKAGE CURRENT AND ELECTRIC STRENGTH AT OPERATING TEMPERATURE		P
13.1	Leakage current not excessive and electric strength adequate		P
	Heating appliances operated at 1.15 times the rated power input (W).....:	(see appended table)	P
	Motor-operated appliances and combined appliances supplied at 1.06 times the rated voltage (V).....:		N/A
	Protective impedance and radio interference filters disconnected before carrying out the tests		N/A
	grill incorporated in oven, oven or grill operated most unfavourable (IEC 60335-2-9).		N/A
13.2	For class 0, class II and class III appliances, leakage current measured by means of the circuit described in figure 4 of IEC 60990		N/A
	For other appliances, a low impedance ammeter may be used		P

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Leakage current measurements	(see appended table)	P
	If earthed metal between live parts and surface of glass-ceramic (or similar) of hotplate, leakage current between live parts and each of vessels in turn connected to earthed metal not exceeding 0,75 mA (IEC 60335-2-9)		N/A
	If no earthed metal between live parts and surface of glass-ceramic (or similar) of hotplate, leakage current between live parts and each of vessels in turn not exceeding 0,25 mA (IEC 60335-2-9)		N/A
13.3	The appliance is disconnected from the supply		P
	Electric strength tests according to table 4.....	(see appended table)	P
	test voltage of 1000V if earthed metal between live parts and surface of glass-ceramic (or similar) of hotplate (IEC 60335-2-9).		N/A
	test voltage of 3000 V if no earthed metal between live parts and surface of glass-ceramic (or similar) of hotplate (IEC 60335-2-9).		N/A
	No breakdown during the tests		P
14	TRANSIENT OVERVOLTAGES		N/A
	Appliances withstand the transient over-voltages to which they may be subjected		N/A
	Clearances having a value less than specified in table 16 subjected to an impulse voltage test, the test voltage specified in table 6	(see appended table)	N/A
	No flashover during the test, unless		N/A
	of functional insulation if the appliance complies with clause 19 with the clearance short-circuited		N/A
15	MOISTURE RESISTANCE		P
15.1	Enclosure provides the degree of moisture protection according to classification of the appliance		N/A
	Compliance checked as specified in 15.1.1, taking into account 15.1.2, followed by the electric strength test of 16.3		N/A
	No trace of water on insulation which can result in a reduction of clearances or creepage distances below values specified in clause 29		N/A
15.1.1	Appliances, other than IPX0, subjected to tests as specified in IEC 60529.....		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Water valves containing live parts in external hoses for connection of an appliance to the water mains tested as specified for IPX7 appliances		N/A
15.1.2	Hand-held appliance turned continuously through the most unfavourable positions during the test		N/A
	Built-in appliances installed according to the instructions		N/A
	Appliances placed or used on the floor or table placed on a horizontal unperforated support		N/A
	Appliances normally fixed to a wall and appliances with pins for insertion into socket-outlets are mounted on a wooden board		N/A
	For IPX3 appliances, the base of wall mounted appliances is placed at the same level as the pivot axis of the oscillating tube		N/A
	For IPX4 appliances, the horizontal centre line of the appliance is aligned with the pivot axis of the oscillating tube, and		N/A
	for appliances normally used on the floor or table, the movement is limited to two times 90° for a period of 5 min, the support being placed at the level of the pivot axis of the oscillating tube		N/A
	Wall-mounted appliances, take into account the distance to the floor stated in the instructions		N/A
	Appliances normally fixed to a ceiling are mounted underneath a horizontal unperforated support, the pivot axis of the oscillating tube located at the level of the underside of the support, and		N/A
	for IPX4 appliances, the movement of the tube is limited to two times 90° from the vertical for a period of 5 min		N/A
	Appliances with type X attachment fitted with a flexible cord as described		N/A
	Detachable parts subjected to the relevant treatment with the main part		N/A
	However, if a part has to be removed for user maintenance and a tool is needed, this part is not removed		N/A
15.2	Spillage of liquid does not affect the electrical insulation		N/A
	Appliances with type X attachment fitted with a flexible cord as described		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Appliances incorporating an appliance inlet tested with or without an connector, whichever is most unfavourable		N/A
	Detachable parts are removed		N/A
	Overfilling test; quantity : as specified in IEC 60335-2-9		N/A
	Ovens: 0.5l (IEC 60335-2-9)		N/A
	Hotplates and cookers : 0.5l ,15s (IEC 60335-2-9)		N/A
	Hotplates incorporate a thermal control : 0.02l (IEC 60335-2-9)		N/A
	Hotplates having ventilating opening : 0.2l (IEC 60335-2-9)		N/A
	Other appliances : 0.1l/100cm ² 1min (IEC 60335-2-9)		N/A
	The appliance withstands the electric strength test of 16.3		N/A
	No trace of water on insulation that can result in a reduction of clearances or creepage distances below values specified in clause 29		N/A
15.101	Appliances to be immersed in water for cleaning sufficiently protected against effects of immersion (IEC 60335-2-9)		N/A
	Testing conditions and scheduling as specified		N/A
	No trace of water on insulation which can result in reduction of creepage distances and clearance below values specified in 29		N/A
15.3	Appliances proof against humid conditions	The temperature: 25°C; RH: 93%	P
	Checked by test Cab: Damp heat steady state in IEC 60068-2-78		P
	Detachable parts removed and subjected, if necessary, to the humidity test with the main part		P
	Humidity test for 48 h in a humidity cabinet	For 48h	P
	Reassembly of those parts that may have been removed		P
	The appliance withstands the tests of clause 16		P
16	LEAKAGE CURRENT AND ELECTRIC STRENGTH		P
16.1	Leakage current not excessive and electric strength adequate		P

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Protective impedance disconnected from live parts before carrying out the tests		N/A
	Tests carried out at room temperature and not connected to the supply		P
	For hotplates, the tests are carried out with a vessel as specified for normal operation placed on each cooking zone (IEC 60335-2-9).		N/A
16.2	Single-phase appliances: test voltage 1.06 times rated voltage (V)		P
	Three-phase appliances: test voltage 1.06 times rated voltage divided by $\sqrt{3}$ (V)		N/A
	Leakage current measurements	(see appended table)	P
	Limit values doubled if:		N/A
	- all controls have an off position in all poles, or		N/A
	- the appliance has no control other than a thermal cut-out, or		N/A
	- all thermostats, temperature limiters and energy regulators do not have an off position, or		N/A
	- the appliance has radio interference filters		N/A
	With the radio interference filters disconnected, the leakage current do not exceed limits specified	(see appended table)	N/A
	If earthed metal between live parts and surface of glass-ceramic (or similar) of hotplate, leakage current between live parts and each of vessels in turn connected to earthed metal not exceeding 0,75 mA (IEC 60335-2-9)		N/A
	If no earthed metal between live parts and surface of glass-ceramic (or similar) of hotplate, leakage current between live parts and each of vessels in turn not exceeding 0,25 mA (IEC 60335-2-9)		N/A
16.3	Electric strength tests according to table 7.....	(see appended table)	P
	Test voltage applied between the supply cord and inlet bushing and cord guard and cord anchorage as specified	(see appended table)	P
	test voltage of 1250 V if earthed metal between live parts and surface of glass-ceramic (or similar) of hotplate. (IEC 60335-2-9)		N/A
	test voltage of 3000 V if no earthed metal between live parts and surface of glass-ceramic (or similar) of hotplate. (IEC 60335-2-9)		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	No breakdown during the tests		P
17	OVERLOAD PROTECTION OF TRANSFORMERS AND ASSOCIATED CIRCUITS		N/A
	No excessive temperatures in transformer or associated circuits in event of short-circuits likely to occur in normal use	(see appended table)	N/A
	Appliance supplied with 1.06 or 0.94 times rated voltage under the most unfavourable short-circuit or overload likely to occur in normal use (V)		N/A
	Basic insulation is not short-circuited		N/A
	Temperature rise of insulation of the conductors of safety extra-low voltage circuits not exceeding the relevant value specified in table 3 by more than 15 K		N/A
	Temperature of the winding not exceeding the value specified in table 8		N/A
	However, limits do not apply to fail-safe transformers complying with sub-clause 15.5 of IEC 61558-1		N/A
18	ENDURANCE		N/A
	Requirements and tests are specified in part 2 when necessary		N/A
19	ABNORMAL OPERATION		P
19.1	The risk of fire, mechanical damage or electric shock under abnormal or careless operation obviated		P
	Electronic circuits so designed and applied that a fault will not render the appliance unsafe	(see appended table)	N/A
	Appliances incorporating heating elements subjected to the tests of 19.2 and 19.3, and		P
	if the appliance also has a control that limit the temperature during clause 11 it is subjected to the test of 19.4, and		P
	if applicable, to the test of 19.5		P
	Appliances incorporating PTC heating elements are also subjected to the test of 19.6		N/A
	Appliances incorporating motors subjected to the tests of 19.7 to 19.10, as applicable		N/A
	Appliances incorporating electronic circuits subjected to the tests of 19.11 and 19.12, as applicable		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Appliances incorporating contactors or relays subjected to the test of 19.14, being carried out before the tests of 19.11		N/A
	Appliances incorporating voltage selector switches subjected to the test of 19.15		N/A
	Unless otherwise specified, the tests are continued until a non-self-resetting thermal cut-out operates, or		P
	until steady conditions are established		P
	If a heating element or intentionally weak part becomes open-circuited, the relevant test is repeated on a second sample		N/A
	Tests of 19.4 and 19.5 are only applicable to: -breadmakers, contact grills, food dehydrators - ovens, roasters, hotplates, cookers, rotary grills if they incorporate a timer or if their instructions indicate a cooking operation longer than 1h (IEC 60335-2-9)		P
	Toasters are subjected to the tests 19.101 and 19.102 (IEC 60335-2-9)		N/A
	Induction hotplates are subjected to the tests 19.103 and 19.104 (IEC 60335-2-9)		N/A
19.2	Test of appliances with heating elements with restricted heat dissipation; test voltage (V), power input of 0.85 times rated power input (W)	Test of clause 19.3 is more unfavourable	P
	Radiant grills, raclette grills that are loaded from the front , rotary grills, ovens, hotplates and cookers are placed as near as possible to the walls of the test corner (IEC 60335-2-9)		N/A
	They are tested empty with lids open or closed whichever is the more unfavourable (IEC 60335-2-9)	With lid closed	P
	Hotplates are operated without a vessel and with the controls adjusted to the highest setting (IEC 60335-2-9)		N/A
	Induction hotplates are operated under conditions of clause 11 but with empty vessels, controls adjusted to the highest setting (IEC 60335-2-9)		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Cookers are only tested with the heating unit that results in the most unfavourable conditions, their controls adjusted to the highest setting. However ovens are operated if they do not have an indicating lamp to show when they are switched on, controls adjusted to the highest setting (IEC 60335-2-9)		N/A
19.3	Test of 19.2 repeated; test voltage (V), power input of 1.24 times rated power input (W)	(see appended table)	P
19.4	Test conditions as in clause 11, any control limiting the temperature during tests of clause 11 short-circuited		P
	Air-circulating fans of food dehydrators disconnected (IEC 60335-2-9)		N/A
19.5	Test of 19.4 repeated on Class 0I and I appliances with tubular sheathed or embedded heating elements. No short-circuiting, but one end of the element connected to the sheath	Thermal link and thermostat were located at different polarities of heating element.	P
	The test repeated with reversed polarity and the other end of the heating element connected to the sheath		P
	The test is not carried out on appliances intended to be permanently connected to fixed wiring and on appliances where an all-pole disconnection occurs during the test of 19.4		N/A
19.6	Appliances with PTC heating elements tested at rated voltage, establishing steady conditions		N/A
	The working voltage of the PTC heating element is increased by 5% and the appliance is operated until steady conditions are re-established. The voltage is then increased in similar steps until 1.5 times working voltage or until the PTC heating element ruptures (V)		N/A
19.7	Stalling test by locking the rotor if the locked rotor torque is smaller than the full load torque, or		N/A
	locking moving parts of other appliances		N/A
	Locked rotor, capacitors open-circuited one at a time		N/A
	Test repeated with capacitors short-circuited one at a time, unless		N/A
	capacitor is of class P2 of IEC 60252-1		N/A
	Appliances with timer or programmer supplied with rated voltage for each of the tests, for a period equal to the maximum period allowed.....		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Other appliances supplied with rated voltage for a period as specified		N/A
	Winding temperatures not exceeding values specified in table 8.....	(see appended table)	N/A
19.8	Multi-phase motors operated at rated voltage with one phase disconnected		N/A
19.9	Running overload test on appliances incorporating motors intended to be remotely or automatically controlled or liable to be operated continuously		N/A
	Motor-operated and combined appliances for which 30.2.3 is applicable and that use overload protective devices relying on electronic circuits to protect the motor windings, are also subjected to the test		N/A
	Winding temperatures not exceeding values as specified	(see appended table)	N/A
19.10	Series motor operated at 1.3 times rated voltage for 1 min (V).....		N/A
	During the test, parts not being ejected from the appliance		N/A
19.11	Electronic circuits, compliance checked by evaluation of the fault conditions specified in 19.11.2 for all circuits or parts of circuits, unless		N/A
	they comply with the conditions specified in 19.11.1		N/A
	Appliances incorporating an electronic circuit that relies upon a programmable component to function correctly, subjected to the test of 19.11.4.8, unless		N/A
	restarting does not result in a hazard		N/A
	Appliances having a device with an off position obtained by electronic disconnection, or a device placing the appliance in a stand-by mode, subjected to the tests of 19.11.4		N/A
	If the safety of the appliance under any of the fault conditions depends on the operation of a miniature fuse-link complying with IEC 60127, the test of 19.12 is carried out		N/A
	During and after each test the following is checked:		N/A
	- the temperature of the windings do not exceed the values specified in table 8		N/A
	- the appliance complies with the conditions specified in 19.13		N/A
	- any current flowing through protective impedance not exceeding the limits specified in 8.1.4		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	If a conductor of a printed board becomes open-circuited, the appliance is considered to have withstood the particular test, provided both of the following conditions are met:		N/A
	- the base material of the printed circuit board withstands the test of Annex E		N/A
	- any loosened conductor does not reduce clearance or creepage distances between live parts and accessible metal parts below the values specified in clause 29		N/A
19.11.1	Fault conditions a) to g) in 19.11.2 are not applied to circuits or parts of circuits meeting both of the following conditions:		N/A
	- the electronic circuit is a low-power circuit, that is, the maximum power at low-power points does not exceed 15 W according to the tests specified		N/A
	- the protection against electric shock, fire hazard, mechanical hazard or dangerous malfunction of other parts of the appliance does not rely on the correct functioning of the electronic circuit		N/A
19.11.2	Fault conditions applied one at a time, the appliance operating under conditions specified in clause 11, but supplied at rated voltage, duration of the tests as specified:		N/A
	a) short circuit of functional insulation if clearances or creepage distances are less than the values specified in clause 29		N/A
	b) open circuit at the terminals of any component		N/A
	c) short circuit of capacitors, unless		N/A
	they comply with IEC 60384-14		N/A
	d) short circuit of any two terminals of an electronic component, other than integrated circuits		N/A
	This fault condition is not applied between the two circuits of an optocoupler		N/A
	e) failure of triacs in the diode mode		N/A
	f) failure of microprocessors and integrated circuits		N/A
	g) failure of an electronic power switching device		N/A
	Each low power circuit is short-circuited by connecting the low-power point to the pole of the supply source from which the measurements were made		N/A
19.11.3	If the appliance incorporates a protective electronic circuit which operates to ensure compliance with clause 19, the relevant test is repeated with a single fault simulated, as indicated in a) to g) of 19.11.2		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
19.11.4	Appliances having a device with an off position obtained by electronic disconnection, or		N/A
	a device that can be placed in the stand-by mode,		N/A
	subjected to the tests of 19.11.4.1 to 19.11.4.7, the device being set in the off position or in the stand-by mode		N/A
	Appliances incorporating a protective electronic circuit subjected to the tests of 19.11.4.1 to 19.11.4.7, the tests being carried out after the protective electronic circuit has operated, except that		N/A
	appliances operated for 30 s or 5 min during the test of 19.7 are not subjected to the tests for electromagnetic phenomena.		N/A
	Surge protective devices disconnected, unless		N/A
	They incorporate spark gaps		N/A
19.11.4.1	The appliance is subjected to electrostatic discharges in accordance with IEC 61000-4-2, test level 4		N/A
19.11.4.2	The appliance is subjected to radiated fields in accordance with IEC 61000-4-3, test level 3		N/A
19.11.4.3	The appliance is subjected to fast transient bursts in accordance with IEC 61000-4-4, test level 3 or 4 as specified		N/A
19.11.4.4	The power supply terminals of the appliance subjected to voltage surges in accordance with IEC 61000-4-5, test level 3 or 4 as specified		N/A
	Earthed heating elements in class I appliances disconnected		N/A
19.11.4.5	The appliance is subjected to injected currents in accordance with IEC 61000-4-6, test level 3		N/A
19.11.4.6	Appliances having a rated current not exceeding 16 A are subjected to the Class 3 voltage dips and interruptions in accordance with IEC 61000-4-11		N/A
	Appliances having a rated current exceeding 16 A are subjected to the Class 3 voltage dips and interruptions in accordance with IEC 61000-4-34		N/A
19.11.4.7	The appliance is subjected to mains signals in accordance with IEC 61000-4-13, test level class 2		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
19.11.4.8	The appliance is supplied at rated voltage and operated under normal operation. After 60s the power supply is reduced to a level such that the appliance ceases to respond or parts controlled by the programmable component cease to operate		N/A
	The appliance continues to operate normally, or		N/A
	requires a manual operation to restart		N/A
19.12	If the safety of the appliance for any of the fault conditions specified in 19.11.2 depends on the operation of a miniature fuse-link complying with IEC 60127, the test is repeated, measuring the current flowing through the fuse-link; measured current (A); rated current of the fuse-link (A).....:		N/A
19.13	During the tests the appliance does not emit flames, molten metal, poisonous or ignitable gas in hazardous amounts		P
	Temperature rises not exceeding the values shown in table 9	(see appended table)	P
	Compliance with clause 8 not impaired		P
	If the appliance can still be operated it complies with 20.2		N/A
	Insulation, other than of class III appliances or class III constructions that do not contain live parts, withstands the electric strength test of 16.3, the test voltage as specified in table 4:		P
	- basic insulation (V)	1000V/1min	P
	- supplementary insulation (V)	Covered by reinforced insulation	P
	- reinforced insulation (V)	3000V/1min	P
	After operation or interruption of a control, clearances and creepage distances across the functional insulation withstand the electric strength test of 16.3, the test voltage being twice the working voltage		P
	The appliance does not undergo a dangerous malfunction, and		P
	no failure of protective electronic circuits, if the appliance is still operable		N/A
	Appliances tested with an electronic switch in the off position, or in the stand-by mode:		N/A
	- do not become operational, or		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	- if they become operational, do not result in a dangerous malfunction during or after the tests of 19.11.4		N/A
	If the appliance contains lids or doors that are controlled by one or more interlocks, one of the interlocks may be released provided that:		N/A
	- the lid or door does not move automatically to an open position when the interlock is released, and		N/A
	- the appliance does not start after the cycle in which the interlock was released		N/A
	During the test of 19.102 any flame or smoke from the bread are ignored (IEC 60335-2-9)		N/A
	Temperature rise of the windings of induction hotplates not exceeding the values specified in 19.7 (IEC 60335-2-9)		N/A
19.14	Appliances operated under the conditions of clause 11, any contactor or relay contact operating under the conditions of clause 11 being short-circuited		N/A
	For a relay or contactor with more than one contact, all contacts are short-circuited at the same time		N/A
	A relay or contactor operating only to ensure the appliance is energized for normal use is not short-circuited		N/A
	If more than one relay or contactor operates in clause 11, they are short-circuited in turn		N/A
19.15	For appliances with a mains voltage selector switch, the switch is set to the lowest rated voltage position and the highest value of rated voltage is applied		N/A
19.101	Toasters operated at rated power input and under normal operation, but without bread, for six cycles of operation, test repeated 500 times (IEC 60335-2-9)		N/A
	The mechanism operates satisfactorily and no sustained arcing occurs. (IEC 60335-2-9)		N/A
19.102	Toasters: test with the ejector mechanism locked (IEC 60335-2-9)		N/A
19.103	Induction hotplates operated with the specified steel disk placed on the centre of the cooking zone (IEC 60335-2-9)		N/A
19.104	Induction hotplates operated with thermal controls short-circuited or rendered inoperative in turn: The temperature rise of the oil shall not exceed 270 K (IEC 60335-2-9).		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
20	STABILITY AND MECHANICAL HAZARDS		P
20.1	Appliances having adequate stability		P
	Tilting test through an angle of 10°, appliance placed on an inclined plane/horizontal support, not connected to the supply mains; appliance does not overturn		P
	Tilting test repeated on appliances with heating elements, angle of inclination increased to 15°		P
	Possible heating test in overturned position; temperature rise does not exceed values shown in table 9		N/A
20.2	Moving parts adequately arranged or enclosed as to provide protection against personal injury	No moving parts	N/A
	Protective enclosures, guards and similar parts are non-detachable, and		N/A
	have adequate mechanical strength		N/A
	Enclosures that can be opened by overriding an interlock are considered to be detachable parts		N/A
	Self-resetting thermal cut-outs and overcurrent protective devices not causing a hazard by unexpected closure		N/A
	Not possible to touch dangerous moving parts with the test probe described		N/A
20.101	Oven with horizontal hinged door: successful tilting test in conditions as specified, if relevant (weight of 3,5 kg) (IEC 60335-2-9).		N/A
21	MECHANICAL STRENGTH		P
21.1	Appliance has adequate mechanical strength and is constructed as to withstand rough handling		P
	Checked by applying 3 blows to every point of the enclosure like to be weak, in accordance with test Ehb of IEC 60068-2-75, spring hammer test, with an impact energy of 0,5 J	(see appended table)	P
	The appliance shows no damage impairing compliance with this standard, and		P
	compliance with 8.1, 15.1 and clause 29 not impaired		P
	If doubt, supplementary or reinforced insulation subjected to the electric strength test of 16.3		N/A
	If necessary, repetition of groups of three blows on a new sample		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	For appliances intended for outdoor use, the impact energy is 0.7J (IEC 60335-2-9)		N/A
	Appliances incorporates visibly glowing heating elements located at the top of the oven and accessible to the test probe 41 of IEC 61032 (IEC 60335-2-9)		N/A
	For hotplates with surfaces of glass-ceramic or similar, three blows applied to parts surfaces not exposed to the test of 21.101, impact energy 0,70J ± 0,05 J. (IEC 60335-2-9).		N/A
21.2	Accessible parts of solid insulation having strength to prevent penetration by sharp implements		P
	Test not applicable if the thickness of supplementary insulation is at least 1 mm and reinforced insulation at least 2 mm		P
	The insulation is tested as specified, and does withstand the electric strength test of 16.3		N/A
21.101	Surfaces of hotplates of glass-ceramic or similar material withstand the stresses liable to occur in normal use, under test conditions as specified (IEC 60335-2-9).		N/A
	After the tests, surface of hotplate not broken).		N/A
	Withstand dielectric strength test of 16.3		N/A
22	CONSTRUCTION		P
22.1	Appliance marked with the first numeral of the IP system, relevant requirements of IEC 60529 are fulfilled	IP20	N/A
22.2	Stationary appliance: means to ensure all-pole disconnection from the supply being provided:		N/A
	- a supply cord fitted with a plug, or		N/A
	- a switch complying with 24.3, or		N/A
	- a statement in the instruction sheet that a disconnection incorporated in the fixed wiring is to be provided, or		N/A
	- an appliance inlet		N/A
	Single-pole switches and single-pole protective devices for the disconnection of heating elements in single-phase, permanently connected class 01 and class I appliances, connected to the phase conductor		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
22.3	Appliance provided with pins: no undue strain on socket-outlets		N/A
	Applied torque not exceeding 0.25 Nm		N/A
	Pull force of 50N to each pin after the appliance has being placed in the heating cabinet; when cooled to room temperature the pins are not displaced by more than 1mm		N/A
	Each pin subjected to a torque of 0.4Nm; the pins are not rotating, unless		N/A
	rotating does not impair compliance with this standard		N/A
22.4	Appliance for heating liquids and appliance causing undue vibration not provided with pins for insertion into socket-outlets		N/A
22.5	No risk of electric shock when touching the pins of the plug, for appliances having a capacitor with rated capacitance exceeding 0,1µF, the appliance being disconnected from the supply at the instant of voltage peak		N/A
	Voltage not exceeding 34 V (V).....:		N/A
22.6	Electrical insulation not affected by condensing water or leaking liquid		N/A
	Electrical insulation of Class II appliances not affected if a hose ruptures or seal leaks		N/A
	In case of doubt, test as described		N/A
22.7	Adequate safeguards against the risk of excessive pressure in appliances containing liquid or gases or having steam-producing devices		N/A
22.8	Electrical connections not subject to pulling during cleaning of compartments to which access can be gained without the aid of a tool, and that are likely to be cleaned in normal use		N/A
22.9	Insulation, internal wiring, windings, commutators and slip rings not exposed to oil, grease or similar substances, unless		P
	the substance has adequate insulating properties		N/A
22.10	Not possible to reset voltage-maintained non-self-resetting thermal cut-outs by the operation of an automatic switching device incorporated within the appliance, if:		N/A
	- a non-self-resetting thermal cut-out is required by the standard, and		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	- a voltage maintained non-self-resetting thermal cut-out is used to meet it		N/A
	Non-self-resetting thermal motor protectors have a trip-free action, unless		N/A
	they are voltage maintained		N/A
	Reset buttons of non-self-resetting controls so located or protected that accidental resetting is unlikely		N/A
22.11	Reliable fixing of non-detachable parts that provide the necessary degree of protection against electric shock, moisture or contact with moving parts		P
	Obvious locked position of snap-in devices used for fixing such parts		N/A
	No deterioration of the fixing properties of snap-in devices used in parts that are likely to be removed during installation or servicing		N/A
	Tests as described	Pull and push: 50 N to all parts of the appliance	P
22.12	Handles, knobs etc. fixed in a reliable manner		P
	Fixing in wrong position of handles, knobs etc. indicating position of switches or similar components not possible		P
	Axial force 15 N applied to parts, the shape being so that an axial pull is unlikely to be applied		N/A
	Axial force 30 N applied to parts, the shape being so that an axial pull is likely to be applied	For handle	P
22.13	Unlikely that handles, when gripped as in normal use, make the operator's hand touch parts having a temperature rise exceeding the value specified for handles which are held for short periods only		P
22.14	No ragged or sharp edges creating a hazard for the user in normal use, or during user maintenance		P
	No exposed pointed ends of self-tapping screws or other fasteners, likely to be touched by the user in normal use or during user maintenance		P
22.15	Storage hooks and the like for flexible cords smooth and well rounded		N/A
22.16	Automatic cord reels cause no undue abrasion or damage to the sheath of the flexible cord, no breakage of conductors strands and no undue wear of contacts		N/A
	Cord reel tested with 6000 operations, as specified		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Electric strength test of 16.3, voltage of 1000 V applied		N/A
22.17	Spacers not removable from the outside by hand or by means of a screwdriver or a spanner		N/A
22.18	Current-carrying parts and other metal parts resistant to corrosion		P
22.19	Driving belts not relied upon to provide the required level of insulation, unless		N/A
	constructed to prevent inappropriate replacement		N/A
22.20	Direct contact between live parts and thermal insulation effectively prevented, unless		P
	material used is non-corrosive, non-hygroscopic and non-combustible		N/A
22.21	Wood, cotton, silk, ordinary paper and fibrous or hygroscopic material not used as insulation, unless		P
	impregnated		N/A
	This requirement does not apply to magnesium oxide and mineral ceramic fibres used for the electrical insulation of heating elements		N/A
22.22	Appliances not containing asbestos		P
22.23	Oils containing polychlorinated biphenyl (PCB) not used		P
22.24	Bare heating elements, except in class III appliances or class III constructions that do not contain live parts, adequately supported		N/A
	Heating elements constructed or supported so they are unlikely to become displaced in normal use. (IEC 60335-2-9)		P
	In case of rupture, the heating conductor is unlikely to come in contact with accessible metal parts		N/A
22.25	Sagging heating conductors, except in class III appliances or class III constructions that do not contain live parts, cannot come into contact with accessible metal parts		N/A
22.26	For class III constructions the insulation between parts operating at safety extra-low voltage and other live parts complies with the requirements for double or reinforced insulation		N/A
22.27	Parts connected by protective impedance separated by double or reinforced insulation		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
22.28	Metal parts of Class II appliances conductively connected to gas pipes or in contact with water, separated from live parts by double or reinforced insulation		N/A
22.29	Class II appliances permanently connected to fixed wiring so constructed that the required degree of access to live parts is maintained after installation		N/A
22.30	Parts serving as supplementary or reinforced insulation fixed so that they cannot be removed without being seriously damaged, or		P
	so constructed that they cannot be replaced in an incorrect position, and so that if they are omitted, the appliance is rendered inoperable or manifestly incomplete		P
22.31	Neither clearances nor creepage distances over supplementary and reinforced insulation reduced below values specified in clause 29 as a result of wear		P
	Neither clearances nor creepage distances between live parts and accessible parts reduced below values for supplementary insulation if wires, screws etc. become loose		P
22.32	Supplementary and reinforced insulation constructed or protected against pollution so that clearances or creepage distances are not reduced below the values in clause 29		P
	Supplementary insulation of natural or synthetic rubber resistant to ageing, or arranged and dimensioned so that creepage distances are not reduced below values specified in 29.2		N/A
	Ceramic material not tightly sintered, similar materials or beads alone not used as supplementary or reinforced insulation		N/A
	Insulating material in which heating conductors are embedded is considered to be basic insulation, not reinforced insulation		N/A
	Oxygen bomb test at 70 °C for 96 h and 16 h at room temperature		N/A
22.33	Conductive liquids that are or may become accessible in normal use and conductive liquids that are in contact with unearthed accessible metal parts are not in direct contact with live parts		P
	Electrodes not used for heating liquids		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	For class II constructions, conductive liquids that are or may become accessible in normal use and conductive liquids that are in contact with unearthed accessible metal parts, not in direct contact with basic or reinforced insulation, unless		N/A
	the reinforced insulation consists of at least 3 layers		N/A
	For class II constructions, conductive liquids which are in contact with live parts, not in direct contact with reinforced insulation, unless		N/A
	the reinforced insulation consists of at least 3 layers		N/A
	An air layer not used as basic or supplementary insulation in a double insulation system if likely to be bridged by leaking liquid		N/A
22.34	Shafts of operating knobs, handles, levers etc. not live, unless		P
	the shaft is not accessible when the part is removed		N/A
22.35	For other than class III constructions, handles, levers and knobs, held or actuated in normal use, not becoming live in the event of a failure of basic insulation		P
	Such parts being of metal, and their shafts or fixings are likely to become live in the event of a failure of basic insulation, are either adequately covered by insulation material or their accessible parts are separated from their shafts or fixings by supplementary insulation		N/A
	This requirement does not apply to handles, levers and knobs on stationary appliances, other than those of electrical components, provided they are reliably connected to an earthing terminal or earthing contact, or separated from live parts by earthed metal		N/A
	Insulating material covering metal handles, levers and knobs withstand the electric strength test of 16.3 for supplementary insulation		N/A
22.36	For appliances other than class III, handles continuously held in the hand in normal use so constructed that when gripped as in normal use, the operators hand is not likely to touch metal parts, unless		N/A
	they are separated from live parts by double or reinforced insulation		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
22.37	Capacitors in Class II appliances not connected to accessible metal parts and their casings, if of metal, separated from accessible metal parts by supplementary insulation, unless		N/A
	the capacitors comply with 22.42		N/A
22.38	Capacitors not connected between the contacts of a thermal cut-out		N/A
22.39	Lamp holders used only for the connection of lamps		N/A
22.40	Motor-operated appliances and combined appliances intended to be moved while in operation, or having accessible moving parts, fitted with a switch to control the motor. The actuating member of the switch being easily visible and accessible		N/A
	If the appliance cannot operate continuously, automatically or remotely without giving rise to a hazard, appliances for remote operation being fitted with a switch for stopping the operation. The actuating member of the switch being easily visible and accessible		N/A
22.41	No components, other than lamps, containing mercury		P
22.42	Protective impedance consisting of at least two separate components		N/A
	Values specified in 8.1.4 not exceeded if any one of the components are short-circuited or open-circuited		N/A
	Resistors checked by the test of 14.1 a) in IEC 60065		N/A
	Capacitors checked by the tests for class Y capacitors in IEC 60384-14		N/A
22.43	Appliances adjustable for different voltages, accidental changing of the setting of the voltage unlikely to occur		N/A
22.44	Appliances not having an enclosure that is shaped or decorated like a toy		P
22.45	When air is used as reinforced insulation, clearances not reduced below the values specified in 29.1.3 due to deformation as a result of an external force applied to the enclosure		P
22.46	For programmable protective electronic circuits used to ensure compliance with the standard, the software contains measures to control the fault/error conditions in table R.1		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Software that contains measures to control the fault/error conditions specified in table R.2 is to be specified in parts 2 for particular constructions or to address specific hazards		N/A
	These requirements are not applicable to software used for functional purpose or compliance with clause 11		N/A
22.47	Appliances connected to the water mains withstand the water pressure expected in normal use		N/A
	No leakage from any part, including any inlet water hose		N/A
22.48	Appliances connected to the water mains constructed to prevent backsiphonage of non-potable water		N/A
22.49	For remote operation, the duration of operation is to be set before the appliance can be started, unless		N/A
	the appliance switches off automatically or can operate continuously without hazard		N/A
22.50	Controls incorporated in the appliance take priority over controls actuated by remote operation		N/A
22.51	There is a control on the appliance manually adjusted to the setting for remote operation before the appliance can be operated in this mode		N/A
	There is a visual indication showing that the appliance is adjusted for remote operation		N/A
	These requirements not necessary on appliances that can operate as follows, without giving rise to a hazard:		N/A
	- continuously, or		N/A
	- automatically, or		N/A
	- remotely		N/A
22.52	Socket-outlets on appliances accessible to the user in accordance with the socket-outlet system used in the country in which the appliance is sold		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
22.101	Radiant grills: no timer that is intended to delay the operation of a heating element (IEC 60335-2-9)		N/A
	Unless having a thermostat and being incorporated in an oven or other compartment, (IEC 60335-2-9)		N/A
22.102	Barbecue shall not be provided with bare heating elements (IEC 60335-2-9)		N/A
	Oven: heating elements with bare conductors at the top only (IEC 60335-2-9)		N/A
22.103	Oven vents constructed so that moisture or grease cannot reduce the clearances and creepage distances. (IEC 60335-2-9)		N/A
22.104	Ovens constructed so that shelves can easily slide in the supports and do not fall out of position when the sides are displaced as much as possible. (IEC 60335-2-9)		N/A
22.105	Appliances have not openings on the underside that would allow small items to penetrate and touch live parts. (IEC 60335-2-9)		P
	Distance measured between the supporting surface and live parts through openings (IEC 60335-2-9)		P
	Distance requested as specified: (IEC 60335-2-9)		P
22.106	Grills and barbecues constructed so that their heating elements are fixed in position or prevented from operating when they are not in their normal position of use. (IEC 60335-2-9)		N/A
22.107	Hotplate constructed so that heating elements are prevented from rotating about a vertical axis and are adequately supported in all positions of adjustment of their supports. (IEC 60335-2-9)		N/A
22.108	Hotplate constructed so that inadvertent operation of touch controls is unlikely if this could give rise to a hazardous situation due to spillage of liquids or damp cloth placed on the control panel, and complies with test as specified... (IEC 60335-2-9)		N/A
22.109	Hotplate incorporating touch controls constructed so that at least two manual operations are requested to switch on a heating element but only one to switch it off..... (IEC 60335-2-9)		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
22.110	Induction hotplates constructed so that they can only be operated with a suitable vessel placed on the cooking zone. (IEC 60335-2-9)		N/A
	Temperature rise of iron not exceeding 35K (IEC 60335-2-9)		N/A
22.111	Heating element in breadmakers located so they are not exposed to dough that they may rise over the edge of the dough container during normal use of the appliance (IEC 60335-2-9)		N/A
22.112	Reconnection of the power supply to a breadmaker after an interruption shall not result in a fire due to an extended heating period. (IEC 60335-2-9)		N/A
	All batteries are removed and the breadmaker is supplied at rated voltage and operated in heating mode without load (IEC 60335-2-9)		N/A
	The appliance shall eventually require a manual operation to restart it..... (IEC 60335-2-9)		N/A
23	INTERNAL WIRING		P
23.1	Wireways smooth and free from sharp edges		P
	Wires protected against contact with burrs, cooling fins etc.		P
	Wire holes in metal well-rounded or provided with bushings		P
	Wiring effectively prevented from coming into contact with moving parts		N/A
23.2	Beads etc. on live wires cannot change their position, and are not resting on sharp edges		N/A
	Beads inside flexible metal conduits contained within an insulating sleeve		N/A
23.3	Electrical connections and internal conductors movable relatively to each other not exposed to undue stress		P
	Flexible metallic tubes not causing damage to insulation of conductors		P
	Open-coil springs not used		P
	Adequate insulating lining provided inside a coiled spring, the turns of which touch one another		P
	No damage after 10 000 flexings for conductors flexed during normal use, or		P
	100 flexings for conductors flexed during user maintenance		P

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Electric strength test of 16.3, 1000 V between live parts and accessible metal parts		P
	Not more than 10% of the strands of any conductor broken, and		P
	not more than 30% for wiring supplying circuits that consume no more than 15W		N/A
	Appliance with 2 stop positions: 10000 flexings made with moving part fully opened (IEC 60335-2-9)		N/A
23.4	Bare internal wiring sufficiently rigid and fixed		N/A
23.5	The insulation of internal wiring subjected to the supply mains voltage withstanding the electrical stress likely to occur in normal use		P
	Basic insulation electrically equivalent to the basic insulation of cords complying with IEC 60227 or IEC 60245, or		N/A
	no breakdown when a voltage of 2000 V is applied for 15 min between the conductor and metal foil wrapped around the insulation		P
23.6	Sleeving used as supplementary insulation on internal wiring retained in position by clamping at both ends, or		P
	be such that it can only be removed by breaking or cutting		P
23.7	The colour combination green/yellow only used for earthing conductors		P
23.8	Aluminium wires not used for internal wiring		P
23.9	Stranded conductors not consolidated by soldering where they are subjected to contact pressure, unless		P
	the contact pressure is provided by spring terminals		N/A
23.10	The insulation and sheath of internal wiring, incorporated in external hoses for the connection of an appliance to the water mains, at least equivalent to that of light polyvinyl chloride sheathed flexible cord (60227 IEC 52)		N/A
24	COMPONENTS		P
24.1	Components comply with safety requirements in relevant IEC standards		P
	List of components	(see appended table)	P

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	If components have not been tested and found to comply with relevant IEC standard for the number of cycles specified, they are tested in accordance with 24.1.1 to 24.1.9		P
	For components mentioned in 24.1.1 to 24.1.9 no additional tests specified in the relevant component standard are necessary other than those specified in 24.1.1 to 24.1.9		P
	Components not tested and found to comply with relevant IEC standard and components not marked or not used in accordance with its marking, tested under the conditions occurring in the appliance		P
	Lampholders and starterholders that have not being tested and found to comply with the relevant IEC standard, tested as a part of the appliance and additionally according to the gauging and interchangeability requirements of the relevant IEC standard		N/A
	No additional tests specified for nationally standardized plugs such as those detailed in IEC/TR 60083 or connectors complying with the standard sheets of IEC 60320-1 and IEC 60309		P
24.1.1	Capacitors likely to be permanently subjected to the supply voltage and used for radio interference suppression or for voltage dividing, complying with IEC 60384-14		N/A
	If the capacitors have to be tested, they are tested according to Annex F		N/A
24.1.2	Safety isolating transformers complying with IEC 61558-2-6		N/A
	If they have to be tested, they are tested according to Annex G		N/A
24.1.3	Switches complying with IEC 61058-1, the number of cycles of operation being at least 10 000		N/A
	If they have to be tested, they are tested according to Annex H		N/A
	If the switch operates a relay or contactor, the complete switching system is subjected to the test		N/A
	If the switch only operates a motor starting relay complying with IEC 60730-2-10 with the number of cycles of a least 10 000 as specified, the complete switching system need not be tested		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Switches controlling heating elements of hotplates subjected to 50000 cycles of operation (IEC 60335-2-9)		N/A
24.1.4	Automatic controls complying with IEC 60730-1 with the relevant part 2. The number of cycles of operation being at least:		P
	- thermostats: 10 000		P
	- temperature limiters: 1 000		N/A
	- self-resetting thermal cut-outs: 300		N/A
	- voltage maintained non-self-resetting thermal cut-outs: 1 000		N/A
	- other non-self-resetting thermal cut-outs: 30		N/A
	- timers: 3 000		N/A
	- energy regulators: 10 000		N/A
	- energy regulators for automatic action (IEC 60335-2-9): 100 000		N/A
	- energy regulators for manual action (IEC 60335-2-9): 10 000		N/A
	Self-resetting thermal cut-outs for heating elements of glass-ceramic hotplates (IEC 60335-2-9) 100 000		N/A
	The number of cycles for controls operating during clause 11 need not be declared, if the appliance meets the requirements of this standard when they are short-circuited		N/A
	Thermal motor protectors are tested in combination with their motor under the conditions specified in Annex D		N/A
	For water valves containing live parts and that are incorporated in external hoses for connection of an appliance to the water mains, the degree of protection declared for subclause 6.5.2 of IEC 60730-2-8 is IPX7		N/A
24.1.5	Appliance couplers complying with IEC 60320-1		N/A
	However, for appliances classified higher than IPX0, the appliance couplers complying with IEC 60320-2-3		N/A
	Interconnection couplers complying with IEC 60320-2-2		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Appliance couplers incorporating thermostats, thermal cut-outs or fuses comply with IEC 60320-1, with exceptions specified in IEC 60335-9 (IEC 60335-2-9)		N/A
	Not applicable to conditions as specified (IEC 60335-2-9)		N/A
24.1.6	Small lamp holders similar to E10 lampholders complying with IEC 60238, the requirements for E10 lampholders being applicable		N/A
24.1.7	For remote operation of the appliance via a telecommunication network, the relevant standard for the telecommunication interface circuitry in the appliance is IEC 62151		N/A
24.1.8	The relevant standard for thermal links is IEC 60691		P
	Thermal links not complying with IEC 60691 are considered to be an intentionally weak part for the purposes of Clause 19		N/A
24.1.9	Contactors and relays, other than motor starting relays, tested as part of the appliance		N/A
	They are also tested in accordance with Clause 17 of IEC 60730-1, the number of cycles of operations in 24.1.4 selected according to the contactor or relay function in the appliance		N/A
24.2	Appliances not fitted with:		P
	- switches or automatic controls in flexible cords		P
	- devices causing the protective device in the fixed wiring to operate in the event of a fault in the appliance		P
	- thermal cut-outs that can be reset by soldering, unless		N/A
	the solder has a melting point of at least 230 °C		N/A
24.3	Switches intended for all-pole disconnection of stationary appliances are directly connected to the supply terminals and have a contact separation in all poles, providing full disconnection under overvoltage category III conditions		N/A
24.4	Plugs and socket-outlets for extra-low voltage circuits and heating elements, not interchangeable with plugs and socket-outlets listed in IEC/TR 60083 or IEC 60906-1 or with connectors and appliance inlets complying with the standard sheets of IEC 60320-1		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
24.5	Capacitors in auxiliary windings of motors marked with their rated voltage and capacitance, and used accordingly		N/A
	Voltage across capacitors in series with a motor winding does not exceed 1,1 times rated voltage, when the appliance is supplied at 1,1 times rated voltage under minimum load		N/A
24.6	Working voltage of motors connected to the supply mains and having basic insulation that is inadequate for the rated voltage of the appliance, not exceeding 42 V		N/A
	In addition, the motors comply with the requirements of Annex I		N/A
24.7	Detachable hose-sets for connection of appliances to the water mains comply with IEC 61770		N/A
	They are supplied with the appliance		N/A
	Appliances intended to be permanently connected to the water mains not connected by a detachable hose-set		N/A
24.8	Motor running capacitors in appliances for which 30.2.3 is applicable and that are permanently connected in series with a motor winding, not causing a hazard in event of a failure		N/A
	One or more of the following conditions are to be met:		N/A
	- the capacitors are of class P2 according to IEC 60252-1		N/A
	- the capacitors are housed within a metallic or ceramic enclosure		N/A
	- the distance of separation of the outer surface to adjacent non-metallic parts exceeds 50 mm		N/A
	- adjacent non-metallic parts within 50 mm withstand the needle-flame test of Annex E		N/A
	- adjacent non-metallic parts within 50 mm classified as at least V-1 according to IEC 60695-11-10		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
24.101	Thermostats and energy regulators incorporating an off position: off position maintained under test conditions (IEC 60335-2-9)		N/A
	Thermostats and energy regulators incorporating an off position : no breakdown after application of 500V across the contacts not switch on as a result of variations in ambient temperature (IEC 60335-2-9)		N/A
24.102	Thermal cut-outs incorporated in food dehydrators in order to comply with 19.4 are non-self-resetting (IEC 60335-2-9)		N/A
25	SUPPLY CONNECTION AND EXTERNAL FLEXIBLE CORDS		P
25.1	Appliance not intended for permanent connection to fixed wiring, means for connection to the supply:		P
	- supply cord fitted with a plug,		P
	- an appliance inlet having at least the same degree of protection against moisture as required for the appliance, or		N/A
	- pins for insertion into socket-outlets		N/A
	Appliances incorporating an appliance inlet other than those standardized in IEC 60320-1, shall be supplied with a cord set (IEC 60335-2-9)		N/A
25.2	Appliance not provided with more than one means of connection to the supply mains		P
	Stationary appliance for multiple supply may be provided with more than one means of connection, provided electric strength test of 1250 V for 1 min between each means of connection causes no breakdown		N/A
25.3	Appliance intended to be permanently connected to fixed wiring provided with one of the following means for connection to the supply mains:		N/A
	- a set of terminals allowing the connection of a flexible cord		N/A
	- a fitted supply cord		N/A
	- a set of supply leads accommodated in a suitable compartment		N/A
	- a set of terminals for the connection of cables of fixed wiring, cross-sectional areas specified in 26.6, and the appliance allows the connection of the supply conductors after the appliance has been fixed to its support		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	- a set of terminals and cable entries, conduit entries, knock-outs or glands, allowing connection of appropriate types of cable or conduit, and the appliance allows the connection of the supply conductors after the appliance has been fixed to its support		N/A
	For a fixed appliance constructed so that parts can be removed to facilitate easy installation, this requirement is met if it is possible to connect the fixed wiring without difficulty after a part of the appliance has been fixed to its support		N/A
25.4	Cable and conduit entries, rated current of appliance not exceeding 16 A, dimension according to table 10 (mm)		N/A
	Introduction of conduit or cable does not reduce clearances or creepage distances below values specified in clause 29		N/A
25.5	Method for assembling the supply cord to the appliance:		P
	- type X attachment		N/A
	- type Y attachment		P
	- type Z attachment, if allowed in relevant part 2		N/A
	Type X attachment, other than those with a specially prepared cord, not used for flat twin tinsel cords		N/A
	For multi-phase appliances supplied with a supply cord and that are intended to be permanently connected to fixed wiring, the supply cord is assembled to the appliance by type Y attachment		N/A
25.6	Plugs fitted with only one flexible cord		P
25.7	Supply cords, other than for class III appliances, being one of the following types:		P
	- rubber sheathed (at least 60245 IEC 53)	H05RR-F	P
	- polychloroprene sheathed (at least 60245 IEC 57)		N/A
	- cross-linked polyvinyl chloride sheathed (at least 60245 IEC 88)		N/A
	- polyvinyl chloride sheathed. Not used if they are likely to touch metal parts having a temperature rise exceeding 75 K during the test of clause 11		N/A
	<ul style="list-style-type: none"> • light polyvinyl chloride sheathed cord (60227 IEC 52), for appliances not exceeding 3 kg 		N/A
	<ul style="list-style-type: none"> • ordinary polyvinyl chloride sheathed cord (60227 IEC 53), for other appliances 	H05VV-F	P

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	- heat resistant polyvinyl chloride sheathed. Not used for type X attachment other than specially prepared cords		N/A
	<ul style="list-style-type: none"> heat-resistant light polyvinyl chloride sheathed cord (60227 IEC 56), for appliances not exceeding 3 kg 		N/A
	<ul style="list-style-type: none"> heat-resistant polyvinyl chloride sheathed cord (60227 IEC 57), for other appliances 		N/A
	Supply cords for class III appliances adequately insulated		N/A
	Test with 500 V for 2 min for supply cords of class III appliances that contain live parts		N/A
25.8	Nominal cross-sectional area of supply cords not less than table 11; rated current (A); cross-sectional area (mm ²).....:	Max. rated current: <6A, 3G0,75mm ²	P
25.9	Supply cords not in contact with sharp points or edges		P
25.10	Supply cord of class I appliances have a green/yellow core for earthing		P
25.11	Conductors of supply cords not consolidated by soldering where they are subject to contact pressure, unless		P
	the contact pressure is provided by spring terminals		N/A
25.12	Insulation of the supply cord not damaged when moulding the cord to part of the enclosure		N/A
25.13	Inlet openings so constructed as to prevent damage to the supply cord		P
	If the enclosure at the inlet opening is not of insulating material, a non-detachable lining or bushing complying with 29.3 for supplementary insulation provided		N/A
	If unsheathed supply cord, a similar additional bushing or lining is required, unless the appliance is		N/A
	class 0, or		N/A
	a class III appliance not containing live parts		N/A
25.14	Supply cords moved while in operation adequately protected against excessive flexing		N/A
	Flexing test, as described:		N/A
	- applied force (N).....:		N/A
	- number of flexings.....:		N/A
	The test does not result in:		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	- short-circuit between the conductors, such that the current exceeds a value of twice the rated current		N/A
	- breakage of more than 10% of the strands of any conductor		N/A
	- separation of the conductor from its terminal		N/A
	- loosening of any cord guard		N/A
	- damage to the cord or the cord guard		N/A
	- broken strands piercing the insulation and becoming accessible		N/A
25.15	For appliances with supply cord and appliances to be permanently connected to fixed wiring by a flexible cord, conductors of the supply cord relieved from strain, twisting and abrasion by use of cord anchorage		P
	The cord cannot be pushed into the appliance to such an extent that the cord or internal parts of the appliance can be damaged		P
	Pull and torque test of supply cord, values shown in table 12: mass (kg); pull (N); torque (not on automatic cord reel) (Nm)	60N, 0,25Nm	P
	Cord not damaged and max. 2 mm displacement of the cord	Max. 0,9mm	P
25.16	Cord anchorages for type X attachments constructed and located so that:		N/A
	- replacement of the cord is easily possible		N/A
	- it is clear how the relief from strain and the prevention of twisting are obtained		N/A
	- they are suitable for different types of supply cord		N/A
	- cord cannot touch the clamping screws of cord anchorage if these screws are accessible, unless		N/A
	they are separated from accessible metal parts by supplementary insulation		N/A
	- the cord is not clamped by a metal screw which bears directly on the cord		N/A
	- at least one part of the cord anchorage securely fixed to the appliance, unless		N/A
	it is part of a specially prepared cord		N/A
	- screws which have to be operated when replacing the cord do not fix any other component, unless		N/A
	the appliance becomes inoperative or incomplete or the parts cannot be removed without a tool		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	- if labyrinths can be bypassed the test of 25.15 is nevertheless withstood		N/A
	- for class 0, 0I and I appliances they are of insulating material or are provided with an insulating lining, unless		N/A
	failure of the insulation of the cord does not make accessible metal parts live		N/A
	- for class II appliances they are of insulating material, or		N/A
	if of metal, they are insulated from accessible metal parts by supplementary insulation		N/A
	After the test of 25.15, under the conditions specified, the conductors have not moved by more than 1 mm in the terminals		N/A
25.17	Adequate cord anchorages for type Y and Z attachment, test with the cord supplied with the appliance	Type Y attachment	P
25.18	Cord anchorages only accessible with the aid of a tool, or		P
	Constructed so that the cord can only be fitted with the aid of a tool		P
25.19	Type X attachment, glands not used as cord anchorage in portable appliances		N/A
	Tying the cord into a knot or tying the cord with string not used		N/A
25.20	The insulated conductors of the supply cord for type Y and Z attachment additionally insulated from accessible metal parts		P
25.21	Space for supply cord for type X attachment or for connection of fixed wiring constructed:		N/A
	- to permit checking of conductors with respect to correct positioning and connection before fitting any cover		N/A
	- so there is no risk of damage to the conductors or their insulation when fitting the cover		N/A
	- for portable appliances, so that the uninsulated end of a conductor, if it becomes free from the terminal, prevented from contact with accessible metal parts		N/A
	2 N test to the conductor for portable appliances; no contact with accessible metal parts		N/A
25.22	Appliance inlets:		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	- live parts not accessible during insertion or removal		N/A
	Requirement not applicable to appliance inlets complying with IEC 60320-1		N/A
	- connector can be inserted without difficulty		N/A
	- the appliance is not supported by the connector		N/A
	- not for cold conditions if temp. rise of external metal parts exceeds 75 K during clause 11, unless		N/A
	the supply cord is unlikely to touch such metal parts		N/A
25.23	Interconnection cords comply with the requirements for the supply cord, except that:		N/A
	- the cross-sectional area of the conductors is determined on the basis of the maximum current during clause 11		N/A
	- the thickness of the insulation may be reduced		N/A
	If necessary, electric strength test of 16.3		N/A
25.24	Interconnection cords not detachable without the aid of a tool if compliance with this standard is impaired when they are disconnected		N/A
25.25	Dimensions of pins that are inserted into socket-outlets compatible with the dimensions of the relevant socket-outlet.		P
	Dimensions of pins and engagement face in accordance with the dimensions of the relevant plug in IEC/TR 60083		P
26	TERMINALS FOR EXTERNAL CONDUCTORS		P
26.1	Appliances provided with terminals or equally effective devices for connection of external conductors		P
	Terminals only accessible after removal of a non-detachable cover, except		P
	for class III appliances that do not contain live parts		N/A
	Earthing terminals may be accessible if a tool is required to make the connections and means are provided to clamp the wire independently from its connection		N/A
26.2	Appliances with type X attachment and appliances for the connection of cables to fixed wiring provided with terminals in which connections are made by means of screws, nuts or similar devices, unless		N/A
	the connections are soldered		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Screws and nuts not used to fix any other component, except		N/A
	internal conductors, if so arranged that they are unlikely to be displaced when fitting the supply conductors		N/A
	If soldered connections used, the conductor so positioned or fixed that reliance is not placed on soldering alone, unless		N/A
	barriers provided so that neither clearances nor creepage distances between live parts and other metal parts reduced below the values for supplementary insulation if the conductor becomes free at the soldered joint		N/A
26.3	Terminals for type X attachment and for connection of cables of fixed wiring so constructed that the conductor is clamped between metal surfaces with sufficient contact pressure but without damaging the conductor		N/A
	Terminals fixed so that when the clamping means is tightened or loosened:		N/A
	- the terminal does not become loose		N/A
	- internal wiring is not subjected to stress		N/A
	- neither clearances nor creepage distances are reduced below the values in clause 29		N/A
	Compliance checked by inspection and by the test of subclause 9.6 of IEC 60999-1, the torque applied being equal to two-thirds of the torque specified (Nm)		N/A
	No deep or sharp indentations of the conductors		N/A
26.4	Terminals for type X attachment, except those having a specially prepared cord and those for the connection of cables of fixed wiring, no special preparation of conductors such as by soldering, use of cable lugs, eyelets or similar, and		N/A
	so constructed or placed that conductors prevented from slipping out when clamping screws or nuts are tightened		N/A
26.5	Terminals for type X attachment so located or shielded that if a wire of a stranded conductor escapes, no risk of accidental connection to other parts that result in a hazard		N/A
	Stranded conductor test, 8 mm insulation removed		N/A
	No contact between live parts and accessible metal parts and,		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	for class II constructions, between live parts and metal parts separated from accessible metal parts by supplementary insulation only		N/A
26.6	Terminals for type X attachment and for connection of cables of fixed wiring suitable for connection of conductors with cross-sectional area according to table 13; rated current (A); nominal cross-sectional area (mm ²).....:		N/A
	If a specially prepared cord is used, terminals need only be suitable for that cord		N/A
26.7	Terminals for type X attachment, except in class III appliances not containing live parts, accessible after removal of a cover or part of the enclosure		N/A
26.8	Terminals for the connection of fixed wiring, including the earthing terminal, located close to each other		N/A
26.9	Terminals of the pillar type constructed and located as specified		N/A
26.10	Terminals with screw clamping and screwless terminals not used for flat twin tinsel cords, unless		P
	conductors ends fitted with means suitable for screw terminals		P
	Pull test of 5 N to the connection		P
26.11	For type Y and Z attachment, soldered, welded, crimped or similar connections may be used	Type Y, crimped connection	P
	For Class II appliances, the conductor so positioned or fixed that reliance is not placed on soldering, welding or crimping alone		N/A
	If soldering, welding or crimping alone used, barriers provided so that clearances and creepage distances between live parts and other metal parts are not reduced below the values for supplementary insulation if the conductor becomes free		N/A
27	PROVISION FOR EARTHING		P
27.1	Accessible metal parts of Class 0I and I appliances permanently and reliably connected to an earthing terminal or earthing contact of the appliance inlet	Class I	P
	Earthing terminals and earthing contacts not connected to the neutral terminal		P
	Class 0, II and III appliances have no provision for earthing		N/A
	Safety extra-low voltage circuits not earthed, unless		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	protective extra-low voltage circuits		N/A
	No earthing via flexible metal tubes, coiled springs and cord anchorage (IEC 60335-2-9)		P
27.2	Clamping means of earthing terminals adequately secured against accidental loosening		P
	Terminals for the connection of external equipotential bonding conductors allow connection of conductors of 2.5 to 6 mm ² , and		N/A
	do not provide earthing continuity between different parts of the appliance, and		N/A
	conductors cannot be loosened without the aid of a tool		P
27.3	For a detachable part having an earth connection and being plugged into another part of the appliance, the earth connection is made before and separated after current-carrying connections when removing the part		N/A
	For appliances with supply cords, current-carrying conductors become taut before earthing conductor, if the cord slips out of the cord anchorage		P
27.4	No risk of corrosion resulting from contact between parts of the earthing terminal and the copper of the earthing conductor or other metal		P
	Parts providing earthing continuity, other than parts of a metal frame or enclosure, have adequate resistance to corrosion		P
	If of steel, these parts provided with an electroplated coating with a thickness at least 5 µm		N/A
	Adequate protection against rusting of parts of coated or uncoated steel, only intended to provide or transmit contact pressure		N/A
	In the body of the earthing terminal is a part of a frame or enclosure of aluminium or aluminium alloys, precautions taken to avoid risk of corrosion		N/A
27.5	Low resistance of connection between earthing terminal and earthed metal parts		P
	This requirement does not apply to connections providing earthing continuity in the protective extra-low voltage circuit, provided the clearances of basic insulation are based on the rated voltage of the appliance		N/A
	Resistance not exceeding 0,1 Ω at the specified low-resistance test (Ω).....:	Max 0,05Ω	P

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
27.6	The printed conductors of printed circuit boards not used to provide earthing continuity in hand-held appliances.		N/A
	They may be used to provide earthing continuity in other appliances if at least two tracks are used with independent soldering points and the appliance complies with 27.5 for each circuit		N/A
28	SCREWS AND CONNECTIONS		P
28.1	Fixings, electrical connections and connections providing earthing continuity withstand mechanical stresses		P
	Screws not of soft metal liable to creep, such as zinc or aluminium		P
	Diameter of screws of insulating material min. 3 mm		N/A
	Screws of insulating material not used for any electrical connections or connections providing earthing continuity		N/A
	Screws used for electrical connections or connections providing earthing continuity screwed into metal		P
	Screws not of insulating material if their replacement by a metal screw can impair supplementary or reinforced insulation		P
	For type X attachment, screws to be removed for replacement of supply cord or for user maintenance, not of insulating material if their replacement by a metal screw impairs basic insulation		N/A
	For screws and nuts; torque-test as specified in table 14.....:	(see appended table)	P
28.2	Electrical connections and connections providing earthing continuity constructed so that contact pressure is not transmitted through non-ceramic insulating material liable to shrink or distort, unless		P
	there is resiliency in the metallic parts to compensate for shrinkage or distortion of the insulating material		N/A
	This requirement does not apply to electrical connections in circuits of appliances for which:		N/A
	<ul style="list-style-type: none"> • 30.2.2 is applicable and that carry a current not exceeding 0,5 A 		N/A
	<ul style="list-style-type: none"> • 30.2.3 is applicable and that carry a current not exceeding 0,2 A 		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
28.3	Space-threaded (sheet metal) screws only used for electrical connections if they clamp the parts together		N/A
	Thread-cutting (self-tapping) screws and thread rolling screws only used for electrical connections if they generate a full form standard machine screw thread		N/A
	Thread-cutting (self-tapping) screws not used if they are likely to be operated by the user or installer		N/A
	Thread-cutting, thread rolling and space threaded screws may be used in connections providing earthing continuity provided it is not necessary to disturb the connection:		N/A
	- in normal use,		N/A
	- during user maintenance,		N/A
	- when replacing a supply cord having a type X attachment, or		N/A
	- during installation		N/A
	At least two screws being used for each connection providing earthing continuity, unless		N/A
	the screw forms a thread having a length of at least half the diameter of the screw		N/A
28.4	Screws and nuts that make mechanical connection secured against loosening if they also make electrical connections or connections providing earthing continuity		P
	This requirement does not apply to screws in the earthing circuit if at least two screws are used, or		N/A
	if an alternative earthing circuit is provided		N/A
	Rivets for electrical connections or connections providing earthing continuity secured against loosening if the connections are subjected to torsion		N/A
29	CLEARANCES, CREEPAGE DISTANCES AND SOLID INSULATION		P
	Clearances, creepage distances and solid insulation withstand electrical stress		P
	For coatings used on printed circuits boards to protect the microenvironment (Type 1) or to provide basic insulation (Type 2), Annex J applies		N/A
	The microenvironment is pollution degree 1 under type 1 protection		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	For type 2 protection, the spacing between the conductors before the protection is applied is not less than the values specified in Table 1 of IEC 60664-3		N/A
	These values apply to functional, basic, supplementary and reinforced insulation.....:		P
29.1	Clearances not less than the values specified in table 16, taking into account the rated impulse voltage for the overvoltage categories of table 15, unless	(see appended table)	P
	for basic insulation and functional insulation they comply with the impulse voltage test of clause 14		N/A
	However, if the distances are affected by wear, distortion, movement of the parts or during assembly, the clearances for rated impulse voltages of 1500V and above are increased by 0,5 mm and the impulse voltage test is not applicable		P
	Impulse voltage test is not applicable:		N/A
	- when the microenvironment is pollution degree 3, or		P
	- for basic insulation of class 0 and class 01 appliances		N/A
	Appliances are in overvoltage category II		P
	A force of 2 N is applied to bare conductors, other than heating elements		P
	A force of 30 N is applied to accessible surfaces		P
29.1.1	Clearances of basic insulation withstand the overvoltages, taking into account the rated impulse voltage		P
	The values of table 16 or the impulse voltage test of clause 14 are applicable.....:	(see appended table)	P
	Clearance at the terminals of tubular sheathed heating elements may be reduced to 1,0 mm if the microenvironment is pollution degree 1		P
	Lacquered conductors of windings considered to be bare conductors		N/A
29.1.2	Clearances of supplementary insulation not less than those specified for basic insulation in table 16:	(see appended table)	P
29.1.3	Clearances of reinforced insulation not less than those specified for basic insulation in table 16, using the next higher step for rated impulse voltage	(see appended table)	P

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	For double insulation, with no intermediate conductive part between basic and supplementary insulation, clearances are measured between live parts and the accessible surface, and the insulation system is treated as reinforced insulation		P
29.1.4	Clearances for functional insulation are the largest values determined from:		P
	- table 16 based on the rated impulse voltage	(see appended table)	P
	- table F.7a in IEC 60664-1, frequency not exceeding 30 kHz		P
	- clause 4 of IEC 60664-4, frequency exceeding 30 kHz		N/A
	If values of table 16 are largest, the impulse voltage test of clause 14 may be applied instead, unless		N/A
	the microenvironment is pollution degree 3, or		P
	the distances can be affected by wear, distortion, movement of the parts or during assembly		P
	However, clearances are not specified if the appliance complies with clause 19 with the functional insulation short-circuited		N/A
	Lacquered conductors of windings considered to be bare conductors		N/A
	However, clearances at crossover points are not measured		N/A
	Clearance between surfaces of PTC heating elements may be reduced to 1mm		N/A
29.1.5	Appliances having higher working voltages than rated voltage, clearances for basic insulation are the largest values determined from:		N/A
	- table 16 based on the rated impulse voltage		N/A
	- table F.7a in IEC 60664-1, frequency not exceeding 30 kHz		N/A
	- clause 4 of IEC 60664-4, frequency exceeding 30 kHz		N/A
	If clearances for basic insulation are selected from Table F.7a of IEC 60664-1 or Clause 4 of IEC 60664-4, the clearances of supplementary insulation are not less than those specified for basic insulation		N/A
	If clearances for basic insulation are selected from Table F.7a of IEC 60664-1, the clearances of reinforced insulation dimensioned as specified in Table F.7a are to withstand 160% of the withstand voltage required for basic insulation		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	If clearances for basic insulation are selected from Clause 4 of IEC 60664-4, the clearances of reinforced insulation are twice the value required for basic insulation		N/A
	If the secondary winding of a step-down transformer is earthed, or if there is an earthed screen between the primary and secondary windings, clearances of basic insulation on the secondary side not less than those specified in table 16, but using the next lower step for rated impulse voltage		N/A
	Circuits supplied with a voltage lower than rated voltage, clearances of functional insulation are based on the working voltage used as the rated voltage in table 15		N/A
29.2	Creepage distances not less than those appropriate for the working voltage, taking into account the material group and the pollution degree	(see appended table)	P
	Pollution degree 2 applies, unless		N/A
	- precautions taken to protect the insulation; pollution degree 1	At the end terminal of heating element	P
	- insulation subjected to conductive pollution; pollution degree 3		P
	A force of 2 N is applied to bare conductors, other than heating elements		P
	A force of 30 N is applied to accessible surfaces		P
	In a double insulation system, the working voltage for both the basic and supplementary insulation is taken as the working voltage across the complete double insulation system		P
	Pollution degree 3 applies, unless the insulation is enclosed or located so that it is unlikely to be exposed to pollution during normal use of the appliance (IEC 60335-2-9)		P
29.2.1	Creepage distances of basic insulation not less than specified in table 17	(see appended table)	P
	However, if the working voltage is periodic and has a frequency exceeding 30 kHz, the creepage distances are also determined from table 2 of IEC 60664-4, these values being used if exceeding the values in table 17		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Except for pollution degree 1, corresponding creepage distance not less than the minimum specified for the clearance in table 16, if the clearance has been checked according to the test of clause 14		N/A
29.2.2	Creepage distances of supplementary insulation at least those specified for basic insulation in table 17, or	(see appended table)	P
	Table 2 of IEC 60664-4, as applicable		N/A
29.2.3	Creepage distances of reinforced insulation at least double those specified for basic insulation in table 17, or	(see appended table)	P
	Table 2 of IEC 60664-4, as applicable		N/A
29.2.4	Creepage distances of functional insulation not less than specified in table 18.....	(see appended table)	P
	However, if the working voltage is periodic and has a frequency exceeding 30 kHz, the creepage distances are also determined from table 2 of IEC 60664-4, these values being used if exceeding the values in table 18.....		N/A
	Creepage distances may be reduced if the appliance complies with clause 19 with the functional insulation short-circuited		N/A
29.3	Supplementary and reinforced insulation have adequate thickness, or a sufficient number of layers, to withstand the electrical stresses		P
	Compliance checked:		P
	- by measurement, in accordance with 29.3.1, or		P
	- by an electric strength test in accordance with 29.3.2, or		N/A
	- by an assessment of the thermal quality of the material combined with an electric strength test, in accordance with 29.3.3, and		N/A
	for accessible parts of reinforced insulation consisting of a single layer, by measurement in accordance with 29.3.4, or		N/A
	- as specified in subclause 6.3 of IEC 60664-4 for insulation that is subjected to any periodic voltage having a frequency exceeding 30 kHz		N/A
	Requirement not applied to the sheath of a visibly glowing heating element that is inaccessible to test probe 41 of IEC 61032 (IEC 60335-2-9)		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
29.3.1	Supplementary insulation have a thickness of at least 1 mm		P
	Reinforced insulation have a thickness of at least 2 mm		P
29.3.2	Each layer of material withstand the electric strength test of 16.3 for supplementary insulation		N/A
	Supplementary insulation consist of at least 2 layers		N/A
	Reinforced insulation consist of at least 3 layers		N/A
29.3.3	The insulation is subjected to the dry heat test Bb of IEC 60068-2-2, followed by		N/A
	the electric strength test of 16.3		N/A
	If the temperature rise during the tests of clause 19 does not exceed the value specified in table 3, the test of IEC 60068-2-2 is not carried out		N/A
29.3.4	Thickness of accessible parts of reinforced insulation consisting of a single layer not less than specified in table 19.....:		N/A
30	RESISTANCE TO HEAT AND FIRE		P
30.1	External parts of non-metallic material,		P
	parts supporting live parts, and		P
	parts of thermoplastic material providing supplementary or reinforced insulation		P
	sufficiently resistant to heat		P
	Ball-pressure test according to IEC 60695-10-2		P
	External parts tested at 40 °C plus the maximum temperature rise determined during the test of clause 11, or at 75 °C, whichever is the higher; temperature (°C).....:	(see appended table)	P
	Parts supporting live parts tested at 40°C plus the maximum temperature rise determined during the test of clause 11, or at 125 °C, whichever is the higher; temperature (°C).....:	(see appended table)	P
	Parts of thermoplastic material providing supplementary or reinforced insulation tested at 25 °C plus the maximum temperature rise determined during clause 19, if higher; temperature (°C)	(see appended table)	N/A
	Temperature rises occurring during the test of 19.102 are not taken into account (IEC 60335-2-9)		N/A
30.2	Parts of non-metallic material resistant to ignition and spread of fire		P

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	This requirement does not apply to:		P
	parts having a mass not exceeding 0,5 g, provided the cumulative effect is unlikely to propagate flames that originate inside the appliance by propagating flames from one part to another, or		P
	decorative trims, knobs and other parts unlikely to be ignited or to propagate flames that originate inside the appliance		P
	Compliance checked by the test of 30.2.1, and in addition:		P
	- for attended appliances, 30.2.2 applies		P
	- for unattended appliances, 30.2.3 applies		N/A
	For appliances for remote operation, 30.2.3 applies		N/A
	For base material of printed circuit boards, 30.2.4 applies		N/A
	For breadmakers, food dehydrators, 30.2.3 applies (IEC 60335-2-9)		N/A
	For cookers, ovens, roasters, rotary grills if they incorporate a timer or if their instructions indicate a cooking operation longer than 1h , 30.2.3 applies (IEC 60335-2-9)		N/A
	For other appliances, 30.2.2 applies (IEC 60335-2-9)		P
30.2.1	Parts of non-metallic material subjected to the glow-wire test of IEC 60695-2-11 at 550 °C		P
	However, test not carried out if the material is classified as having a glow-wire flammability index according to IEC 60695-2-12 of at least 550 °C, or		N/A
	the material is classified at least HB40 according to IEC 60695-11-10		N/A
	Parts for which the glow-wire test cannot be carried out need to meet the requirements in ISO 9772 for material classified HBF		N/A
30.2.2	Appliances operated while attended, parts of non-metallic material supporting current-carrying connections, and		P
	parts of non-metallic material within a distance of 3mm of such connections,		P
	subjected to the glow-wire test of IEC 60695-2-11		P
	The test severity is:		P

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	- 750 °C, for connections carrying a current exceeding 0,5 A during normal operation	(see appended table)	P
	- 650 °C, for other connections		N/A
	Glow-wire applied to an interposed shielding material, if relevant		N/A
	The glow-wire test is not carried out on parts of material classified as having a glow-wire flammability index according to IEC 60695-2-12 of at least:		N/A
	- 750 °C, for connections carrying a current exceeding 0,5 A during normal operation		N/A
	- 650 °C, for other connections		N/A
	The glow-wire test is also not carried out on small parts. These parts are to:		N/A
	- comprise material having a glow-wire flammability index of at least 750 °C, or 650 °C as appropriate, or		N/A
	- comply with the needle-flame test of Annex E, or		N/A
	- comprise material classified as V-0 or V-1 according to IEC 60695-11-10		N/A
	Glow-wire test not applicable to conditions as specified		N/A
30.2.3	Appliances operated while unattended, tested as specified in 30.2.3.1 and 30.2.3.2		N/A
	The tests are not applicable to conditions as specified		N/A
30.2.3.1	Parts of non-metallic material supporting connections carrying a current exceeding 0,2 A during normal operation, and		N/A
	parts of non-metallic material, other than small parts, within a distance of 3 mm,		N/A
	subjected to the glow-wire test of IEC 60695-2-11 with a test severity of 850 °C		N/A
	Glow-wire applied to an interposed shielding material, if relevant		N/A
	The glow-wire test is not carried out on parts of material classified as having a glow-wire flammability index according to IEC 60695-2-12 of at least 850 °C		N/A
30.2.3.2	Parts of non-metallic material supporting connections, and		N/A
	parts of non-metallic material within a distance of 3mm,		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	subjected to glow-wire test of IEC 60695-2-11		N/A
	The test severity is:		N/A
	- 750 °C, for connections carrying a current exceeding 0,2 A during normal operation		N/A
	- 650 °C, for other connections		N/A
	Glow-wire applied to an interposed shielding material, if relevant		N/A
	However, the glow-wire test of 750 °C or 650 °C as appropriate, is not carried out on parts of material fulfilling both or either of the following classifications:		N/A
	- a glow-wire ignition temperature according to IEC 60695-2-13 of at least:		N/A
	<ul style="list-style-type: none"> • 775 °C, for connections carrying a current exceeding 0,2 A during normal operation 		N/A
	<ul style="list-style-type: none"> • 675 °C, for other connections 		N/A
	- a glow-wire flammability index according to IEC 60695-2-12 of at least:		N/A
	- 750 °C, for connections carrying a current exceeding 0,2 A during normal operation		N/A
	- 650 °C, for other connections		N/A
	The glow-wire test is also not carried out on small parts. These parts are to:		N/A
	- comprise material having a glow-wire ignition temperature of at least 775 °C or 675 °C as appropriate, or		N/A
	- comprise material having a glow-wire flammability index of at least 750 °C or 650 °C as appropriate, or		N/A
	- comply with the needle-flame test of Annex E, or		N/A
	- comprise material classified as V-0 or V-1 according to IEC 60695-11-10		N/A
	The consequential needle-flame test of Annex E applied to non-metallic parts that encroach within the vertical cylinder placed above the centre of the connection zone and on top of the non-metallic parts supporting current-carrying connections, and parts of non-metallic material within a distance of 3 mm of such connections if these parts are those:		N/A
	- parts that withstood the glow-wire test of IEC 60695-2-11 of 750 °C or 650 °C as appropriate, but produce a flame that persist longer than 2 s, or		N/A
	- parts that comprised material having a glow-wire flammability index of at least 750 °C or 650 °C as appropriate, or		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	- small parts, that comprised material having a glow-wire flammability index of at least 750 °C or 650 °C as appropriate, or		N/A
	- small parts for which the needle-flame test of Annex E was applied, or		N/A
	- small parts for which a material classification of V-0 or V-1 was applied		N/A
	However, the consequential needle-flame test is not carried out on non-metallic parts, including small parts, within the cylinder that are:		N/A
	- parts having a glow-wire ignition temperature of at least 775 °C or 675 °C as appropriate, or		N/A
	- parts comprising material classified as V-0 or V-1 according to IEC 60695-11-10, or		N/A
	- parts shielded by a flame barrier that meets the needle-flame test of Annex E or that comprises material classified as V-0 or V-1 according to IEC 60695-11-10		N/A
30.2.4	Base material of printed circuit boards subjected to the needle-flame test of Annex E		N/A
	Test not applicable to conditions as specified		N/A
31	RESISTANCE TO RUSTING		P
	Relevant ferrous parts adequately protected against rusting		N/A
	For appliances intended for outdoor use, compliance is checked by the salt mist test, Kb of IEC 60068-2-52, severity 2 applicable (IEC 60335-2-9)		N/A
	Before the test, enclosures having a coating are scratched by means of hardened steel pin (IEC 60335-2-9)		N/A
	After the test, the appliance shall not have deteriorated to such an extent that compliance with this standard, in particular with Clauses 8 and 27, is impaired (IEC 60335-2-9)		N/A
	After the test, the coating shall not be broken and shall not have loosened from the surface (IEC 60335-2-9)		N/A
32	RADIATION, TOXICITY AND SIMILAR HAZARDS		P
	Appliance does not emit harmful radiation or present a toxic or similar hazard due to their operation in normal use		P

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Compliance is checked by the limits or tests specified in part 2, if relevant		N/A
A	ANNEX A (INFORMATIVE) ROUTINE TESTS		P
	Description of routine tests to be carried out by the manufacturer		P
B	ANNEX B (NORMATIVE) APPLIANCES POWERED BY RECHARGEABLE BATTERIES		N/A
	The following modifications to this standard are applicable for appliances powered by batteries that are recharged in the appliance		N/A
	This annex does not apply to battery chargers		N/A
3.1.9	Appliance operated under the following conditions:		N/A
	- the appliance, supplied by its fully charged battery, operated as specified in relevant part 2		N/A
	- the battery is charged, the battery being initially discharged to such an extent that the appliance cannot operate		N/A
	-if possible, the appliance is supplied from the supply mains through its battery charger, the battery being initially discharged to such an extent that the appliance cannot operate. The appliance is operated as specified in relevant part 2		N/A
	- if the appliance incorporates inductive coupling between two parts that are detachable from each other, the appliance is supplied from the supply mains with the detachable part removed		N/A
3.6.2	Part to be removed in order to discard the battery is not considered to be detachable		N/A
5.B.101	Appliances supplied from the supply mains tested as specified for motor-operated appliances		N/A
7.1	Battery compartment for batteries intended to be replaced by the user, marked with battery voltage and polarity of the terminals		N/A
	The positive terminal indicated by symbol IEC 60417-5005 and the negative terminal by symbol IEC 60417-5006		N/A
7.6	Symbols 60417-5005 and IEC 60417-5006		N/A
7.12	The instructions give information regarding charging		N/A
	The instructions for appliances incorporating batteries intended to be replaced by the user includes required information		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Details about how to remove batteries containing materials hazardous to the environment given		N/A
7.15	Markings placed on the part of the appliance connected to the supply mains		N/A
8.2	Appliances having batteries that according to the instruction may be replaced by the user need only have basic insulation between live parts and the inner surface of the battery compartment		N/A
	If the appliance can be operated without batteries, double or reinforced insulation required		N/A
11.7	The battery is charged for the period stated in the instructions or 24 h		N/A
19.1	Appliances subjected to tests of 19.B.101, 19.B.102 and 19.B.103		N/A
19.10	Not applicable		N/A
19.B.101	Appliances supplied at rated voltage for 168 h, the battery being continually charged		N/A
19.B.102	For appliances having batteries that can be removed without the aid of a tool, short-circuit of the terminals of the battery, the battery being fully charged,		N/A
19.B.103	Appliances having batteries replaceable by the user supplied at rated voltage under normal operation with the battery removed or in any position allowed by the construction		N/A
21.B.101	Appliances having pins for insertion into socket-outlets have adequate mechanical strength		N/A
	Part of the appliance incorporating the pins subjected to the free fall test, procedure 2, of IEC 60068-2-31, the number of falls being:		N/A
	- 100, if the mass of the part does not exceed 250 g (g)		N/A
	- 50, if the mass of the part exceeds 250 g		N/A
	After the test, the requirements of 8.1, 15.1.1, 16.3 and clause 29 are met		N/A
22.3	Appliances having pins for insertion into socket-outlets tested as fully assembled as possible		N/A
25.13	An additional lining or bushing not required for interconnection cords in class III appliances or class III constructions operating at safety extra-low voltage not containing live parts		N/A
30.2	For parts of the appliance connected to the supply mains during the charging period, 30.2.3 applies		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	For other parts, 30.2.2 applies		N/A
C	ANNEX C (NORMATIVE) AGEING TEST ON MOTORS		N/A
	Tests, as described, carried out when doubt with regard to the temperature classification of the insulation of a motor winding		N/A
	The value of p in Table C.1 is 2000 (IEC 60335-2-9)		N/A
D	ANNEX D (NORMATIVE) THERMAL MOTOR PROTECTORS		N/A
	Applicable to appliances having motors that incorporate thermal motor protectors necessary for compliance with the standard		N/A
	Test conditions as specified		N/A
E	ANNEX E (NORMATIVE) NEEDLE-FLAME TEST		N/A
	Needle-flame test carried out in accordance with IEC 60695-11-5, with the following modifications:		N/A
7	Severities		N/A
	The duration of application of the test flame is 30 s \pm 1 s		N/A
9	Test procedure		N/A
9.1	The specimen so arranged that the flame can be applied to a vertical or horizontal edge as shown in the examples of Figure 1		N/A
9.2	The first paragraph does not apply		N/A
	If possible, the flame is applied at least 10 mm from a corner		N/A
9.3	The test is carried out on one specimen		N/A
	If the specimen does not withstand the test, the test may be repeated on two additional specimens, both withstanding the test		N/A
11	Evaluation of test results		N/A
	The duration of burning not exceeding 30 s		N/A
	However, for printed circuit boards, the duration of burning not exceeding 15 s		N/A
F	ANNEX F (NORMATIVE) CAPACITORS		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Capacitors likely to be permanently subjected to the supply voltage, and used for radio interference suppression or voltage dividing, comply with the following clauses of IEC 60384-14, with the following modifications:		N/A
1.5	Terms and definitions		N/A
1.5.3	Class X capacitors tested according to subclass X2		N/A
1.5.4	This subclause is applicable		N/A
1.6	Marking		N/A
	Items a) and b) are applicable		N/A
3.4	Approval testing		N/A
3.4.3.2	Table 3 is applicable as described		N/A
4.1	Visual examination and check of dimensions		N/A
	This subclause is applicable		N/A
4.2	Electrical tests		N/A
4.2.1	This subclause is applicable		N/A
4.2.5	This subclause is applicable		N/A
4.2.5.2	Only table 11 is applicable		N/A
	Values for test A apply		N/A
	However, for capacitors in heating appliances the values for test B or C apply		N/A
4.12	Damp heat, steady state		N/A
	This subclause is applicable		N/A
	Only insulation resistance and voltage proof are checked		N/A
4.13	Impulse voltage		N/A
	This subclause is applicable		N/A
4.14	Endurance		N/A
	Subclauses 4.14.1, 4.14.3, 4.14.4 and 4.14.7 are applicable		N/A
4.14.7	Only insulation resistance and voltage proof are checked		N/A
	No visible damage		N/A
4.17	Passive flammability test		N/A
	This subclause is applicable		N/A
4.18	Active flammability test		N/A
	This subclause is applicable		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
G	ANNEX G (NORMATIVE) SAFETY ISOLATING TRANSFORMERS		N/A
	The following modifications to this standard are applicable for safety isolating transformers:		N/A
7	Marking and instructions		N/A
7.1	Transformers for specific use marked with:		N/A
	-name, trademark or identification mark of the manufacturer or responsible vendor.....:		N/A
	-model or type reference		N/A
17	Overload protection of transformers and associated circuits		N/A
	Fail-safe transformers comply with subclause 15.5 of IEC 61558-1		N/A
22	Construction		N/A
	Subclauses 19.1 and 19.1.2 of IEC 61558-2-6 are applicable		N/A
29	Clearances, creepage distances and solid insulation		N/A
29.1, 29.2, 29.3	The distances specified in items 2a, 2c and 3 in table 13 of IEC 61558-1 apply		N/A
	For insulated winding wires complying with subclause 19.12.3 of IEC 61558-1 there are no requirements for clearances or creepage distances		N/A
	For windings providing reinforced insulation, the distance specified in item 2c of table 13 of IEC 61558-1 is not assessed		N/A
	For safety isolating transformers subjected to periodic voltages with a frequency exceeding 30 kHz, the clearances, creepage distances and solid insulation values specified in IEC 60664-4 are applicable, if greater than the values specified in items 2a, 2c and 3 in table 13 of IEC 61558-1		N/A
H	ANNEX H (NORMATIVE) SWITCHES		N/A
	Switches comply with the following clauses of IEC 61058-1, as modified below:		N/A
	The tests of IEC 61058-1 carried out under the conditions occurring in the appliance		N/A
	Before being tested, switches are operated 20 times without load		N/A
8	Marking and documentation		N/A
	Switches are not required to be marked		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	However, a switch that can be tested separately from the appliance marked with the manufacturer's name or trade mark and the type reference		N/A
13	Mechanism		N/A
	The tests may be carried out on a separate sample		N/A
15	Insulation resistance and dielectric strength		N/A
15.1	Not applicable		N/A
15.2	Not applicable		N/A
15.3	Applicable for full disconnection and micro-disconnection		N/A
17	Endurance		N/A
	Compliance is checked on three separate appliances or switches		N/A
	For 17.2.4.4, the number of cycles declared according to 7.1.4 is 10 000, unless		N/A
	otherwise specified in 24.1.3 of the relevant part 2 of IEC 60335.....:		N/A
	Switches for operation under no load and which can be operated only by a tool, and		N/A
	switches operated by hand that are interlocked so that they cannot be operated under load,		N/A
	are not subjected to the tests		N/A
	However, switches without this interlock are subjected to the test of 17.2.4.4 for 100 cycles of operation		N/A
	Subclauses 17.2.2 and 17.2.5.2 not applicable		N/A
	The ambient temperature during the test is that occurring in the appliance during the test of Clause 11 in IEC 60335-1		N/A
	The temperature rise of the terminals not more than 30 K above the temperature rise measured in clause 11 of IEC 60335-1 (K)		N/A
20	Clearances, creepage distances, solid insulation and coatings of rigid printed board assemblies		N/A
	This clause is applicable to clearances and creepage distances for functional insulation, across full disconnection and micro-disconnection, as stated in table 24		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
I	ANNEX I (NORMATIVE) MOTORS HAVING BASIC INSULATION THAT IS INADEQUATE FOR THE RATED VOLTAGE OF THE APPLIANCE		N/A
	The following modifications to this standard are applicable for motors having basic insulation that is inadequate for the rated voltage of the appliance:		N/A
8	Protection against access to live parts		N/A
8.1	Metal parts of the motor are considered to be bare live parts		N/A
11	Heating		N/A
11.3	The temperature rise of the body of the motor is determined instead of the temperature rise of the windings		N/A
11.8	The temperature rise of the body of the motor, where in contact with insulating material, not exceeding values in table 3 for the relevant insulating material		N/A
16	Leakage current and electric strength		N/A
16.3	Insulation between live parts of the motor and its other metal parts is not subjected to the test		N/A
19	Abnormal operation		N/A
19.1	The tests of 19.7 to 19.9 are not carried out		N/A
19.1.101	Appliance operated at rated voltage with each of the following fault conditions:		N/A
	- short circuit of the terminals of the motor, including any capacitor incorporated in the motor circuit		N/A
	- short circuit of each diode of the rectifier		N/A
	- open circuit of the supply to the motor		N/A
	- open circuit of any parallel resistor, the motor being in operation		N/A
	Only one fault simulated at a time, the tests carried out consecutively		N/A
22	Construction		N/A
22.1.101	For class I appliances incorporating a motor supplied by a rectifier circuit, the d.c. circuit being insulated from accessible parts of the appliance by double or reinforced insulation		N/A
	Compliance checked by the tests specified for double and reinforced insulation		N/A
J	ANNEX J (NORMATIVE) COATED PRINTED CIRCUIT BOARDS		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Testing of protective coatings of printed circuit boards carried out in accordance with IEC 60664-3 with the following modifications:		N/A
5.7	Conditioning of the test specimens		N/A
	When production samples are used, three samples of the printed circuit board are tested		N/A
5.7.1	Cold		N/A
	The test is carried out at -25 °C		N/A
5.7.3	Rapid change of temperature		N/A
	Severity 1 is specified		N/A
5.9	Additional tests		N/A
	This subclause is not applicable		N/A
K	ANNEX K (NORMATIVE) OVERVOLTAGE CATEGORIES		P
	The information on overvoltage categories is extracted from IEC 60664-1		P
	Overvoltage category is a numeral defining a transient overvoltage condition		P
	Equipment of overvoltage category IV is for use at the origin of the installation		N/A
	Equipment of overvoltage category III is equipment in fixed installations and for cases where the reliability and the availability of the equipment is subject to special requirements		N/A
	Equipment of overvoltage category II is energy consuming equipment to be supplied from the fixed installation		P
	If such equipment is subjected to special requirements with regard to reliability and availability, overvoltage category III applies		N/A
	Equipment of overvoltage category I is equipment for connection to circuits in which measures are taken to limit transient overvoltages to an appropriate low level		N/A
L	ANNEX L (INFORMATIVE) GUIDANCE FOR THE MEASUREMENT OF CLEARANCES AND CREEPAGE DISTANCES		P
	Information for the determination of clearances and creepage distances		P
M	ANNEX M (NORMATIVE) POLLUTION DEGREE		P

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	The information on pollution degrees is extracted from IEC 60664-1		P
	Pollution		P
	The microenvironment determines the effect of pollution on the insulation, taking into account the macroenvironment		P
	Means may be provided to reduce pollution at the insulation by effective enclosures or similar		P
	Minimum clearances specified where pollution may be present in the microenvironment		P
	Degrees of pollution in the microenvironment		P
	For evaluating creepage distances, the following degrees of pollution in the microenvironment are established:		P
	- pollution degree 1: no pollution or only dry, non-conductive pollution occurs. The pollution has no influence	At the end terminal of heating element	P
	- pollution degree 2: only non-conductive pollution occurs, except that occasionally a temporary conductivity caused by condensation is to be expected		N/A
	- pollution degree 3: conductive pollution occurs or dry non-conductive pollution occurs that becomes conductive due to condensation that is to be expected		P
	- pollution degree 4: the pollution generates persistent conductivity caused by conductive dust or by rain or snow		N/A
N	ANNEX N (NORMATIVE) PROOF TRACKING TEST		P
	The proof tracking test is carried out in accordance with IEC 60112 with the following modifications:		P
7	Test apparatus		P
7.3	Test solutions		P
	Test solution A is used		P
10	Determination of proof tracking index (PTI)		P
10.1	Procedure		P
	The proof voltage is 100V, 175V, 400V or 600V ...:	175V	P
	The test is carried out on five specimens		P

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	In case of doubt, additional test with proof voltage reduced by 25V, the number of drops increased to 100		N/A
10.2	Report		P
	The report states if the PTI value was based on a test using 100 drops with a test voltage of (PTI-25) V		N/A
O	ANNEX O (INFORMATIVE) SELECTION AND SEQUENCE OF THE TESTS OF CLAUSE 30		P
	Description of tests for determination of resistance to heat and fire		P
P	ANNEX P (INFORMATIVE) GUIDANCE FOR THE APPLICATION OF THIS STANDARD TO APPLIANCES USED IN WARM DAMP EQUABLE CLIMATES		N/A
	Modifications applicable for class 0 and 01 appliances having a rated voltage exceeding 150V, intended to be used in countries having a warm damp equable climate and that are marked WDaE		N/A
	Modifications may also be applied to class 1 appliances having a rated voltage exceeding 150V, intended to be used in countries having a warm damp equable climate and that are marked WdaE, if liable to be connected to a supply mains that excludes the protective earthing conductor		N/A
5.7	The ambient temperature for the tests of clauses 11 and 13 is 40 +3/0 °C		N/A
7.1	The appliance marked with the letters WDaE		N/A
7.12	The instructions state that the appliance is to be supplied through a residual current device (RCD) having a rated residual operating current not exceeding 30 mA		N/A
	The instructions state that the appliance is considered to be suitable for use in countries having a warm damp equable climate, but may also be used in other countries		N/A
11.8	The values of Table 3 are reduced by 15 K		N/A
13.2	The leakage current for class I appliances not exceeding 0,5 mA		N/A
15.3	The value of t is 37 °C		N/A
16.2	The leakage current for class I appliances not exceeding 0,5 mA (mA):		N/A
19.13	The leakage current test of 16.2 is applied in addition to the electric strength test of 16.3		N/A
Q	ANNEX Q (INFORMATIVE) SEQUENCE OF TESTS FOR THE EVALUATION OF ELECTRONIC CIRCUITS		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Description of tests for appliances incorporating electronic circuits		N/A
R	ANNEX R (NORMATIVE) SOFTWARE EVALUATION		N/A
	Programmable electronic circuits requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2 validated in accordance with the requirements of this annex		N/A
R.1	Programmable electronic circuits using software		N/A
	Programmable electronic circuits requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2 constructed so that the software does not impair compliance with the requirements of this standard		N/A
R.2	Requirements for the architecture		N/A
	Programmable electronic circuits requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2 use measures to control and avoid software-related faults/errors in safety-related data and safety-related segments of the software		N/A
R.2.1.1	Programmable electronic circuits requiring software incorporating measures to control the fault/error conditions specified in table R.2 have one of the following structures:		N/A
	- single channel with periodic self-test and monitoring		N/A
	- dual channel (homogenous) with comparison		N/A
	- dual channel (diverse) with comparison		N/A
	Programmable electronic circuits requiring software incorporating measures to control the fault/error conditions specified in table R.1 have one of the following structures:		N/A
	- single channel with functional test		N/A
	- single channel with periodic self-test		N/A
	- dual channel without comparison		N/A
R.2.2	Measures to control faults/errors		N/A
R.2.2.1	When redundant memory with comparison is provided on two areas of the same component, the data in one area is stored in a different format from that in the other area		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
R.2.2.2	Programmable electronic circuits with functions requiring software incorporating measures to control the fault/error conditions specified in table R.2 and that use dual channel structures with comparison, have additional fault/error detection means for any fault/errors not detected by the comparison		N/A
R.2.2.3	For programmable electronic circuits with functions requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2, means are provided for the recognition and control of errors in transmissions to external safety-related data paths		N/A
R.2.2.4	For programmable electronic circuits with functions requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2, the programmable electronic circuits incorporate measures to address the fault/errors in safety-related segments and data indicated in table R.1 and R.2 as appropriate		N/A
R.2.2.5	For programmable electronic circuits with functions requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2, detection of a fault/error occur before compliance with clause 19 is impaired		N/A
R.2.2.6	The software is referenced to relevant parts of the operating sequence and the associated hardware functions		N/A
R.2.2.7	Labels used for memory locations are unique		N/A
R.2.2.8	The software is protected from user alteration of safety-related segments and data		N/A
R.2.2.9	Software and safety-related hardware under its control is initialized and terminates before compliance with clause 19 is impaired		N/A
R.3	Measures to avoid errors		N/A
R.3.1	General		N/A
	For programmable electronic circuits with functions requiring software incorporating measures to control the fault/error conditions specified in table R.1 or R.2, the following measures to avoid systematic fault in the software are applied		N/A
	Software that incorporates measures used to control the fault/error conditions specified in table R.2 is inherently acceptable for software required to control the fault/error conditions specified in table R.1		N/A
R.3.2	Specification		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
R.3.2.1	Software safety requirements:	Software Id:	N/A
	The specification of the software safety requirements includes the descriptions listed		N/A
R.3.2.2	Software architecture		N/A
R.3.2.2.1	The specification of the software architecture includes the aspects listed - techniques and measures to control software faults/errors (refer to R.2.2); - interactions between hardware and software; - partitioning into modules and their allocation to the specified safety functions; - hierarchy and call structure of the modules (control flow); - interrupt handling; - data flow and restrictions on data access; - architecture and storage of data; - time-based dependencies of sequences and data	Document ref. No:	N/A
R.3.2.2.2	The architecture specification is validated against the specification of the software safety requirements by static analysis		N/A
R.3.2.3	Module design and coding		N/A
R.3.2.3.1	Based on the architecture design, software is suitably refined into modules		N/A
	Software module design and coding is implemented in a way that is traceable to the software architecture and requirements		N/A
R.3.2.3.2	Software code is structured		N/A
R.3.2.3.3	Coded software is validated against the module specification by static analysis		N/A
	The module specification is validated against the architecture specification by static analysis		N/A
R.3.3.3	Software validation		N/A
	The software is validated with reference to the requirements of the software safety requirements specification		N/A
	Compliance is checked by simulation of:		N/A
	- input signals present during normal operation		N/A
	- anticipated occurrences		N/A

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	- undesired conditions requiring system action		N/A

TABLE R.1 ^e – GENERAL FAULT/ERROR CONDITIONS						
Component ^a	Fault/error	Acceptable measures ^{b, c}	Definitions	Document reference for applied measure	Document reference for applied test	Verdict
1 CPU						N/A
1.1 Registers	Stuck at	Functional test, or periodic self-test using either: - static memory test, or - word protection with single bit redundancy	H.2.16.5 H.2.16.6 H.2.19.6 H.2.19.8.2			N/A
1.2 VOID						N/A
1.3 Programme counter	Stuck at	Functional test, or Periodic self-test, or Independent time-slot monitoring, or Logical monitoring of the programme sequence	H.2.16.5 H.2.16.6 H.2.18.10.4 H.2.18.10.2			N/A
2 Interrupt handling and execution	No interrupt or too frequent interrupt	Functional test, or time-slot monitoring	H.2.16.5 H.2.18.10.4			N/A
3 Clock	Wrong frequency (for quartz synchronized clock: harmonics/sub-harmonics only)	Frequency monitoring, or time slot monitoring	H.2.18.10.1 H.2.18.10.4			N/A
4. Memory						N/A
4.1 Invariable memory	All single bit faults	Periodic modified checksum, or multiple checksum, or word protection with single bit redundancy	H.2.19.3.1 H.2.19.3.2 H.2.19.8.2			N/A

IEC 60335-2-9						
Clause	Requirement + Test		Result - Remark			Verdict
4.2 Variable memory	DC fault	Periodic static memory test, or word protection with single bit redundancy	H.2.19.6 H.2.19.8.2			N/A
4.3 Addressing (relevant to variable and invariable memory)	Stuck at	Word protection with single bit redundancy including the address	H.2.19.8.2			N/A
5 Internal data path	Stuck at	Word protection with single bit redundancy	H.2.19.8.2			N/A
5.1 VOID						N/A
5.2 Addressing	Wrong address	Word protection with single bit redundancy including the address	H.2.19.8.2			N/A
6 External communication	Hamming distance 3	Word protection with multi-bit redundancy, or CRC – single work, or Transfer redundancy, or Protocol test	H.2.19.8.1 H.2.19.4.1 H.2.18.2.2 H.2.18.14			N/A
6.1 VOID						N/A
6.2 VOID						N/A
6.3 Timing	Wrong point in time Wrong sequence	Time-slot monitoring, or scheduled transmission Time-slot and logical monitoring, or comparison of redundant communication channels by either: - reciprocal comparison - independent hardware comparator Logical monitoring, or time-slot monitoring, or Scheduled transmission	H.2.18.10.4 H.2.18.18 H.2.18.10.3 H.2.18.15 H.2.18.3 H.2.18.10.2 H.2.18.10.4 H.2.18.18			N/A

IEC 60335-2-9						
Clause	Requirement + Test		Result - Remark			Verdict
7 Input/output periphery	Fault conditions specified in 19.11.2	Plausibility check	H.2.18.13			N/A
7.1 VOID						N/A
7.2 Analog I/O						N/A
7.2.1 A/D and D/A- converter	Fault conditions specified in 19.11.2	Plausibility check	H.2.18.13			N/A
7.2.2 Analog multiplexer	Wrong addressing	Plausibility check	H.2.18.13			N/A
8 VOID						N/A
9 Custom chips ^d e.g. ASIC, GAL, gate array	Any output outside the static and dynamic functional specificatio n	Periodic self-test	H.2.16.6			N/A
<p>NOTE A Stuck-at fault model denotes a fault model representing an open circuit or a non-varying signal level. A DC fault model denotes a stuck-at fault model incorporating short circuit between signal lines.</p> <p>a) For fault/error assessment, some components are divided into their sub-functions. b) For each sub-function in the table, the Table R.2 measure will cover the software fault/error. c) Where more than one measure is given for a sub-function, these are alternatives. d) To be divided as necessary by the manufacturer into sub-functions. e) Table R.1 is applied according to the requirements of R.1 to R.2.2.9 inclusive.</p>						

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict

10.1	TABLE: Power input deviation					P
Input deviation of/at:	P rated (W)	P measured (W)	ΔP	Required ΔP	Remark	
AC 230V; 50Hz	750	717	-4,4%	+5 %/-10 %	ZM-227B	
AC 230V; 50Hz	750	724	-3,5%	+5 %/-10 %	ZM-227	
AC 230V; 50Hz	750	730	-2,7%	+5 %/-10 %	ZM-707	
AC 230V; 50Hz	750	731	-2,5%	+5 %/-10 %	ZM-707B	
AC 230V; 50Hz	1400	1394	-0,4%	+5 %/-10 %	ZM-258B	
AC 230V; 50Hz	800	730	-8,75%	+5 %/-10 %	ZM-268B	
AC 230V; 50Hz	750	734,1	-2,1%	+5 %/-10 %	ZM-202B	
AC 230V; 50Hz	750	728,0	-2,9%	+5 %/-10 %	ZM-228C	
AC 230V	800	759,8	-5,0%	+5 %/-10 %	ZM-267	
AC 230V; 50Hz	1400	1418	+1,3%	+5 %/-10 %	ZM-259B	
AC 230V; 60Hz	1400	1418	+1,3%	+5 %/-10 %	ZM-259B	
AC 230V; 50Hz	750	715,6	-4,6%	+5 %/-10 %	ZM-707C	
AC 230V; 60Hz	750	715,4	-4,6%	+5 %/-10 %	ZM-707C	
AC 230V; 50Hz	750	718,7	-4,2%	+5 %/-10 %	ZM-200B	
AC 230V; 50Hz	750	718,6	-4,2%	+5 %/-10 %	ZM-200B	
AC 230V; 50Hz	1200	1187	-1,1%	+5 %/-10 %	ZM-269B	
AC 230V; 60Hz	1200	1179	-1,8%	+5 %/-10 %	ZM-269B	
AC 230V; 50Hz	800	773,3	-3,3%	+5 %/-10 %	ZM-267B	
AC 230V; 60Hz	800	766,2	-4,2%	+5 %/-10 %	ZM-267B	
AC 230V; 50Hz	1400	1390	-0,7%	+5 %/-10 %	ZM-259	
AC 230V; 60Hz	1400	1386	-1,0%	+5 %/-10 %	ZM-259	
AC 230V; 50Hz	750	727,2	-3,0%	+5 %/-10 %	ZM-207	
AC 230V; 60Hz	750	726,7	-3,1%	+5 %/-10 %	ZM-207	

IEC 60335-2-9					
Clause	Requirement + Test			Result - Remark	Verdict
AC 230V; 50Hz	750	710,4	-5,3%	+5 %/-10 %	ZM-208
AC 230V; 60Hz	750	706,5	-5,8%	+5 %/-10 %	ZM-208
AC 230V; 50Hz	750	717,6	-4,3%	+5 %/-10 %	ZM-206B
AC 230V; 60Hz	750	715,2	-4,6%	+5 %/-10 %	ZM-206B
AC 230V; 50Hz	750	723,5	-3,5%	+5 %/-10 %	ZM-206
AC 230V; 60Hz	750	723,1	-3,6%	+5 %/-10 %	ZM-206
AC 230V; 50Hz	750	724	-3,5%	+5 %/-10 %	ZM-227
Supplementary information:					

10.2	TABLE: Current deviation					N/A
Current deviation of/at:	I rated (A)	I measured (A)	ΔI	Required ΔI	Remark	
Supplementary information:						

11.8	TABLE: Heating test(ZM-227B)			P
	Test voltage (V).....:	263,8V		—
	Ambient (°C).....:	24,2°C		—
Thermocouple locations		Max. temperature rise measured, ΔT (K)	Max. temperature rise limit, ΔT (K)	
Power cord		25,9	50	
Test corner		17,1	65	
Electrical box cover		27,8	Clause 30.1	
Base plastic enclosure(inside)		63,4	Clause 30.1	
Indicator cover(inside)		45,2	Clause 30.1	
Top plastic enclosure(inside)		72,8	Clause 30.1	
Ambient of thermostat		91,9	T-25=225	
Ambient of thermal link		74,7	For reference	
Internal wire(near heating element)		77,7	T-25=155	
Silicone sleeving		70,1	T-25=175	
Handle and projection of the accessible part of handle		6,6	60	
Metal cover		41,2	For reference	
Centre of heating surface		145,2	For reference	

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict

Supplementary information:

11.8	TABLE: Heating test(ZM-707B)		P
	Test voltage (V).....:	260,9V	—
	Ambient (°C).....:	24,1°C	—
Thermocouple locations		Max. temperature rise measured, ΔT (K)	Max. temperature rise limit, ΔT (K)
Power cord		24,8	50
Test corner		15,9	65
Electrical box cover		26,5	Clause 30.1
Base plastic enclosure(inside)		63,8	Clause 30.1
Indicator cover(inside)		46,4	Clause 30.1
Top plastic enclosure(inside)		72,6	Clause 30.1
Ambient of thermostat		91,9	T-25=225
Ambient of thermal link		75,7	For reference
Internal wire(near heating element)		78,2	T-25=155
Silicone sleeving		70,4	T-25=175
Handle and projection of the accessible part of handle		6,2	35
Metal clip		10,5	35
Metal cover		49,6	For reference
Centre of heating surface		145,7	For reference
Supplementary information:			

11.8	TABLE: Heating test(ZM-707)		P
	Test voltage (V).....:	262,4V	—
	Ambient (°C).....:	24,6°C	—
Thermocouple locations		Max. temperature rise measured, ΔT (K)	Max. temperature rise limit, ΔT (K)
Power cord		25,6	50
Test corner		17,1	65
Electrical box cover		27,6	Clause 30.1
Base plastic enclosure(inside)		63,2	Clause 30.1
Indicator cover(inside)		45,7	Clause 30.1
Top plastic enclosure(inside)		72,1	Clause 30.1

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Ambient of thermostat	91,2	T-25=225
	Ambient of thermal link	72,4	For reference
	Internal wire(near heating element)	77,3	T-25=155
	Silicone sleeving	69,9	T-25=175
	Handle and projection of the accessible part of handle	6,0	35
	Metal clip	9,6	35
	Centre of heating surface	148,3	For reference
Supplementary information:			

11.8	TABLE: Heating test(ZM-258B)		P
	Test voltage (V).....:	266,8V	—
	Ambient (°C).....:	23,8°C	—
Thermocouple locations		Max. temperature rise measured, ΔT (K)	Max. temperature rise limit, ΔT (K)
	Power cord	28,9	50
	Test corner	17,2	65
	Electrical box cover	25,4	Clause 30.1
	Base plastic enclosure(inside)	96,5	Clause 30.1
	Indicator cover(inside)	52,9	Clause 30.1
	Top plastic enclosure(inside)	99,8	Clause 30.1
	Ambient of thermostat	90,6	T-25=225
	Ambient of thermal link	109,6	For reference
	Internal wire(near heating element)	88,0	T-25=155
	Silicone sleeving	119,5	T-25=175
	Handle and projection of the accessible part of handle	30,3	60
	Metal cover	37,2	For reference
	Centre of heating surface	124,0	For reference
Supplementary information:			

11.8	TABLE: Heating test(ZM-227)		P
	Test voltage (V).....:	261,1V	—
	Ambient (°C).....:	24,3°C	—

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Thermocouple locations	Max. temperature rise measured, ΔT (K)	Max. temperature rise limit, ΔT (K)
	Power cord	26,8	50
	Test corner	18,9	65
	Electrical box cover	29,8	Clause 30.1
	Base plastic enclosure(inside)	60,8	Clause 30.1
	Indicator cover(inside)	44,8	Clause 30.1
	Top plastic enclosure(inside)	70,9	Clause 30.1
	Ambient of thermostat	86,6	T-25=225
	Ambient of thermal link	71,9	For reference
	Internal wire(near heating element)	73,7	T-25=155
	Silicone sleeving	87,8	T-25=175
	Handle and projection of the accessible part of handle	9,2	60
	Centre of heating surface	132,7	For reference
Supplementary information:			

11.8	TABLE: Heating test(ZM-268B)		P
	Test voltage (V).....:	270,5V	—
	Ambient (°C).....:	21,8°C	—
	Thermocouple locations	Max. temperature rise measured, ΔT (K)	Max. temperature rise limit, ΔT (K)
	Power cord	24,7	50
	Test corner	16,1	65
	Electrical box cover	16,6	Clause 30.1
	Base plastic enclosure(inside)	94	Clause 30.1
	Indicator cover(inside)	8,6	Clause 30.1
	Top plastic enclosure(inside)	40,5	Clause 30.1
	Ambient of thermostat	145,7	T-25=225
	Ambient of thermal link	135,5	For reference
	Internal wire(near heating element)	58,2	T-25=155
	Silicone sleeving	78,9	T-25=175
	Handle and projection of the accessible part of handle	1,5	60
	Metal cover	29,4	For reference

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Centre of heating surface	74,4	For reference
Supplementary information: Sandwich maker function			

11.8	TABLE: Heating test(ZM-268B)		P
	Test voltage (V).....:	270,5V	—
	Ambient (°C).....:	21,1°C	—
Thermocouple locations		Max. temperature rise measured, ΔT (K)	Max. temperature rise limit, ΔT (K)
Power cord		27,2	50
Test corner		17,5	65
Electrical box cover		18,7	Clause 30.1
Base plastic enclosure(inside)		73,0	Clause 30.1
Indicator cover(inside)		6,8	Clause 30.1
Top plastic enclosure(inside)		44,6	Clause 30.1
Ambient of thermostat		112,0	T-25=225
Ambient of thermal link		74,5	For reference
Internal wire(near heating element)		60,6	T-25=155
Silicone sleeving		67,2	T-25=175
Handle and projection of the accessible part of handle		0,5	60
Metal cover		31,6	For reference
Centre of heating surface		151,0	For reference
Supplementary information: Griddle function			

11.8	TABLE: Heating test(ZM-267)		P
	Test voltage (V).....:	269,7V	—
	Ambient (°C).....:	24,2°C	—
Thermocouple locations		Max. temperature rise measured, ΔT (K)	Max. temperature rise limit, ΔT (K)
Power cord		29,5	50
Test corner		23,3	65
Electrical box cover		29,0	Clause 30.1
Base plastic enclosure(inside)		104,8	Clause 30.1
Indicator cover(inside)		90,4	Clause 30.1
Top plastic enclosure(inside)		93,9	Clause 30.1

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Ambient of thermostat	131,2	T-25=225
	Ambient of thermal link	116,4	For reference
	Internal wire(near heating element)	127,7	T-25=155
	Silicone sleeving	115,2	T-25=175
	Handle and projection of the accessible part of handle	33,4	60
	Metal cover	47,6	For reference
	Centre of heating surface	202,3	For reference
Supplementary information:			

11.8	TABLE: Heating test(ZM-259B)		P
	Test voltage (V):	255,6V	—
	Ambient (°C):	22,9°C	—
Thermocouple locations		Max. temperature rise measured, ΔT (K)	Max. temperature rise limit, ΔT (K)
	Power cord	22,1	50
	Test corner	18,0	65
	Electrical box cover	19,2	Clause 30.1
	Base plastic enclosure(inside)	73,2	Clause 30.1
	Indicator cover(inside)	59,6	Clause 30.1
	Top plastic enclosure(inside)	74,5	Clause 30.1
	Ambient of thermostat	88,6	T-25=225
	Ambient of thermal link	116,9	For reference
	Internal wire(near heating element)	95,1	T-25=155
	Silicone sleeving	160,6	T-25=175
	Handle and projection of the accessible part of handle	32,8	60
	Metal cover	39,8	For reference
	Centre of heating surface	171,0	For reference
Supplementary information:			

11.8	TABLE: Heating test(ZM-707C)		P
	Test voltage (V):	263,7V	—
	Ambient (°C):	23,4°C	—

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Thermocouple locations	Max. temperature rise measured, ΔT (K)	Max. temperature rise limit, ΔT (K)
	Power cord	27,2	50
	Test corner	23,7	65
	Electrical box cover	31,6	Clause 30.1
	Base plastic enclosure(inside)	65,9	Clause 30.1
	Indicator cover(inside)	39,8	Clause 30.1
	Top plastic enclosure(inside)	71,5	Clause 30.1
	Ambient of thermostat	88,7	T-25=225
	Ambient of thermal link	102,8	For reference
	Internal wire(near heating element)	93,1	T-25=155
	Silicone sleeving	132,1	T-25=175
	Grip and 25mm projection of the accessible part of handle	3,8	60
	Handle cliper	17,7	60
	Metal cover	39,2	For reference
	Centre of heating surface	194,2	For reference
Supplementary information:			

11.8	TABLE: Heating test(ZM-200B)		P
	Test voltage (V).....:	262,4V	—
	Ambient (°C).....:	24,6°C	—
	Thermocouple locations	Max. temperature rise measured, ΔT (K)	Max. temperature rise limit, ΔT (K)
	Power cord	24,8	50
	Test corner	15,9	65
	Electrical box cover	26,5	Clause 30.1
	Base plastic enclosure(inside)	63,8	Clause 30.1
	Indicator cover(inside)	46,4	Clause 30.1
	Top plastic enclosure(inside)	72,6	Clause 30.1
	Ambient of thermostat	91,9	T-25=225
	Ambient of thermal link	75,7	For reference
	Internal wire(near heating element)	78,2	T-25=155
	Silicone sleeving	70,4	T-25=175
	Handle and projection of the accessible part of	6,2	35

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
handle			
Metal clip		10,5	35
Metal cover		49,6	For reference
Centre of heating surface		145,7	For reference
Supplementary information:			

11.8	TABLE: Heating test(ZM-259B)		P
	Test voltage (V).....:	255,6V	—
	Ambient (°C).....:	22,9°C	—
Thermocouple locations		Max. temperature rise measured, ΔT (K)	Max. temperature rise limit, ΔT (K)
Power cord		22,1	50
Test corner		18,0	65
Electrical box cover		19,2	Clause 30.1
Base plastic enclosure(inside)		73,2	Clause 30.1
Indicator cover(inside)		59,6	Clause 30.1
Top plastic enclosure(inside)		74,5	Clause 30.1
Ambient of thermostat		88,6	T-25=225
Ambient of thermal link		116,9	For reference
Internal wire(near heating element)		95,1	T-25=155
Silicone sleeving		160,6	T-25=175
Handle and projection of the accessible part of handle		32,8	60
Metal cover		39,8	For reference
Centre of heating surface		171,0	For reference
Supplementary information:			

11.8	TABLE: Heating test(ZM-707C)		P
	Test voltage (V).....:	263,7V	—
	Ambient (°C).....:	23,4°C	—
Thermocouple locations		Max. temperature rise measured, ΔT (K)	Max. temperature rise limit, ΔT (K)
Power cord		27,2	50
Test corner		23,7	65

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Electrical box cover	31,6	Clause 30.1
	Base plastic enclosure(inside)	65,9	Clause 30.1
	Indicator cover(inside)	39,8	Clause 30.1
	Top plastic enclosure(inside)	71,5	Clause 30.1
	Ambient of thermostat	88,7	T-25=225
	Ambient of thermal link	102,8	For reference
	Internal wire(near heating element)	93,1	T-25=155
	Silicone sleeving	132,1	T-25=175
	Grip and 25mm projection of the accessible part of handle	3,8	60
	Handle cliper	17,7	60
	Metal cover	39,2	For reference
	Centre of heating surface	194,2	For reference
Supplementary information:			

11.8	TABLE: Heating test(ZM-269B)		P
	Test voltage (V).....:	261,8V	—
	Ambient (°C).....:	24,8°C	—
	Thermocouple locations	Max. temperature rise measured, ΔT (K)	Max. temperature rise limit, ΔT (K)
	Power cord	22,2	50
	Test corner	18,3	65
	Electrical box cover	20,2	Clause 30.1
	Base plastic enclosure(inside)	51,3	Clause 30.1
	Indicator cover(inside)	45,5	Clause 30.1
	Top plastic enclosure(inside)	60,5	Clause 30.1
	Ambient of thermostat	94,7	T-25=225
	Ambient of thermal link	100,1	For reference
	Internal wire(near heating element)	122,7	T-25=155
	Silicone sleeving	111,9	T-25=175
	Handle and projection of the accessible part of handle	4,9	60
	Metal cover	34,3	For reference
	Centre of heating surface	131,8	For reference
Supplementary information:			

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict

11.8	TABLE: Heating test(ZM-206B)		P
	Test voltage (V).....:	264V	—
	Ambient (°C).....:	24,9°C	—
Thermocouple locations		Max. temperature rise measured, ΔT (K)	Max. temperature rise limit, ΔT (K)
Power cord		17,1	50
Test corner		15,0	65
Electrical box cover		18,9	Clause 30.1
Base plastic enclosure(inside)		63,9	Clause 30.1
Indicator cover(inside)		53,4	Clause 30.1
Top plastic enclosure(inside)		54,1	Clause 30.1
Ambient of thermostat		64,3	T-25=225
Ambient of thermal link		80,4	For reference
Internal wire(near heating element)		59,2	T-25=155
Silicone sleeving		68,5	T-25=175
Grip and 25mm projection of the accessible part of handle		28,0	60
Metal cover		30,5	For reference
Centre of heating surface		126,4	For reference
Supplementary information:			

11.8	TABLE: Heating test(ZM-206)		P
	Test voltage (V).....:	264,8V	—
	Ambient (°C).....:	24,4°C	—
Thermocouple locations		Max. temperature rise measured, ΔT (K)	Max. temperature rise limit, ΔT (K)
Power cord		36,3	50
Test corner		39,2	65
Electrical box cover		31,9	Clause 30.1
Base plastic enclosure(inside)		71,2	Clause 30.1
Indicator cover(inside)		57,6	Clause 30.1
Top plastic enclosure(inside)		75,3	Clause 30.1
Ambient of thermostat		100,9	T-25=225
Ambient of thermal link		110,2	For reference

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Internal wire(near heating element)	86,2	T-25=155
	Silicone sleeving	118,3	T-25=175
	Grip and 25mm projection of the accessible part of handle	44,6	60
	Centre of heating surface	163,9	For reference
Supplementary information:			

11.8	TABLE: Heating test, resistance method					N/A
	Test voltage (V).....:					—
	Ambient, t1 (°C)					—
	Ambient, t2 (°C)					—
Temperature rise of winding	R1 (Ω)	R2 (Ω)	Δ T (K)	Max. Δ T (K)	Insulation class	
Supplementary information:						

13.2	TABLE: Leakage current (ZM-227B)			P
	Heating appliances: 1.15 x rated input (W)....:		939,1W	—
	Motor-operated and combined appliances: 1.06 x rated voltage (V).....:		—	—
Leakage current between			I (mA)	Max. allowed I (mA)
L/N and accessible earthed metal parts			0,011	0,75
L/N and accessible plastic part			0,009	0,35 peak
Supplementary information:				

13.2	TABLE: Leakage current (ZM-707)			P
	Heating appliances: 1.15 x rated input (W)....:		939,1W	—
	Motor-operated and combined appliances: 1.06 x rated voltage (V).....:		—	—
Leakage current between			I (mA)	Max. allowed I (mA)
L/N and accessible earthed metal parts			0,014	0,75
L/N and accessible plastic part			0,008	0,35 peak
Supplementary information:				

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
13.2	TABLE: Leakage current (ZM-258B)		P
	Heating appliances: 1.15 x rated input (W)....:	1502,6W	—
	Motor-operated and combined appliances: 1.06 x rated voltage (V)	—	—
Leakage current between		I (mA)	Max. allowed I (mA)
L/N and accessible earthed metal parts		0,013	0,75
L/N and accessible plastic part		0,010	0,35 peak
Supplementary information:			

13.2	TABLE: Leakage current (ZM-227)		P
	Heating appliances: 1.15 x rated input (W)....:	939,1W	—
	Motor-operated and combined appliances: 1.06 x rated voltage (V)	—	—
Leakage current between		I (mA)	Max. allowed I (mA)
L/N and accessible earthed metal parts		0,013	0,75
L/N and accessible plastic part		0,010	0,35 peak
Supplementary information:			

13.2	TABLE: Leakage current (ZM-268B)		P
	Heating appliances: 1.15 x rated input (W)....:	1001,7	—
	Motor-operated and combined appliances: 1.06 x rated voltage (V)	—	—
Leakage current between		I (mA)	Max. allowed I (mA)
L/N and accessible earthed metal parts		0,07	0,75
L/N and accessible plastic part		0,05	0,35 peak
Supplementary information:			

13.2	TABLE: Leakage current(ZM-267)		P
	Heating appliances: 1.15 x rated input (W)....:	1001,7	—
	Motor-operated and combined appliances: 1.06 x rated voltage (V)	—	—
Leakage current between		I (mA)	Max. allowed I (mA)
L/N and accessible earthed metal parts		0,09	0,75
L/N and accessible plastic part		0,02	0,35 peak

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict

Supplementary information:

13.2	TABLE: Leakage current (ZM-259B)		P
	Heating appliances: 1.15 x rated input (W)...	1753W	—
	Motor-operated and combined appliances: 1.06 x rated voltage (V)	—	—
Leakage current between		I (mA)	Max. allowed I (mA)
L/N and accessible earthed metal parts		0,05	0,75
L/N and accessible plastic part		0,02	0,35 peak

Supplementary information:

13.2	TABLE: Leakage current (ZM-707C)		P
	Heating appliances: 1.15 x rated input (W)...	939,1W	—
	Motor-operated and combined appliances: 1.06 x rated voltage (V)	—	—
Leakage current between		I (mA)	Max. allowed I (mA)
L/N and accessible earthed metal parts		0,05	0,75
L/N and accessible plastic part		0,02	0,35 peak

Supplementary information:

13.2	TABLE: Leakage current (ZM-269B)		P
	Heating appliances: 1.15 x rated input (W)...	1502,6W	—
	Motor-operated and combined appliances: 1.06 x rated voltage (V)	—	—
Leakage current between		I (mA)	Max. allowed I (mA)
L/N and accessible earthed metal parts		0,35	0,75
L/N and accessible plastic part		0,07	0,35 peak

Supplementary information:

13.2	TABLE: Leakage current (ZM-206B)		P
	Heating appliances: 1.15 x rated input (W)...	939,1W	—
	Motor-operated and combined appliances: 1.06 x rated voltage (V)	—	—
Leakage current between		I (mA)	Max. allowed I (mA)

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
L/N and accessible earthed metal parts		0,04	0,75
L/N and accessible plastic part		0,07	0,35 peak
Supplementary information:			

13.3	TABLE: Dielectric strength(ZM-227M, ZM-707B, ZM-258B, ZM-227, ZM-268B, ZM-267, ZM-259B, ZM-707C, ZM-269B, ZM-206B)			P
Test voltage applied between:		Test potential applied (V)	Breakdown / flashover (Yes/No)	
L/N and accessible earthed metal parts		1000	No	
L/N and plastic enclosure, indicator cover		3000	No	
Supplementary information:				

14	TABLE: Transient overvoltages					N/A
Clearance between:	CI (mm)	Required CI (mm)	Rated impulse voltage (V)	Impulse test voltage (V)	Flashover (Yes/No)	
Supplementary information:						

16.2	TABLE: Leakage current (ZM-227)			P
	Single phase appliances: 1.06 x rated voltage (V)	1,06x240=254,4		—
	Three phase appliances 1.06 x rated voltage divided by $\sqrt{3}$ (V).....	—		—
Leakage current between		I (mA)	Max. allowed I (mA)	
L/N and accessible earthed metal parts		0,015	0,75	
L/N and accessible plastic part		0,004	0,25	
Supplementary information:				

16.2	TABLE: Leakage current (ZM-707)			P
	Single phase appliances: 1.06 x rated voltage (V)	1,06x240=254,4		—
	Three phase appliances 1.06 x rated voltage divided by $\sqrt{3}$ (V).....	—		—
Leakage current between		I (mA)	Max. allowed I (mA)	

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
L/N and accessible earthed metal parts		0,015	0,75
L/N and accessible plastic part		0,004	0,25
Supplementary information:			

16.2	TABLE: Leakage current (ZM-258B)		P
	Single phase appliances: 1.06 x rated voltage (V)	1,06x240=254,4	—
	Three phase appliances 1.06 x rated voltage divided by $\sqrt{3}$ (V).....	—	—
Leakage current between		I (mA)	Max. allowed I (mA)
L/N and accessible earthed metal parts		0,015	0,75
L/N and accessible plastic part		0,005	0,25
Supplementary information:			

16.2	TABLE: Leakage current (ZM-268B)		P
	Single phase appliances: 1.06 x rated voltage (V)	1,06x240=254,4	—
	Three phase appliances 1.06 x rated voltage divided by $\sqrt{3}$ (V).....	—	—
Leakage current between		I (mA)	Max. allowed I (mA)
L/N and accessible earthed metal parts		0,07	0,75
L/N and accessible plastic part		0,06	0,25
Supplementary information:			

16.2	TABLE: Leakage current (ZM-267)		P
	Single phase appliances: 1.06 x rated voltage (V)	1,06x240=254,4	—
	Three phase appliances 1.06 x rated voltage divided by $\sqrt{3}$ (V).....	—	—
Leakage current between		I (mA)	Max. allowed I (mA)
L/N and accessible earthed metal parts		0,14	0,75
L/N and accessible plastic part		0,05	0,25
Supplementary information:			

16.2	TABLE: Leakage current (ZM-259B)		P
------	----------------------------------	--	---

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
	Single phase appliances: 1.06 x rated voltage (V)	1,06x240=254,4	—
	Three phase appliances 1.06 x rated voltage divided by $\sqrt{3}$ (V).....	—	—
Leakage current between		I (mA)	Max. allowed I (mA)
L/N and accessible earthed metal parts		0,09	0,75
L/N and accessible plastic part		0,04	0,25
Supplementary information:			

16.2	TABLE: Leakage current (ZM-269B)		P
	Single phase appliances: 1.06 x rated voltage (V)	1,06x240=254,4	—
	Three phase appliances 1.06 x rated voltage divided by $\sqrt{3}$ (V).....	—	—
Leakage current between		I (mA)	Max. allowed I (mA)
L/N and accessible earthed metal parts		0,09	0,75
L/N and accessible plastic part		0,02	0,25
Supplementary information:			

16.3	TABLE: Dielectric strength(ZM-258B, ZM-268B, ZM-267, ZM-259B, ZM-269B)		P
Test voltage applied between:		Test potential applied (V)	Breakdown / flashover (Yes/No)
L/N and accessible earthed metal parts		1250	No
L/N and plastic enclosure, indicator cover		3000	No
Supplementary information:			

17	TABLE: Overload protection		N/A
Thermocouple locations		Max. temperature rise measured, ΔT (K)	Max. temperature rise limit, ΔT (K)
Supplementary information:			

17	TABLE: Overload protection, resistance method		N/A
	Test voltage (V).....		—

IEC 60335-2-9						
Clause	Requirement + Test			Result - Remark		Verdict
	Ambient, t1 (°C)					—
	Ambient, t2 (°C)					—
Temperature of winding		R1 (Ω)	R2 (Ω)	Δ T (K)	T (°C)	Max. T (°C)
Supplementary information:						

19	Abnormal operation conditions						P
Operational characteristics	YES/NO	Operational conditions					
Are there electronic circuits to control the appliance operation?	NO						
Are there “off” or “stand-by” position?	NO						
The unintended operation of the appliance results in dangerous malfunction?	NO						
Sub-clause	Operating conditions description	Test results description	PEC description	EMP 19.11.4	Software type required	19.11.3 PEC	Final result
19.2				N.A			P
19.3							P
19.4							P
19.5							P
19.6				N.A			N/A
19.7							N/A
19.8							N/A
19.9							N/A
19.10							N/A
19.11.2							N/A
19.11.4.8							N/A
19.10X							N/A
Supplementary information:							

19.7	TABLE: Abnormal operation, locked rotor/moving parts					N/A
	Test voltage (V).....					—

IEC 60335-2-9						
Clause	Requirement + Test	Result - Remark			Verdict	
	Ambient, t1 (°C)				—	
	Ambient, t2 (°C)				—	
	Temperature of winding	R1 (Ω)	R2 (Ω)	Δ T (K)	T (°C)	Max. T (°C)
Supplementary information:						

19.9	TABLE: Abnormal operation, running overload					N/A
	Test voltage (V).....					—
	Ambient, t1 (°C)					—
	Ambient, t2 (°C)					—
	Temperature of winding	R1 (Ω)	R2 (Ω)	Δ T (K)	T (°C)	Max. T (°C)
Supplementary information:						

19.13	TABLE: Abnormal operation, temperature rises(ZM-707)				P
	Thermocouple locations	Max. temperature rise measured, Δ T (K)		Max. temperature rise limit, Δ T (K)	
		19.3	19.4		
	Power cord	26,4	55,6	150	
	Test corner	19,2	18,7	150	
	Electrical box cover	28,3	—	Clause 30.1	
	Base plastic enclosure(inside)	65,0	—	Clause 30.1	
	Indicator cover(inside)	45,9	—	Clause 30.1	
	Top plastic enclosure(inside)	73,4	—	Clause 30.1	
	Ambient of thermal link	73,7	253,7	For reference	

19.13	TABLE: Abnormal operation, temperature rises(ZM-707B)				P
	Thermocouple locations	Max. temperature rise measured, Δ T (K)		Max. temperature rise limit, Δ T (K)	
		19.3	19.4		
	Power cord	25,4	54,5	150	
	Test corner	15,9	16,9	150	
	Electrical box cover	27,0	—	Clause 30.1	
	Base plastic enclosure(inside)	63,4	—	Clause 30.1	
	Indicator cover(inside)	46,3	—	Clause 30.1	

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
Top plastic enclosure(inside)	72,6	—	Clause 30.1
Ambient of thermal link	75,6	254,9	For reference

19.13	TABLE: Abnormal operation, temperature rises(ZM-258B)		P
Thermocouple locations	Max. temperature rise measured, ΔT (K)		Max. temperature rise limit, ΔT (K)
	19.3	19.4	
Power cord	30,3	39,6	150
Test corner	19,4	18,3	150
Electrical box cover	27,0	—	Clause 30.1
Base plastic enclosure(inside)	97,8	—	Clause 30.1
Indicator cover(inside)	54,0	—	Clause 30.1
Top plastic enclosure(inside)	100,9	—	Clause 30.1
Ambient of thermal link	115,4	263,0	For reference

19.13	TABLE: Abnormal operation, temperature rises(ZM-268B)		P
Thermocouple locations	Max. temperature rise measured, ΔT (K)		Max. temperature rise limit, ΔT (K)
	19.3	19.4	
Power cord	23,1	33,5	150
Test corner	18,3	29,8	150
Electrical box cover	18,4	—	Clause 30.1
Base plastic enclosure(inside)	121,2	—	Clause 30.1
Indicator cover(inside)	10,3	—	Clause 30.1
Top plastic enclosure(inside)	41,7	—	Clause 30.1
Ambient of thermal link	133,8	276,1	For reference

Supplementary information: Sandwich maker function

19.13	TABLE: Abnormal operation, temperature rises(ZM-268B)		P
Thermocouple locations	Max. temperature rise measured, ΔT (K)		Max. temperature rise limit, ΔT (K)
	19.3	19.4	
Power cord	30,7	27,9	150
Test corner	17,6	19,8	150
Electrical box cover	21,7	—	Clause 30.1
Base plastic enclosure(inside)	75,7	—	Clause 30.1

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
Indicator cover(inside)	3,0	—	Clause 30.1
Top plastic enclosure(inside)	45,8	—	Clause 30.1
Ambient of thermal link	75,2	275,0	For reference
Supplementary information: Griddle function			

19.13	TABLE: Abnormal operation, temperature rises(ZM-267)		P
Thermocouple locations	Max. temperature rise measured, ΔT (K)		Max. temperature rise limit, ΔT (K)
	19.3	19.4	
Power cord	31,1	47,7	150
Test corner	25,1	48,9	150
Electrical box cover	30,9	—	Clause 30.1
Base plastic enclosure(inside)	105,2	—	Clause 30.1
Indicator cover(inside)	93,6	—	Clause 30.1
Top plastic enclosure(inside)	97,9	—	Clause 30.1
Supplementary information:			

19.13	TABLE: Abnormal operation, temperature rises(ZM-259B)		P
Thermocouple locations	Max. temperature rise measured, ΔT (K)		Max. temperature rise limit, ΔT (K)
	19.3	19.4	
Power cord	22,2	37,9	150
Test corner	19,4	37,3	150
Electrical box cover	21,2	—	Clause 30.1
Base plastic enclosure(inside)	87,2	—	Clause 30.1
Indicator cover(inside)	63,4	—	Clause 30.1
Top plastic enclosure(inside)	79,1	—	Clause 30.1

19.13	TABLE: Abnormal operation, temperature rises(ZM-707C)		P
Thermocouple locations	Max. temperature rise measured, ΔT (K)		Max. temperature rise limit, ΔT (K)
	19.3	19.4	
Power cord	27,4	57,7	150
Test corner	24,2	58,5	150
Electrical box cover	31,7	—	Clause 30.1
Base plastic enclosure(inside)	68,1	—	Clause 30.1

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict
Indicator cover(inside)	40,6	—	Clause 30.1
Top plastic enclosure(inside)	73,8	—	Clause 30.1

19.13	TABLE: Abnormal operation, temperature rises(ZM-269B)			P
Thermocouple locations	Max. temperature rise measured, ΔT (K)		Max. temperature rise limit, ΔT (K)	
	19.3	19.4		
Power cord	21,4	37,3	150	
Test corner	17,3	31,3	150	
Electrical box cover	19,6	—	Clause 30.1	
Base plastic enclosure(inside)	54,1	—	Clause 30.1	
Indicator cover(inside)	47,2	—	Clause 30.1	
Top plastic enclosure(inside)	63,9	—	Clause 30.1	

24.1	TABLE: Critical components information(See CDF ZC10-SS-50087662 001)					P
Object / part No.	Manufacturer/ trademark	Type / model	Technical data	Standard	Mark(s) of conformity ¹⁾	
Supplementary information:						
1) Provided evidence ensures the agreed level of compliance. See OD-CB2039.						
2) For the mark of conformity with *, it means the components also tested with appliance accordingly.						

28.1	TABLE: Threaded part torque test			P
Threaded part identification	Diameter of thread (mm)	Column number (I, II, or III)	Applied torque (Nm)	
Screw for fixing earthing terminal	2,85	II	0,5	
Supplementary information:				

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict

29.1	TABLE: Clearances					P
	Overvoltage category	II			—	
		Type of insulation:				
Rated impulse voltage (V):	Min. cl (mm)	Basic (mm)	Supplementary (mm)	Reinforced (mm)	Functional (mm)	Verdict / Remark
330	0,2* / 0,5 / 0,8**	—	—	—	—	N/A
500	0,2* / 0,5 / 0,8**	—	—	—	—	N/A
800	0,2* / 0,5 / 0,8**	—	—	—	—	N/A
1 500	0,5 / 0,8** / 1,0***	—	—	—	—	N/A
2 500	1,5 / 2,0***	Note1 (2,0mm)	Note2 (2,0mm)	—	Note3 (2,0mm)	P
4 000	3,0 / 3,5***	—	—	Note4 (3,5mm)	—	P
6 000	5,5 / 6,0***	—	—	—	—	N/A
8 000	8,0 / 8,5***	—	—	—	—	N/A
10 000	11,0 / 11,5***	—	—	—	—	N/A

Supplementary information:

*) For tracks on printed circuit boards if pollution degree 1 and 2

**) For pollution degree 3

***) If the construction is affected by wear, distortion, movement of the parts or during assembly

Remark:

Note1: Basic insulation: live part of heating element(inside silicone sealing) to accessible earthed metal part: Cl. = 2,0mm (pollution degree 1), live part of heating element(outside silicone sealing) to accessible earthed metal part: Cl. = 4,0mm (pollution degree 3)

Note2: Supplementary insulation: internal wire to accessible plastic enclosure: Cl. = 4,0mm

Note3: Functional insulation: L-N of power cord: Cl.=8,0mm;

Note4: Reinforced insulation: Live parts to accessible plastic enclosure: Cl.= 10,0mm

IEC 60335-2-9											
Clause	Requirement + Test							Result - Remark			Verdict
29.2	TABLE: Creepage distances, basic, supplementary and reinforced insulation										P
Working voltage (V)	Creepage distance (mm) Pollution degree							Type of insulation			—
	1	2			3						
	Material group			Material group				—			—
	I	II	IIIa/IIIb	I	II	IIIa/IIIb*)	B**)	S**)	R**)	Verdict	
≤50	0,18	0,6	0,85	1,2	1,5	1,7	1,9		—	—	N/A
≤50	0,18	0,6	0,85	1,2	1,5	1,7	1,9	—		—	N/A
≤50	0,36	1,2	1,7	2,4	3,0	3,4	3,8	—	—		N/A
125	0,28	0,75	1,05	1,5	1,9	2,1	2,4		—	—	N/A
125	0,28	0,75	1,05	1,5	1,9	2,1	2,4	—		—	N/A
125	0,56	1,5	2,1	3,0	3,8	4,2	4,8	—	—		N/A
<u>250</u>	<u>0,56</u>	1,25	1,8	2,5	3,2	3,6	<u>4,0</u>	Note 1	—	—	P
<u>250</u>	0,56	1,25	1,8	2,5	3,2	3,6	<u>4,0</u>	—	Note 2	—	P
<u>250</u>	1,12	2,5	3,6	5,0	6,4	7,2	<u>8,0</u>	—	—	Note 3	P
400	1,0	2,0	2,8	4,0	5,0	5,6	6,3		—	—	N/A
400	1,0	2,0	2,8	4,0	5,0	5,6	6,3	—		—	N/A
400	2,0	4,0	5,6	8,0	10,0	11,2	12,6	—	—		N/A
500	1,3	2,5	3,6	5,0	6,3	7,1	8,0		—	—	N/A
500	1,3	2,5	3,6	5,0	6,3	7,1	8,0	—		—	N/A

IEC 60335-2-9											
Clause	Requirement + Test							Result - Remark			Verdict
500	2,6	5,0	7,2	10,0	12,6	14,2	16,0	—	—		N/A
>630 and ≤800	1,8	3,2	4,5	6,3	8,0	9,0	10,0		—	—	N/A
>630 and ≤800	1,8	3,2	4,5	6,3	8,0	9,0	10,0	—		—	N/A
>630 and ≤800	3,6	6,4	9,0	12,6	16,0	18,0	20,0	—	—		N/A
>800 and ≤1000	2,4	4,0	5,6	8,0	10,0	11,0	12,5		—	—	N/A
>800 and ≤1000	2,4	4,0	5,6	8,0	10,0	11,0	12,5	—		—	N/A
>800 and ≤1000	4,8	8,0	11,2	16,0	20,0	22,0	25,0	—	—		N/A
>1000 and ≤1250	3,2	5,0	7,1	10,0	12,5	14,0	16,0		—	—	N/A
>1000 and ≤1250	3,2	5,0	7,1	10,0	12,5	14,0	16,0	—		—	N/A
>1000 and ≤1250	6,4	10,0	14,2	20,0	25,0	28,0	32,0	—	—		N/A
>1250 and ≤1600	4,2	6,3	9,0	12,5	16,0	18,0	20,0		—	—	N/A
>1250 and ≤1600	4,2	6,3	9,0	12,5	16,0	18,0	20,0	—		—	N/A
>1250 and ≤1600	8,4	12,6	18,0	25,0	32,0	36,0	40,0	—	—		N/A
>1600 and ≤2000	5,6	8,0	11,0	16,0	20,0	22,0	25,0		—	—	N/A
>1600 and ≤2000	5,6	8,0	11,0	16,0	20,0	22,0	25,0	—		—	N/A
>1600 and ≤2000	11,2	16,0	22,0	32,0	40,0	44,0	50,0	—	—		N/A
>2000 and ≤2500	7,5	10,0	14,0	20,0	25,0	28,0	32,0		—	—	N/A
>2000 and ≤2500	7,5	10,0	14,0	20,0	25,0	28,0	32,0	—		—	N/A
>2000 and ≤2500	15,0	20,0	28,0	40,0	50,0	56,0	64,0	—	—		N/A
>2500 and ≤3200	10,0	12,5	18,0	25,0	32,0	36,0	40,0		—	—	N/A
>2500 and ≤3200	10,0	12,5	18,0	25,0	32,0	36,0	40,0	—		—	N/A
>2500 and ≤3200	20,0	25,0	36,0	50,0	64,0	72,0	80,0	—	—		N/A
>3200 and ≤4000	12,5	16,0	22,0	32,0	40,0	45,0	50,0		—	—	N/A
>3200 and ≤4000	12,5	16,0	22,0	32,0	40,0	45,0	50,0	—		—	N/A
>3200 and ≤4000	25,0	32,0	44,0	64,0	80,0	90,0	100,0	—	—		N/A
>4000 and ≤5000	16,0	20,0	28,0	40,0	50,0	56,0	63,0		—	—	N/A
>4000 and ≤5000	16,0	20,0	28,0	40,0	50,0	56,0	63,0	—		—	N/A
>4000 and ≤5000	32,0	40,0	56,0	80,0	100,0	112,0	126,0	—	—		N/A
>5000 and ≤6300	20,0	25,0	36,0	50,0	63,0	71,0	80,0		—	—	N/A
>5000 and ≤6300	20,0	25,0	36,0	50,0	63,0	71,0	80,0	—		—	N/A
>5000 and ≤6300	40,0	50,0	72,0	100,0	126,0	142,0	160,0	—	—		N/A

IEC 60335-2-9											
Clause	Requirement + Test								Result - Remark		Verdict
>6300 and ≤8000	25,0	32,0	45,0	63,0	80,0	90,0	100,0		—	—	N/A
>6300 and ≤8000	25,0	32,0	45,0	63,0	80,0	90,0	100,0	—		—	N/A
>6300 and ≤8000	50,0	64,0	90,0	126,0	160,0	180,0	200,0	—	—		N/A
>8000 and ≤10000	32,0	40,0	56,0	80,0	100,0	110,0	125,0		—	—	N/A
>8000 and ≤10000	32,0	40,0	56,0	80,0	100,0	110,0	125,0	—		—	N/A
>8000 and ≤10000	64,0	80,0	112,0	160,0	200,0	220,0	250,0	—	—		N/A
>10000 and ≤12500	40,0	50,0	71,0	100,0	125,0	140,0	160,0		—	—	N/A
>10000 and ≤12500	40,0	50,0	71,0	100,0	125,0	140,0	160,0	—		—	N/A
>10000 and ≤12500	80,0	100,0	142,0	200,0	250,0	280,0	320,0	—	—		N/A
Supplementary information:											
*) Material group IIIb is allowed if the working voltage does not exceed 50 V											
**) B = Basic insulation, S = Supplementary insulation, R = Reinforced insulation											
Note1: Basic insulation: live part of heating element(inside silicone sealing) to accessible earthed metal part: Cr. = 2,0mm (pollution degree 1), live part of heating element(outside silicone sealing) to accessible earthed metal part: Cr. = 5,0mm (pollution degree 3)											
Note2: Supplementary insulation: internal wire to accessible plastic enclosure: Cr. = 4,5mm											
Note3: Reinforced insulation: Live parts to accessible plastic enclosure: Cr.= 15,0mm											

IEC 60335-2-9			
Clause	Requirement + Test	Result - Remark	Verdict

29.2	TABLE: Creepage distances, functional insulation							P
Working voltage (V)	Creepage distance (mm) Pollution degree							Verdict / Remark
	1	2			3			
	Material group			Material group				
	I	II	IIIa/IIIb	I	II	IIIa/IIIb*)		
≤10	0,08	0,4	0,4	0,4	1,0	1,0	1,0	N/A
50	0,16	0,56	0,8	1,0	1,4	1,6	1,8	N/A
125	0,25	0,71	1,0	1,4	1,8	2,0	2,2	N/A
250	0,42	1,0	1,4	2,0	2,5	2,8	3,2 Note 1	P
400	0,75	1,6	2,2	3,2	4,0	4,5	5,0	N/A
500	1,0	2,0	2,8	4,0	5,0	5,6	6,3	N/A
>630 and ≤800	1,8	3,2	4,5	6,3	8,0	9,0	10,0	N/A
>800 and ≤1000	2,4	4,0	5,6	8,0	10,0	11,0	12,5	N/A
>1000 and ≤1250	3,2	5,0	7,1	10,0	12,5	14,0	16,0	N/A
>1250 and ≤1600	4,2	6,3	9,0	12,5	16,0	18,0	20,0	N/A
>1600 and ≤2000	5,6	8,0	11,0	16,0	20,0	22,0	25,0	N/A
>2000 and ≤2500	7,5	10,0	14,0	20,0	25,0	28,0	32,0	N/A
>2500 and ≤3200	10,0	12,5	18,0	25,0	32,0	36,0	40,0	N/A
>3200 and ≤4000	12,5	16,0	22,0	32,0	40,0	45,0	50,0	N/A
>4000 and ≤5000	16,0	20,0	28,0	40,0	50,0	56,0	63,0	N/A
>5000 and ≤6300	20,0	25,0	36,0	50,0	63,0	71,0	80,0	N/A
>6300 and ≤8000	25,0	32,0	45,0	63,0	80,0	90,0	100,0	N/A
>8000 and ≤10000	32,0	40,0	56,0	80,0	100,0	110,0	125,0	N/A
>10000 and ≤12500	40,0	50,0	71,0	100,0	125,0	140,0	160,0	N/A

Supplementary information:

*) Material group IIIb is allowed if the working voltage does not exceed 50 V

Note 1:
Functional insulation: L-N of power cord: Cr.=15,0mm

30		TABLE: Resistance to heat and fire																	P	
Object/ part No.	Manufacture r/ trademark	Type/ model	Ball pressure test °C				Glow wire test (GWT) °C				Glow-wire flammability index (GWFI) °C				Glow- wire ignition temp. (GWIT) °C		Needle- flame test (NFT)	Verdict		
			75	125	cl. 11 +40	cl. 19 +25	550	650		750		850	550	650	750	850			675	775
							te		ti											
Plastic enclosure ⁷⁾	--	--	--	--	146,2 °C	--	--	--	--	30	30	--	--	--	--	--	--	--	P	
Electrical box cover ⁷⁾	--	--	√	--	--	--	--	--	--	30	30	--	--	--	--	--	--	--	P	
Indicator cover	--	--	--	--	100°C	--	√	--	--	--	--	--	--	--	--	--	--	--	P	
Wire connector	--	--	--	--	--	--	--	--	--	30	10	--	--	--	--	--	--	--	P	

Supplementary information:

- 1) Parts of material classified at least HB40 or if relevant HBF
- 2) Parts of material classified as V-0 or V-1
- 3) Flame persisting longer than 2 s (= te – ti) need only be reported for unattended appliances
- 4) Surrounding parts subjected to the needle-flame test of annex E
- 5) Base material classified as V-0 or if relevant VTM-0
- 6) The GWIT pre-selection option, the 850 °C GWFI pre-selection option, and the 850 °C GWT are not applicable for attended appliances
- 7) Wire connector was tested with plastic enclosure and electrical box cover.

IEC60335_2_9J - ATTACHMENT			
Clause	Requirement - Test	Result - Remark	Verdict

ATTACHMENT TO TEST REPORT IEC 60335-2-9 EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES	
Household and similar electrical appliances – Safety – Part 2: Particular requirements for grills, toasters and similar cooking appliances	
Differences according to:	EN 60335-2-9:2003 + A1:2004 + A2:2006 + A12:2007 +A13:2010 used in conjunction with EN 60335-1:2012 EN 62233:2008
Attachment Form No.:	EU_GD_IEC60335_2_9J
Attachment Originator:	LCIE
Master Attachment:	2014-01
Copyright © 2014 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.	

IEC60335_2_9J - ATTACHMENT			
Clause	Requirement - Test	Result - Remark	Verdict
	CENELEC COMMON MODIFICATIONS		
6.1	Delete "class 0" and "class 01"		P
7.1	Single-phase appliances to be connected to the supply mains: 230 V covered		P
	Multi-phase appliances to be connected to the supply mains: 400 V covered		N/A
7.10	Devices used to start/stop operational functions of the appliance distinguished from other manual devices by means of shape, size, surface texture, position, etc.		N/A
	Devices used to start/stop operational functions of the appliance, if any, shall be distinguished from other manual devices by means of shape, or size, or surface texture, or position, etc. A tactile or an audible and visual feedback shall give an indication that the device has been operated (EN 60335-2-9)		N/A
	An indication that the device has been operated is given by:		N/A
	<ul style="list-style-type: none"> • a tactile feedback, or 		N/A
	<ul style="list-style-type: none"> • an audible and visual feedback 		N/A
7.12	The instructions include the substance of the following:		P
	- this appliance can be used by children aged from 8 years and above and persons with reduced physical, sensory or mental capabilities or lack of experience and knowledge if they have been given supervision or instruction concerning use of the appliance in a safe way and understand the hazards involved		P
	- children shall not play with the appliance		P
	- cleaning and user maintenance shall not be made by children without supervision		P
	Children shall not play with the appliance. Cleaning and user maintenance shall not be made by children unless they are older than 8 and supervised. Keep the appliance and its cord out of reach of children less than 8 years. (EN 60335-2-9)		P
7.12.Z1	The specific instructions related to the safe operation of this appliance is collated together in the front section of the user instructions		P
	The height of the characters, measured on the capital letters, is at least 3 mm		P
	These instructions are also available in an alternative format, e.g. on a website		P

IEC60335_2_9J - ATTACHMENT			
Clause	Requirement - Test	Result - Remark	Verdict
7.12.Z101	The specific instructions related to the safe operation of this appliance (as given in 7.12 of this standard) shall be collated together in the front section of the user instructions. The height of the characters, measured on the capital letters, shall be at least 3 mm (EN 60335-2-9)		P
8.1.1	Also test probe 18 of EN 61032 is applied		P
	The appliance being in every possible position during the test		P
	The force on the probe in the straight position is increased to 10 N when probe 18 is used		P
	When using test probe 18 the appliance is fully assembled as in normal use without any parts removed, and		P
	parts intended to be removed for user maintenance are also not removed		P
8.2	Compliance is checked by applying the test probes of EN 61032		P
	For built-in appliances and fixed appliances, the test probe B and probe 18 of EN 61032 are applied only after installation		N/A
11.1	For ovens, rotary grills, rotisseries and cookers, compliance is also checked by the test of 11.Z101. (EN 60335-2-9)		N/A
	For contact grills, waffle irons, sandwich makers, radiant grills, raclette grills, griddles, barbecues, hot plates, candy floss, popcorn makers, compliance is also checked by the test of 11.Z102. (EN 60335-2-9)		P
	For breadmakers and food dehydrators, compliance is also checked by the test of 11.Z103. (EN 60335-2-9)		N/A
	For toasters, compliance is also checked by test of 11.Z104. (EN 60335-2-9)		N/A
	For roasters, compliance is also checked by test of 11.Z105. (EN 60335-2-9)		N/A
	For all other types of appliances, compliance is checked by submitting the appliance to the tests of the nearest mentioned relevant type of appliance. (EN 60335-2-9)		N/A
11.3	For flat surfaces, temperature rises are measured using the probe of figure Z101(or any measuring instrument giving the same results), applied with a force of 4 N ± 1 N. (EN 60335-2-9)		P
11.8	Footnotes to “External enclosure of motor-operated appliances” to be taken into account		N/A

IEC60335_2_9J - ATTACHMENT			
Clause	Requirement - Test	Result - Remark	Verdict
11.8	The temperature rise of handles or grips and that of operational devices such as switches, keypads and knobs that are intended to be touched in normal use is measured as follows: (EN 60335-2-9)		P
	-for operational devices and grips with a surface greater than 300mm², over an area of 20mm around the part normally gripped or touched to operate the appliance		P
	-for operational devices and grips with a surface less than or equal to 300mm², over an area of 25mm around the part normally gripped or touched to operate the appliance		P
	The hot part of operational devices and grips cannot be touched unintentionally		P
	-for handles, over an area of 20mm around the orthogonal projection of all points located at the clearance less than 40mm between the rear part of the handle ,or at least 80mm along the handle and the hot part.		P
	The hot part of handles cannot be touched unintentionally		N/A
	--for surfaces of handles, knobs, grips and similar parts which are held for short periods, table 3 applies		P
11.Z101	Ovens, rotary grills and cookers are placed as specified in 11.2. Appliance supplied at rated power, and operated under normal operation (EN 60335-2-9)		N/A
	Ovens, rotary grills, rotisseries and cookers are supplied at rated power and operated under normal operation. (EN 60335-2-9)		N/A
	All heating units that can be connected to the supply mains at the same time during normal use are switched on. (EN 60335-2-9)		N/A
	Ovens are operated without accessories (EN 60335-2-9)		N/A
	Temperature rise of the surfaces not exceeding the values of table Z101 (EN 60335-2-9)	(See appended table)	N/A
	Ovens having settings higher than 240°C, are also operated at the maximum setting until steady state conditions are established or for 60min, whichever is shorter. The temperature rise limits of table Z101 for top surfaces and door surfaces are increased by 10K (EN 60335-2-9)	(See appended table)	N/A

IEC60335_2_9J - ATTACHMENT			
Clause	Requirement - Test	Result - Remark	Verdict
11.Z102	tact grills, waffle irons, sandwich makers, radiant grills, raclette grills, griddles, the temperature rise limits for top surfaces in table Z101 apply. (EN 60335-2-9)	Sandwich maker	P
	For contact grills, waffle irons, sandwich makers, radiant grills, raclette grills and griddles, barbecues, hot plates, candy floss, popcorn makers, the temperature rise limits in Table Z101 apply. The appliance is supplied at rated power and operated under normal operation. (EN 60335-2-9)		P
11.Z103	For breadmakers, the temperature rise limits for other surfaces in table Z101 apply. (EN 60335-2-9)		N/A
	For breadmakers and food dehydrators, the temperature rise limits in Table Z101 apply. The appliance is supplied at rated power and operated under normal operation. (EN 60335-2-9)		N/A
11.Z104	For toasters, the temperature rise limits in Table Z101 apply. The appliance is operated for three cycles at rated power and operated under normal operation. (EN 60335-2-9)		N/A
11.Z105	For roasters, the temperature rise limits in Table Z101 apply. The appliance is supplied at rated power and operated under normal operation. (EN 60335-2-9)		N/A
15.1.2	Appliances with an automatic cord reel tested with the cord in the most unfavourable position so that the reeling of the wet cord may affect electrical insulation during operation, the cord not being dried before reeling		N/A
20.2	When using the test probe similar to test probe B with a circular stop face, the accessories and detachable covers are removed		N/A
	Test probe 18 applied with a force of 2,5N on the appliance fully assembled		N/A
	Appliances are fully assembled as in normal operation without any parts removed. (EN 60335-2-9)		N/A
24.1	Components comply with the safety requirements specified in the relevant standards as far as they reasonably apply		P
	The requirements of Clause 29 of this standard apply between live parts of components and accessible parts of the appliance.		P
	The requirements of 30.2 of this standard apply to parts of non-metallic material in components including parts of non-metallic material supporting current-carrying connections inside components		P

IEC60335_2_9J - ATTACHMENT			
Clause	Requirement - Test	Result - Remark	Verdict
	Components that have not been previously tested or do not comply with the standard for the relevant component are tested according to the requirements of 30.2		P
	Components that have been previously tested and shown to comply with the resistance to fire requirements in the standard for the relevant component need not be retested provided that:		P
	- the severity specified in the component standard is not less than the severity specified in 30.2, and		P
	- the test report for the component states whether it complied with the standard for the relevant component with or without flame, flames not exceeding 2 s during the test are ignored		P
	Unless components have been previously tested and found to comply with the relevant standard for the number of cycles specified, they are tested in accordance with 24.1.1 to 24.1.9		P
	For components mentioned in 24.1.1 to 24.1.9, no additional tests specified in the relevant standard for the component are necessary other than those specified in 24.1.1 to 24.1.9		P
	Components that have not been separately tested and found to comply with the relevant standard, and		P
	components that are not marked or not used in accordance with their marking,		P
	are tested in accordance with the conditions occurring in the appliance, the number of samples being that required by the relevant standard		P
	Lamp holders and starter holders that have not been previously tested and found to comply with the relevant standard are tested as a part of the appliance and additionally comply with the gauging and interchangeability requirements of the relevant standard under the conditions occurring in the appliance		N/A
	Where the relevant standard specifies these gauging and interchangeability requirements at elevated temperatures, the temperatures measured during the tests of Clause 11 are used		N/A
	Plugs and socket-outlets and other connecting devices of interconnection cords are not interchangeable with plugs and socket-outlets listed in IEC/TR 60083 or IEC 60906-1, or		N/A
	with connectors and appliance inlets complying with the standard sheets of IEC 60320-1,		N/A

IEC60335_2_9J - ATTACHMENT			
Clause	Requirement - Test	Result - Remark	Verdict
	if direct supply to these parts from the supply mains gives rise to a hazard		N/A
24.1.7	If the remote operation of the appliance is via a telecommunication network, the relevant standard for the telecommunication interface circuitry in the appliance is EN 41003		N/A
	Compliance with Clause 8 of this standard is not impaired by connecting the appliance to a device covered by EN 41003		N/A
24.Z1	For motor running capacitors (IEC 60252-1 type P2) with a metallic enclosure having an overpressure fuse the flame testing of internal plastic parts supporting current carrying connections as required in 30.2.2 and 30.2.3.1 is not necessary		N/A
25.6	Supply cords of single-phase portable appliances having a rated current not exceeding 16 A, fitted with a plug complying with the following standard sheets of IEC/TR 60083:		P
	- for Class I appliances: standard sheet C2b, C3b or C4	C4	P
	- for Class II appliances: standard sheet C5 or C6		N/A
25.7	Rubber sheathed cords (60245 IEC 53) are not suitable for appliances intended to be used outdoors or when they are liable to be exposed to significant amount of ultraviolet radiation		N/A
	Halogen-free thermoplastic compound sheathed supply cords have properties at least those of:		N/A
	<ul style="list-style-type: none"> halogen-free thermoplastic compound sheathed cords (H03Z1Z1H2-F or H03Z1Z1-F), for appliances having a mass not exceeding 3 kg 		N/A
	<ul style="list-style-type: none"> halogen-free thermoplastic compound sheathed cords (H05Z1Z1H2-F or H05Z1Z1-F), for other appliances 		N/A
	Cross-linked halogen-free compound sheathed supply cords have properties at least those of cross-linked halogen-free compound sheathed cords (H07ZZ-F)		N/A
26.11	Conductors connected by soldering are not considered to be positioned or fixed so that reliance is not placed upon the soldering alone to maintain them in position unless they are held in place near the terminals independently of the solder		N/A

IEC60335_2_9J - ATTACHMENT			
Clause	Requirement - Test	Result - Remark	Verdict
29.3.Z1	Appliance constructed so that if there is a possibility of damaging the insulation during installation, the insulation withstands the scratch and penetration test of 21.2		N/A
32	Compliance regarding electromagnetic fields is checked according to EN 62233		P
Annex I, 19.1.101	The appliance is supplied at rated voltage and operated under normal operation with each of the fault conditions specified		N/A
	The duration of the test is as specified in 19.7		N/A
ZA	ANNEX ZA (NORMATIVE) SPECIAL NATIONAL CONDITIONS		P
	Norway		N/A
19.5	The test is also applicable to appliances intended to be permanently connected to fixed wiring		N/A
	Norway		N/A
22.2	The second paragraph of this subclause, dealing with single-phase, permanently connected class I appliances having heating elements, is not applicable due to the supply system		N/A
	All CENELEC countries		P
25.6 and 25.25	Information concerning National plug and socket-outlets is available from the CENELEC website. Normative national requirements concerning plug and socket-outlets are shown in the relevant National standard		P
	Ireland and United Kingdom		P
25.8	In the table, the lines for 10 A and 16 A are replaced by:		P
	> 10 and ≤ 13 1,25		P
	> 13 and ≤ 16 1,5		N/A
ZB	ANNEX ZB (INFORMATIVE) A-DEVIATIONS		N/A
	Ireland		N/A

IEC60335_2_9J - ATTACHMENT			
Clause	Requirement - Test	Result - Remark	Verdict
25.6	These regulations apply to all plugs for domestic use at a voltage of not less than 200 V and in general allow only plugs complying with I.S. 401:1997, or equivalent, to be fitted to domestic appliances		N/A
	United Kingdom		P
25.6	These regulations apply to all plugs for domestic use at a voltage of not less than 200 V and in general allow only plugs to BS 1363 to be fitted to domestic appliances. It also allows plugs to BS 4573 and EN 50075 to be fitted to shavers and toothbrushes		P
ZC	ANNEX ZC (NORMATIVE) NORMATIVE REFERENCES TO INTERNATIONAL PUBLICATIONS WITH THEIR CORRESPONDING EUROPEAN PUBLICATIONS		N/A
	A list of referenced documents in this standard		N/A
ZD	ANNEX ZD (INFORMATIVE) IEC and CENELEC CODE DESIGNATIONS FOR FLEXIBLE CORDS		P
	A table with IEC and CENELEC code designations for flexible cords		P
ZE	ANNEX ZE (INFORMATIVE) SPECIFIC ADDITIONAL REQUIREMENTS FOR APPLIANCES AND MACHINES INTENDED FOR COMMERCIAL USE		N/A
7.1	Business name and full address of the manufacturer and, where applicable, his authorized representative		N/A
	Model or type reference		N/A
	Serial number, if any		N/A
	Production year		N/A
	Designation of the appliance		N/A
7.12	Instructions provided with the appliance so that the appliance can be used safely		N/A
	The instructions contain at least the following information:		N/A
	- the business name and full address of the manufacturer and, where applicable, his authorized representative		N/A

IEC60335_2_9J - ATTACHMENT			
Clause	Requirement - Test	Result - Remark	Verdict
	- model or type reference of the appliance as marked on the appliance itself, except for the serial number		N/A
	- the designation of the appliance together with its explanation in case it is given by a combination of letters and/or numbers		N/A
	- the general description of the appliance, when needed due to the complexity of the appliance		N/A
	- specific precautions if required during installation, operation, adjusting, user maintenance, cleaning, repairing or moving		N/A
	- when needed drawings, diagrams, descriptions and explanations necessary for the safe use and user maintenance of the appliance		N/A
	- the possible reasonably foreseeable misuse and, whenever relevant, a warning against the effects it may have on the safe use of the appliance		N/A
	The words "Original instructions" appear on the language version(s) verified by the manufacturer or by the authorized representative		N/A
	When a translation of the original instructions has been provided by a person introducing the appliance on the market; the meaning of the sentence "Translation of the original instructions" appear in the relevant instructions delivered with the appliance		N/A
	The instructions for maintenance/service to be done by specialized personnel, mandated by the manufacturer or the authorized representative may be supplied in only one Community language which the specialized personnel understand		N/A
	The instructions indicate the type and frequency of inspections and maintenance required for safe operation including the preventive maintenance measures		N/A
7.12.ZE1	If needed for specific appliances, the following information to be given:		N/A
	<ul style="list-style-type: none"> on use, transportation, assembly, dismantling when out of service, testing or foreseeable breakdowns, if these operations have consequences on stability of the appliance in order to avoid overturning, falling or uncontrolled movements of the appliance or of its component parts 		N/A

IEC60335_2_9J - ATTACHMENT			
Clause	Requirement - Test	Result - Remark	Verdict
	<ul style="list-style-type: none"> on how to maintain adequate mechanical stability when in use, during transportation, assembly, dismantling, scrapping and any other action involving the appliance 		N/A
	<ul style="list-style-type: none"> on the protective measures to be taken by the user, including, where appropriate, the personal protective equipment to be provided 		N/A
	<ul style="list-style-type: none"> on the operating method to be followed in the event of accident or breakdown; if a blockage is likely to occur the operating method to safely unblock the appliance 		N/A
	<ul style="list-style-type: none"> on the specifications on the spare parts to be used, when these affect the health and safety of the operator 		N/A
	<ul style="list-style-type: none"> on airborne noise emissions, determined and declared in accordance with the relevant Part 2, which includes: 		N/A
	<ul style="list-style-type: none"> - the A-weighted emission sound pressure level at workstations, where this exceeds 70 dB(A) 		N/A
	<ul style="list-style-type: none"> - where this level does not exceed 70 dB(A), this fact is indicated 		N/A
	<ul style="list-style-type: none"> - the peak C-weighted instantaneous sound pressure value at workstations, where this exceeds 63 Pa (130 dB in relation to 20 µPa)..... 		N/A
	<ul style="list-style-type: none"> - the A-weighted sound power level emitted by the machinery, where the A-weighted emission sound pressure level at workstations exceeds 80 dB(A) 		N/A
7.12.ZE2	The instructions includes a warning to disconnect the appliance from its power source during service and when replacing parts		N/A
	If the removal of the plug is foreseen, it is clearly indicated that the removal of the plug has to be such that an operator can check from any of the points to which he has access that the plug remains removed		N/A
	If this is not possible, due to the construction of the appliance or its installation, a disconnection with a locking system in the isolated position is provided		N/A
19.11.4.8	The appliance continues to operate, without causing any hazard to the user, from the same point in its operating cycle at which the voltage fluctuation occurred, or		N/A
	a manual operation is required to restart it		N/A

IEC60335_2_9J - ATTACHMENT			
Clause	Requirement - Test	Result - Remark	Verdict
20.1	Appliances and their components and fittings have adequate mechanical stability during transportation, assembly, dismantling and any other action involving the appliance		N/A
20.2	Dangerous moving transmission parts safeguarded either by design or guards		N/A
	When guards are used, they are fixed guards, interlocking movable guards or protective devices		N/A
	Moving parts directly involved in the function of the appliance which cannot be made completely inaccessible fitted with:		N/A
	- fixed guards or interlocking movable guards preventing access to those sections of the parts that are not used in the work, and		N/A
	- adjustable guards restricting access to those sections of the moving parts where access is necessary		N/A
	Interlocking movable guards used where frequent access is required		N/A
21.1	Appliances and their components and fittings have adequate mechanical strength and is constructed to withstand such rough handling that may be expected in normal use, during transportation, assembly, dismantling, scrapping and any other action involving the appliance		N/A
22.ZE.1	For appliances provided with a seat, the seat gives adequate stability		N/A
	The distance between the seat and the control devices capable of being adapted to the operator		N/A
22.ZE.2	For appliances provided with separate devices for the start and the stop functions, the stop function is unambiguously identifiable and does always override the start function		N/A
	For appliances provided with one device performing the start and the stop function, the stop function is unambiguously identifiable and does always override the start function		N/A
22.ZE.3	Appliances designed in such a way that incorrect mounting is avoided, if this can lead to an unsafe situation		N/A
	If this is not possible, information on the correct mounting is given directly on the part and/or the enclosure		N/A
22.ZE.4	Where the weight, size or shape prevents appliances from being moved manually, they are fitted with attachments for lifting gear, or		N/A

IEC60335_2_9J - ATTACHMENT			
Clause	Requirement - Test	Result - Remark	Verdict
	so designed that they can be fitted with such attachments, or		N/A
	be shaped in such a way that standard lifting gear can easily be used		N/A
	Appliances to be moved manually are constructed or equipped so that they can be moved easily and safely		N/A
22.ZE.5	The fixing systems of fixed guards which prevent access to dangerous moving transmission parts only removable with the use of tools		N/A
	If such guards have to be removed by the user for routine cleaning or maintenance their fixing systems remain attached to the fixed guards or to the machine after removal		N/A
	Where possible, guards are incapable of remaining in place without their fixings		N/A
	This does not apply if, after removal of the screws, or if the component is incorrectly repositioned, the appliance becomes inoperative		N/A
	Movable guards are interlocked		N/A
	The interlocking devices prevent the start of hazardous appliance functions until the guards are fixed in their position, and give a stop command whenever they are no longer closed		N/A
	Where it is possible for an operator to reach the danger zone before the risk due to hazardous appliance functions has ceased, movable guards associated with a guard locking device in addition to an interlocking device that:		N/A
	- prevents the start of hazardous appliance functions until the guard is closed and locked, and		N/A
	- keeps the guard closed and locked until the risk of injury from the hazardous appliance functions has ceased		N/A
	Interlocking movable guards remain attached to the appliance when open, and		N/A
	they are designed and constructed in such a way that they can be adjusted only by means of an intentional action		N/A
22.ZE.6	Interlocking movable guards designed in such a way that the absence or failure of one of their components prevents starting or stops the hazardous appliance functions		N/A
	The guard is opened to the extent needed to cause the interlocking to operate and is then closed, the number of operations being defined in the specific Part 2.....:		N/A

IEC60335_2_9J - ATTACHMENT			
Clause	Requirement - Test	Result - Remark	Verdict
	After this test any defect that may be expected in normal use is applied to the interlock system, including interruption of the supply, only one defect being simulated at a time		N/A
	After these tests the interlock system is fit for further use		N/A
22.ZE.7	Adjustable guards restricting access to areas of the moving parts strictly necessary for the work are:		N/A
	- adjustable manually or automatically, depending on the type of work involved, and		N/A
	- readily adjustable without the use of tools		N/A
22.ZE.8	In case of interruption, re-establishment after an interruption or fluctuation in whatever manner of the power supply, the appliance does not restart		N/A
	However, automatic restarting of the operation is allowed if the appliance may continue to operate, without causing any hazard to the user, from the same point in its operating cycle at which the voltage interruption or fluctuation occurred		N/A
22.ZE.9	Appliances fitted with means to isolate them from all energy sources		N/A
	Such isolators are clearly identified, and		N/A
	they are capable of being locked if reconnection endanger persons		N/A
	After the energy source is disconnected, it is possible to dissipate any energy remaining or stored in the circuits of the appliance without risk to persons		N/A
ZF	ANNEX ZF (INFORMATIVE) CRITERIA APPLIED FOR THE ALLOCATION OF PRODUCTS COVERED BY STANDARDS IN THE EN 60335 SERIES UNDER LVD OR MD		P
	List of standards under CENELEC/TC61 with the allocation under the LVD (Low Voltage Directive) or the MD (Machinery Directive).....:		P
ZG	ANNEX ZG (NORMATIVE) UV APPLIANCES		N/A
	The following modifications to this standard apply to appliances having UV emitters		N/A
	This annex is not applicable to appliances covered by the scopes of IEC 60335-2-27, IEC 60335-2-59 or IEC 60335-2-109		N/A

IEC60335_2_9J - ATTACHMENT			
Clause	Requirement - Test	Result - Remark	Verdict
7.12.ZG	The instructions for appliances incorporating UVC emitters include the substance of the following: WARNING — This appliance contains a UV emitter. Do not stare at the light source		N/A
32	For appliances incorporating UV emitters the manufacturer delivers a declaration providing evidence that the plastic material exposed to the radiation is UV resistant		N/A
ZZ	ANNEX ZZ (INFORMATIVE) COVERAGE OF ESSENTIAL REQUIREMENTS OF EC DIRECTIVES		P
	Description of the relation between this European standard and the LVD (Low Voltage Directive, 2006/95/EC) and the MD (Machinery Directive, 2006/42/EC)		P

Annex EN 62233:2008			
Clause	Requirement + Test	Result - Remark	Verdict
EMF- ELECTROMAGNETICS FIELDS			
	The tested product also complies with the requirements of EN 62233:2008		P
	Limit100%	Measured max. : 12,03%	P

IEC60335_2_9J - ATTACHMENT			
Clause	Requirement - Test	Result - Remark	Verdict

11.Z102	TABLE: Temperature rise limits for surfaces(ZM-227)		P
	Ambient (°C):		24,5
	Test voltage (V):		233,6
		dT (K)	Max. dT (K)
Plastic		46,0	65

11.Z102	TABLE: Temperature rise limits for surfaces(ZM-227B)		P
	Ambient (°C):		24,7
	Test voltage (V):		235,5
		dT (K)	Max. dT (K)
Plastic		43,6	65
Meter cover		39,9	45

11.Z102	TABLE: Temperature rise limits for surfaces(ZM-258B)		P
	Ambient (°C):		23,9
	Test voltage (V):		237,9
		dT (K)	Max. dT (K)
Plastic		44,9	65
Meter cover		36,6	45

11.Z102	TABLE: Temperature rise limits for surfaces(ZM-707)		P
	Ambient (°C):		24,5
	Test voltage (V):		233,2
		dT (K)	Max. dT (K)
Plastic		42,6	65
Meter spring		23,0	45

IEC60335_2_9J - ATTACHMENT			
Clause	Requirement - Test	Result - Remark	Verdict

11.Z102	TABLE: Temperature rise limits for surfaces(ZM-707B)		P
	Ambient (°C):		24,6
	Test voltage (V):		232,7
		dT (K)	Max. dT (K)
Plastic		30,7	65
Meter cover		42,3	45

11.Z102	TABLE: Temperature rise limits for surfaces(ZM-202B)		P
	Ambient (°C):		22,5
	Test voltage (V):		243,6
		dT (K)	Max. dT (K)
Plastic		53,2	65
Metal		41,1	45

11.Z102	TABLE: Temperature rise limits for surfaces(ZM-228C)		P
	Ambient (°C):		22,5
	Test voltage (V):		243,8
		dT (K)	Max. dT (K)
Plastic		42,6	65
Meter cover		34,3	45

11.Z102	TABLE: Temperature rise limits for surfaces(ZM-268B)		P
	Ambient (°C):		21,8
	Test voltage (V):		243,6
		dT (K)	Max. dT (K)
Plastic		49,3	65
Metal		30.1	45
Remark: Sandwich maker function			

IEC60335_2_9J - ATTACHMENT			
Clause	Requirement - Test	Result - Remark	Verdict

11.Z102	TABLE: Temperature rise limits for surfaces(ZM-268B)		P
	Ambient (°C):		21,8
	Test voltage (V):		243,6
		dT (K)	Max. dT (K)
Plastic		43,6	65
Metal		30,8	45
Remark: Griddle function			

11.Z102	TABLE: Temperature rise limits for surfaces(ZM-267)		P
	Ambient (°C):		23,2
	Test voltage (V):		251,0
		dT (K)	Max. dT (K)
Plastic		55,8	65
Metal cover		41,0	45
Metal spring		34,0	45
Remark:			

11.Z102	TABLE: Temperature rise limits for surfaces(ZM-259B)		P
	Ambient (°C):		24,2
	Test voltage (V):		240,2
		dT (K)	Max. dT (K)
Plastic		54,7	65
Metal		35,6	45

11.Z102	TABLE: Temperature rise limits for surfaces(ZM-707C)		P
	Ambient (°C):		24,6
	Test voltage (V):		245,7
		dT (K)	Max. dT (K)
Plastic		60,1	65
Metal		34,8	45

IEC60335_2_9J - ATTACHMENT			
Clause	Requirement - Test	Result - Remark	Verdict
11.Z102	TABLE: Temperature rise limits for surfaces(ZM-200B)		P
	Ambient (°C):		24,0
	Test voltage (V):		245,6
		dT (K)	Max. dT (K)
Plastic		54,5	65
Metal		35,4	45

11.Z102	TABLE: Temperature rise limits for surfaces(ZM-269B)		P
	Ambient (°C):		24,2
	Test voltage (V):		240,2
		dT (K)	Max. dT (K)
Top surface(plastic) accessible by probe A		28,7	65
Top surface(metal) accessible by probe A		32,8	45
Front surface(plastic) accessible by probe A		48,7	65
Left side surface(plastic) accessible by probe A		58,0	65
Right side surface(plastic) accessible by probe A		62,0	65
Rear surface(plastic) accessible by probe A		47,8	65
Rear surface(metal) accessible by probe A		32,7	45
Bottom surface(plastic) accessible by probe 41		28,2	65

11.Z102	TABLE: Temperature rise limits for surfaces(ZM-267B)		P
	Ambient (°C):		24,2
	Test voltage (V):		240,2
		dT (K)	Max. dT (K)
Top surface(plastic) accessible by probe A		41,3	65
Front surface(plastic) accessible by probe A		43,6	65
Left side surface(plastic) accessible by probe A		60,6	65
Right side surface(plastic) accessible by probe A		56,0	65
Rear surface(plastic) accessible by probe A		25,7	65
Rear surface(metal) accessible by probe A		31,9	45
Bottom surface(plastic) accessible by probe 41		34,6	65

IEC60335_2_9J - ATTACHMENT			
Clause	Requirement - Test	Result - Remark	Verdict

11.Z102	TABLE: Temperature rise limits for surfaces(ZM-259)		P
	Ambient (°C):		24,2
	Test voltage (V):		240,2
		dT (K)	Max. dT (K)
	Top surface(plastic) accessible by probe A	43,2	65
	Front surface(plastic) accessible by probe A	32,5	65
	Left side surface(plastic) accessible by probe A	44,9	65
	Right side surface(plastic) accessible by probe A	52,7	65
	Rear surface(plastic) accessible by probe A	36,1	65
	Bottom surface(plastic) accessible by probe 41	31,4	65

11.Z102	TABLE: Temperature rise limits for surfaces(ZM-207)		P
	Ambient (°C):		24,2
	Test voltage (V):		240,2
		dT (K)	Max. dT (K)
	Top surface(plastic) accessible by probe A	35,4	65
	Front surface(plastic) accessible by probe A	34,6	65
	Left side surface(plastic) accessible by probe A	46,5	65
	Right side surface(plastic) accessible by probe A	40,8	65
	Rear surface(plastic) accessible by probe A	36,0	65
	Bottom surface(plastic) accessible by probe 41	45,5	65

11.Z102	TABLE: Temperature rise limits for surfaces(ZM-208)		P
	Ambient (°C):		24,2
	Test voltage (V):		240,2
		dT (K)	Max. dT (K)
	Top surface(plastic) accessible by probe A	35,8	65
	Front surface(plastic) accessible by probe A	24,6	65
	Left side surface(plastic) accessible by probe A	36,8	65
	Right side surface(plastic) accessible by probe A	33,8	65
	Rear surface(plastic) accessible by probe A	25,3	65
	Bottom surface(plastic) accessible by probe 41	26,5	65

IEC60335_2_9J - ATTACHMENT			
Clause	Requirement - Test	Result - Remark	Verdict

11.Z102	TABLE: Temperature rise limits for surfaces(ZM-206B)		P
	Ambient (°C):		24,2
	Test voltage (V):		240,2
		dT (K)	Max. dT (K)
Top surface(plastic) accessible by probe A		30,3	65
Top surface(metal) accessible by probe A		29,0	45
Front surface(plastic) accessible by probe A		20,0	65
Left side surface(plastic) accessible by probe A		30,2	65
Right side surface(plastic) accessible by probe A		33,3	65
Rear surface(plastic) accessible by probe A		24,7	65
Bottom surface(plastic) accessible by probe 41		18,8	65

11.Z102	TABLE: Temperature rise limits for surfaces(ZM-206)		P
	Ambient (°C):		24,2
	Test voltage (V):		240,2
		dT (K)	Max. dT (K)
Top surface(plastic) accessible by probe A		49,6	65
Front surface(plastic) accessible by probe A		36,0	65
Left side surface(plastic) accessible by probe A		44,7	65
Right side surface(plastic) accessible by probe A		43,9	65
Rear surface(plastic) accessible by probe A		37,9	65
Bottom surface(plastic) accessible by probe 41		30,5	65

IEC60335_2_9J - ATTACHMENT			
Clause	Requirement - Test	Result - Remark	Verdict

EN 60335-1:2012/A11			
7.14	In NOTE Z1, replace "IEC 82079-1" by "EN 82079-1".		N/A
Annex ZF	In Table ZF.1 – List of standards under CLC/TC 61, replace line of EN 60335-2-38		N/A

<End of Test Report>

Attachment 1 of 50087662 001

PAH Material List (to be filled by the manufactory)

Material list for PAH risk assessment, only materials accessible without tools shall be listed

PAHSM aterial #	Location/Function of the material	Name/Description of the material	Evidence attached. Institute, report no., date	Category	Smell	Rigidity	Colour
1	Plastic enclosure	PF, white/black/red/pink/ yellow/blue/purple	---	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input type="checkbox"/> Flexible <input checked="" type="checkbox"/> Rigid	<input checked="" type="checkbox"/> Black or dark-colored <input checked="" type="checkbox"/> White or light-colored
2	Handle cover ZM-201, ZM-227, ZM-227B, ZM-258B, ZM-202B, ZM- 228, ZM-228B, ZM-228C, ZM-228D, ZM-268B, ZM-267, ZM-259B, ZM-200, ZM-200B, ZM-206B, ZM- 206, ZM-207B, ZM-207, ZM-208, ZM-208B, ZM- 267B, ZM-259, ZM-269B	PF, white/black	---	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input type="checkbox"/> Flexible <input checked="" type="checkbox"/> Rigid	<input checked="" type="checkbox"/> Black or dark-colored <input checked="" type="checkbox"/> White or light-colored
3	Handle clip ZM-201, ZM-227, ZM-227B, ZM-258B, ZM-202B, ZM- 228, ZM-228B, ZM-228C, ZM-228D, ZM-268B, ZM- 267, ZM-259B, ZM-200, ZM-200B, ZM-206B, ZM- 206, ZM-207B, ZM-207, ZM-208, ZM-208B, ZM- 267B, ZM-259, ZM-269B	ABS, white/black	---	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input type="checkbox"/> Flexible <input checked="" type="checkbox"/> Rigid	<input checked="" type="checkbox"/> Black or dark-colored <input checked="" type="checkbox"/> White or light-colored
4	Axle, Right hinge, left hinge ZM-707, ZM-707B, ZM-707C	PA, white/black	---	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input type="checkbox"/> Flexible <input checked="" type="checkbox"/> Rigid	<input checked="" type="checkbox"/> Black or dark-colored <input checked="" type="checkbox"/> White or light-colored
5	Metal handle ZM-707, ZM-707B, ZM-707C	Metal, white	---	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input type="checkbox"/> Flexible <input checked="" type="checkbox"/> Rigid	<input type="checkbox"/> Black or dark-colored <input checked="" type="checkbox"/> White or light-colored
6	Handle arm ZM-707, ZM- 707B , ZM-707C	PA, black	---	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input type="checkbox"/> Flexible <input checked="" type="checkbox"/> Rigid	<input checked="" type="checkbox"/> Black or dark-colored <input type="checkbox"/> White or light-colored

Attachment 1 of 50087662 001

PAH Material List (to be filled by the manufactory)

Material list for PAH risk assessment, only materials accessible without tools shall be listed

7	Terminal box cover	PP, black/white	---	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input type="checkbox"/> Flexible <input checked="" type="checkbox"/> Rigid	<input checked="" type="checkbox"/> Black or dark-colored <input checked="" type="checkbox"/> White or light-colored
8	Indicator light cover	PC, red/green	---	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input type="checkbox"/> Flexible <input checked="" type="checkbox"/> Rigid	<input checked="" type="checkbox"/> Black or dark-colored <input type="checkbox"/> White or light-colored
9	Metal cover ZM-227B, ZM-258B, ZM-202B, ZM-228C, ZM-228D, ZM-268B, ZM-267, ZM-259B, ZM-200B, ZM-707C, ZM-206B, ZM-207B, ZM-208B, ZM-269B	Metal, white	---	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input type="checkbox"/> Flexible <input checked="" type="checkbox"/> Rigid	<input type="checkbox"/> Black or dark-colored <input checked="" type="checkbox"/> White or light-colored
10	Rubber feet	Rubber, black/white	---	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input checked="" type="checkbox"/> Flexible <input type="checkbox"/> Rigid	<input checked="" type="checkbox"/> Black or dark-colored <input checked="" type="checkbox"/> White or light-colored
11	Clip cover ZM-269B	PVC	---	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input checked="" type="checkbox"/> Flexible <input type="checkbox"/> Rigid	<input type="checkbox"/> Black or dark-colored <input checked="" type="checkbox"/> White or light-colored
12	Power cord	Rubber/PVC, white/black	---	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input checked="" type="checkbox"/> Flexible <input type="checkbox"/> Rigid	<input checked="" type="checkbox"/> Black or dark-colored <input checked="" type="checkbox"/> White or light-colored
13	Power plug	Plastic, white/black	---	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input type="checkbox"/> Flexible <input checked="" type="checkbox"/> Rigid	<input checked="" type="checkbox"/> Black or dark-colored <input checked="" type="checkbox"/> White or light-colored

Attachment 1 of 50087662 001

PAH Material List (to be filled by the manufactory)

Material list for PAH risk assessment, only materials accessible without tools shall be listed

I herewith declare that the above listed materials are used in our product submitted to GS-certification and conform with the attached PAH test reports.

Product Identification: Sandwich maker

Type: ZM-200, ZM-200B, ZM-201, ZM-202B, ZM-206, ZM-206B, ZM-207, ZM-207B, ZM-208, ZM-208B, ZM-227, ZM-227B, ZM-228, ZM-228B, ZM-228C, ZM-228D, ZM-267, ZM-267B, ZM-268B, ZM-258B, ZM-259, ZM-259B, ZM-269B, ZM-707, ZM-707B, ZM-707C

Place _____, Date _____

(Applicant's seal and legally binding signature)



Attachment 2: Information from GS test center

Material list for PAH risk assessment; Only materials accessible without tools

Product designation: Sandwich maker

Certificate No.: S50384128 0001

Test report No.: 50087662 001

Material / Component #	Location / Function of the material	Name / Description of the material	PAH relevant 1)	Evidence attached. Institute, report no., date	Category	Smell	Rigidity	Colour	Correction of data by test center? 1)	Chem. test needed?	Test result (within the given limits)	Attachement
1	Plastic enclosure	PF, white/black/red/pink/yellow/blue/purple	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	----	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input type="checkbox"/> Flexible <input checked="" type="checkbox"/> Rigid	<input checked="" type="checkbox"/> Black or dark-colored <input checked="" type="checkbox"/> White or light-colored	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input type="checkbox"/> passed <input type="checkbox"/> failed	--
2	Handle cover ZM-201, ZM-227, ZM-227B, ZM-258B, ZM-202B, ZM-228, ZM-228B, ZM-228C, ZM-228D, ZM-268B, ZM-267, ZM-259B, ZM-200, ZM-200B, ZM-206B, ZM-206, ZM-207B, ZM-207, ZM-208, ZM-208B, ZM-267B, ZM-259, ZM-269B	PF, white/black	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	----	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input type="checkbox"/> Flexible <input checked="" type="checkbox"/> Rigid	<input checked="" type="checkbox"/> Black or dark-colored <input checked="" type="checkbox"/> White or light-colored	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input type="checkbox"/> passed <input type="checkbox"/> failed	--
3	Handle clip ZM-201, ZM-227, ZM-227B, ZM-258B, ZM-202B, ZM-228, ZM-228B, ZM-228C, ZM-228D, ZM-268B, ZM-267, ZM-259B, ZM-200,	ABS, white/black	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	----	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input type="checkbox"/> Flexible <input checked="" type="checkbox"/> Rigid	<input checked="" type="checkbox"/> Black or dark-colored <input checked="" type="checkbox"/> White or light-colored	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input type="checkbox"/> passed <input type="checkbox"/> failed	--

Material / Component #	Location / Function of the material	Name / Description of the material	PAH relevant 1)	Evidence attached. Institute, report no., date	Category	Smell	Rigidity	Colour	Correction of data by test center? 1)	Chem. test needed?	Test result (within the given limits)	Attachement
	ZM-200B, ZM-206B, ZM-206, ZM-207B, ZM-207, ZM-208, ZM-208B, ZM-267B, ZM-259, ZM-269B											
4	Axle, Right hinge, left hinge ZM-707, ZM-707B, ZM-707C	PA, white/black	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	----	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input type="checkbox"/> Flexible <input checked="" type="checkbox"/> Rigid	<input checked="" type="checkbox"/> Black or dark-colored <input checked="" type="checkbox"/> White or light-colored	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input type="checkbox"/> passed <input type="checkbox"/> failed	--
5	Metal handle ZM-707, ZM-707B, ZM-707C	Metal, white	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	----	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input type="checkbox"/> Flexible <input checked="" type="checkbox"/> Rigid	<input type="checkbox"/> Black or dark-colored <input checked="" type="checkbox"/> White or light-colored	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input type="checkbox"/> passed <input type="checkbox"/> failed	--
6	Handle arm ZM-707, ZM-707B, ZM-707C	PA, black	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	----	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input type="checkbox"/> Flexible <input checked="" type="checkbox"/> Rigid	<input checked="" type="checkbox"/> Black or dark-colored <input type="checkbox"/> White or light-colored	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input type="checkbox"/> passed <input type="checkbox"/> failed	--
7	Terminal box cover	PP, black/white	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	----	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input checked="" type="checkbox"/> Flexible <input type="checkbox"/> Rigid	<input checked="" type="checkbox"/> Black or dark-colored <input checked="" type="checkbox"/> White or light-colored	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input type="checkbox"/> passed <input type="checkbox"/> failed	--
8	Indicator light cover	PC, red/green	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	----	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input type="checkbox"/> Flexible <input checked="" type="checkbox"/> Rigid	<input checked="" type="checkbox"/> Black or dark-colored <input type="checkbox"/> White or light-colored	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input type="checkbox"/> passed <input type="checkbox"/> failed	--
9	Metal cover ZM-227B, ZM-258B, ZM-202B, ZM-228C, ZM-228D, ZM-268B, ZM-267, ZM-259B, ZM-200B, ZM-707C, ZM-206B, ZM-207B, ZM-	Metal, white	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	----	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input type="checkbox"/> Flexible <input checked="" type="checkbox"/> Rigid	<input type="checkbox"/> Black or dark-colored <input checked="" type="checkbox"/> White or light-colored	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input type="checkbox"/> passed <input type="checkbox"/> failed	--

Material / Component #	Location / Function of the material	Name / Description of the material	PAH relevant 1)	Evidence attached. Institute, report no., date	Category	Smell	Rigidity	Colour	Correction of data by test center? 1)	Chem. test needed?	Test result (within the given limits)	Attachement
	208B, ZM-269B											
10	Rubber feet	Rubber, black/white	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	----	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input checked="" type="checkbox"/> Flexible <input type="checkbox"/> Rigid	<input checked="" type="checkbox"/> Black or dark-colored <input checked="" type="checkbox"/> White or light-colored	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input type="checkbox"/> passed <input type="checkbox"/> failed	--
11	Clip cover ZM-269B	PVC	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	----	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input checked="" type="checkbox"/> Flexible <input type="checkbox"/> Rigid	<input type="checkbox"/> Black or dark-colored <input checked="" type="checkbox"/> White or light-colored	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input type="checkbox"/> passed <input type="checkbox"/> failed	--
12	Power cord	Rubber/PVC, black/white	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	----	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input checked="" type="checkbox"/> Flexible <input type="checkbox"/> Rigid	<input checked="" type="checkbox"/> Black or dark-colored <input checked="" type="checkbox"/> White or light-colored	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input type="checkbox"/> passed <input type="checkbox"/> failed	--
13	Power plug	Plastic, black/white	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	----	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	<input type="checkbox"/> Soft <input type="checkbox"/> Flexible <input checked="" type="checkbox"/> Rigid	<input checked="" type="checkbox"/> Black or dark-colored <input checked="" type="checkbox"/> White or light-colored	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes	<input type="checkbox"/> passed <input type="checkbox"/> failed	--

1) Enter all PAK considered materials.

2) Applicant data from Annex 1

Assessed by *name*

Place Ningbo China, Date 2017-08-04

(Test engineers signature)



Risk assessment for the above mentioned product indicates PAH relevance :

Yes ¹⁾

No

Short statement

Rev. 4 on 2008-07-10

Attachment 3 of 50087662 001



LFGB Material List : ZM-200, ZM-200B, ZM-201, ZM-202B, ZM-206, ZM-206B, ZM-207, ZM-207B, ZM-208, ZM-208B, ZM-227, ZM-227B, ZM-228, ZM-228B, ZM-228C, ZM-228D, ZM-267, ZM-267B, ZM-268B, ZM-258B, ZM-259, ZM-259B, ZM-269B, ZM-707, ZM-707B, ZM-707C

Material #	Location / Function of the material	Name / Description of the material	Evidence attached	Colour
1	Coating of heating plate	Coating	Self-declaration from NINGBO BAKELON ELECTRICAL APPLIANCE CO., LTD.	<input checked="" type="checkbox"/> Black or dark-colored <input type="checkbox"/> White or light-colored




Measuring and Testing Equipment List



Used MTE

Report Number: 50087662 001

Description	MTE Type/model	Internal ID	Next Calibration (DD/MM/YY)
<input type="checkbox"/> Digital Power Meter	WT200 12B921862	1.001	14/10/2017
<input type="checkbox"/> Digital Power Meter	WT200 12B921863	1.002	14/10/2017
<input type="checkbox"/> Digital Power Meter	3332 040616028	1.003	14/10/2017
<input type="checkbox"/> Digital Power Meter	3332 031120387	1.004	14/10/2017
<input type="checkbox"/> Digital Power Meter	WT210 27E442930D	1.005	14/10/2017
<input type="checkbox"/> Digital Power Meter	VIP96	1.005A	14/10/2017
<input type="checkbox"/> Digital Power Meter	WT210 91G623881	1.005B	10/01/2018
<input type="checkbox"/> Digital Power Meter	WT210	1.005C	10/01/2018
<input type="checkbox"/> Digital Power Meter	WT210	1.005E	14/10/2017
<input type="checkbox"/> Digital Power Meter	WT310	1.005F	26/07/2017
<input type="checkbox"/> Withstanding Voltage Tester	TOS5051	1.006	14/10/2017
<input type="checkbox"/> Withstanding Voltage Tester	TOS5101	1.006A	14/10/2017
<input type="checkbox"/> Withstanding Voltage Tester	TOS5051A	1.006B	08/03/2018
<input type="checkbox"/> Earth continuity Test	TOS6200	1.007	14/10/2017
<input type="checkbox"/> Earth continuity Test	TOS6210	1.007A	05/01/2018
<input type="checkbox"/> Digital mΩ Meter	HIOKI 3540	1.009	14/10/2017
<input type="checkbox"/> Digital Multimeter	KEITHLEY 2000	1.010	14/10/2017
<input type="checkbox"/> Dual Display Multimeter	FLUKE 45	1.011	14/10/2017
<input type="checkbox"/> True RMS Multimeter	FLUKE 187	1.012	14/10/2017
<input type="checkbox"/> True RMS Multimeter	FLUKE17B+	1.012A	08/03/2018
<input type="checkbox"/> True RMS Multimeter	FLUKE17B+	1.012B	08/03/2018

Signature: Date: 2017.07.28


Measuring and Testing Equipment List



Used MTE

Report Number: 50087662 001

Description	MTE Type/model	Internal ID	Next Calibration (DD/MM/YY)
<input type="checkbox"/> Leakage current tester	HIOKI 3156	1.013	05/01/2018
<input type="checkbox"/> Glow Wire Test Apparatus	F3-3020	1.014A	10/05/2018
<input type="checkbox"/> Tracking tester	DML600	1.015A	08/03/2018
<input type="checkbox"/> Needle Flame Test Apparatus	NF-II	1.016	10/01/2018
<input type="checkbox"/> Measuring Cup	2000ml	1.019A	23/02/2019
<input type="checkbox"/> Measuring Cup	1000ml	1.019B	23/02/2019
<input type="checkbox"/> Measuring Cup	50ml	1.019D	23/02/2019
<input type="checkbox"/> Measuring Cup	25ml	1.019E	23/02/2019
<input type="checkbox"/> Measuring Cup	5ml	1.019G	23/02/2019
<input type="checkbox"/> D.C power supply	PAT160-25T	1.021B	14/10/2017
<input type="checkbox"/> Hybrid Recorder	DX230-3-2 S5E608509	1.026	10/05/2017
<input type="checkbox"/> Hybrid Recorder	GP20-1C1H	1.026A	20/03/2018
<input type="checkbox"/> Hybrid Recorder	DX2303-1-4-3 S5F408198	1.028	05/01/2018
<input type="checkbox"/> Hybrid Recorder	DX230-3-2 S5G508756	1.030A	18/10/2017
<input type="checkbox"/> Hybrid Recorder	DX230-3-3 S5J504440	1.030B	05/01/2018
<input type="checkbox"/> Date Acquisition/Switch Unit	34970A	1.031	18/10/2017
<input type="checkbox"/> Date Acquisition/Switch Unit	MX-100	1.031A	05/01/2018
<input type="checkbox"/> Date Acquisition/Switch Unit	34970A	1.031B	28/09/2017
<input type="checkbox"/> Oscilloscope	TDS3012B	1.032	23/05/2017
<input type="checkbox"/> Oscilloscope	C010340	1.032A	19/02/2018
<input type="checkbox"/> Ball pressure tester	QK1	1.035A	01/02/2019

Signature: Date: 2017.07.28


Measuring and Testing Equipment List



Used MTE

Report Number: 50087662 001

Description	MTE Type/model	Internal ID	Next Calibration (DD/MM/YY)
<input type="checkbox"/> Ball pressure tester	QK1	1.035B	01/02/2019
<input type="checkbox"/> Impact hammer	F 22.50 5021350	1.037	26/07/2017
<input type="checkbox"/> Impact hammer(1J)	HY-SIH-10 2016122006	1.037A	23/02/2018
<input type="checkbox"/> Test Finger With Dyanmometer	P 10.38 5021354	1.038	20/02/2018
<input type="checkbox"/> Torque spanner	IDB10N	1.039A	20/07/2017
<input type="checkbox"/> Torque screw driver	RTD260CN 423281R	1.040	25/07/2017
<input type="checkbox"/> Torque screw driver	RTD15CN 429474B	1.041A	25/07/2017
<input type="checkbox"/> Torque screw driver	RTD60CN 419492G	1.041B	27/09/2017
<input type="checkbox"/> Torque spanner	DB1.5N4	1.042	25/07/2017
<input checked="" type="checkbox"/> Test Probe B	P10.14 5021353	1.044	25/02/2019
<input type="checkbox"/> Jointed Test Finger(ϕ 12×80)	P10.01 5021352	1.045	25/02/2019
<input type="checkbox"/> Test Fingernail	EN60335-1(Fig7)	1.046A	15/04/2019
<input type="checkbox"/> Test Finger	125*100mm	1.047	25/02/2019
<input checked="" type="checkbox"/> Small finger Probe18	IEC61032 (Fig12)	1.047A	25/02/2019
<input type="checkbox"/> Tubular measuring force apparatus	LTZ-10	1.048A	18/10/2017
<input type="checkbox"/> Flexible cord bending tester	WZJ1405001	1.049A	10/01/2018
<input type="checkbox"/> Flexible cord bending tester	WZJ1405001A	1.049B	10/01/2018
<input type="checkbox"/> AN-41 Tumbling barrel	AN-41	1.050	10/01/2018
<input type="checkbox"/> IPX3 , X4 ; X5 , X6 ;	KXT1323	1.051X	22/03/2018
<input type="checkbox"/> IPx8 Tester	KXT1381A	1.051A	09/03/2018
<input type="checkbox"/> Pressure gauge	6MPa	1.051S	20/07/2017

Signature: Date: 2017.07.28


Measuring and Testing Equipment List



Used MTE

Report Number: 50087662 001

Description	MTE Type/model	Internal ID	Next Calibration (DD/MM/YY)
<input type="checkbox"/> Electronic scale	T-1000 1000g	1.052B	10/01/2018
<input type="checkbox"/> Electronic scale	AR124CN(capacity: 120g d=0.001g)	1.052C	10/01/2018
<input type="checkbox"/> Electronic scale	XPE64001L B626681786	1.052D	08/09/2017
<input type="checkbox"/> Electronic scale	BSA224S 34290188	1.052E	10/01/2018
<input type="checkbox"/> Exposure level tester ELT-400	ELT-400	1.053	20/12/2017
<input type="checkbox"/> High voltage probe	P-6015A	1.055	23/05/2017
<input type="checkbox"/> High voltage probe	P-5200	1.055A	03/08/2017
<input type="checkbox"/> High voltage probe	P-5210	1.055C	19/07/2017
<input type="checkbox"/> Stopwatch	HW30	1.056C	13/03/2018
<input type="checkbox"/> Stopwatch	HW30	1.056D	08/08/2017
<input type="checkbox"/> Stopwatch	PS-2013	1.056E	26/09/2017
<input type="checkbox"/> Test probe12	IEC61032(Fig8)	1.057A	25/02/2019
<input type="checkbox"/> Test probe13	IEC61032(Fig9)	1.057B	29/05/2017
<input checked="" type="checkbox"/> Digital Display Caliper	0~150mm s141101102	1.059A	20/02/2018
<input type="checkbox"/> Digital Display Caliper	0~150mm s141101594	1.059B	20/02/2018
<input type="checkbox"/> Digital Display Caliper	0~150mm 1202B50452	1.063A	20/02/2018
<input type="checkbox"/> Digital Display Caliper	0~150mm 04040779	1.063C	27/09/2017
<input type="checkbox"/> Digital Display Caliper	0~150mm 1204B62380	1.063D	27/09/2017
<input type="checkbox"/> Digital Display Caliper	91511 S160900770	1.063E	18/10/2017
<input type="checkbox"/> Digital Display Caliper	91511 S160900300	1.063F	18/10/2017
<input type="checkbox"/> Digital Display Caliper	CD-6"ASX A15139644	1.063G	23/11/2017

Signature: Date: 2017.07.28


Measuring and Testing Equipment List



Used MTE

Report Number: 50087662 001

Description	MTE Type/model	Internal ID	Next Calibration (DD/MM/YY)
<input type="checkbox"/> Digital Display Caliper	91511 S160900767	1.063H	18/10/2017
<input type="checkbox"/> Digital Display Caliper	91511 S160900002	1.063I	18/10/2017
<input type="checkbox"/> Digital Display Caliper	91511 S160900007	1.063J	18/10/2017
<input type="checkbox"/> Digital Display Caliper	91511 s131000169	1.063M	20/02/2018
<input type="checkbox"/> Digital Display Caliper	91511 s1301001074	1.063N	20/02/2018
<input type="checkbox"/> Digital Display Caliper	91511 s1301001081	1.063O	20/02/2018
<input type="checkbox"/> Digital Display Caliper	91511 s130602656	1.063P	20/02/2018
<input type="checkbox"/> Small finger Probe	Probe 19 of IEC61032	1.138	28/05/2017
<input type="checkbox"/> Impulse voltage generator	JC-12	1.145	08/03/2018
<input type="checkbox"/> IP4X	∅1mm/1N	1.154	25/02/2019
<input type="checkbox"/> IP3X	∅2.5mm/3N	1.155	25/02/2019
<input type="checkbox"/> Test probe 41	AG-03	1.156	25/02/2019
<input type="checkbox"/> Impact hammer	TG1058	1.158	17/03/2020
<input type="checkbox"/> Intelligent pure sine-wave power supply	TPS500B	1.159D	11/10/2017
<input type="checkbox"/> Cordless On/Off tester	WHT	1.160	10/01/2018
<input type="checkbox"/> Iron drop tester	DYD-A	1.161	10/01/2018
<input type="checkbox"/> Oven	STH-120	1.162	28/09/2017
<input type="checkbox"/> Oven without air circulation	LG-213	1.162A	10/01/2018
<input type="checkbox"/> Scratch tester	DMS158	1.164	10/01/2018
<input type="checkbox"/> IPX1X2	MDS-E02	1.168	27/10/2017
<input type="checkbox"/> IP5X6X	XH351	1.169	02/06/2017

Signature: Date: 2017.07.28

Measuring and Testing Equipment List



Used MTE

Report Number: 50087662 001

Description	MTE Type/model	Internal ID	Next Calibration (DD/MM/YY)
<input type="checkbox"/> Electric balance	TCS-C-300KG	1.170	10/01/2018
<input type="checkbox"/> Pressure gauge	0-1.6Mpa	1.171D	22/02/2018
<input type="checkbox"/> Pressure gauge	0-1.6Mpa	1.171E	22/02/2018
<input type="checkbox"/> Pressure gauge	0-0.6Mpa	1.171F	22/02/2018
<input type="checkbox"/> Flow meter	250L/h - 2500L/h	1.173A	21/06/2017
<input type="checkbox"/> Flow meter	0.5L/min - 4L/min	1.173B	21/06/2017
<input type="checkbox"/> Pull-push machine	HY930-TS	1.196	05/01/2018
<input type="checkbox"/> Thickness meter for coating	MIni600BFN	1.199	16/10/2017
<input type="checkbox"/> Pull-push machine(Trampoline)	HY-949T	1.200A	24/11/2017
<input type="checkbox"/> Temp. & Humidity recorder	175H1	1.215A	20/07/2017
<input type="checkbox"/> Temp. & Humidity recorder	175H1	1.215B	20/07/2017
<input type="checkbox"/> Temp. & Humidity recorder	175H1	1.215C	20/07/2017
<input type="checkbox"/> Temp. & Humidity recorder	175H1	1.215D	20/07/2017
<input type="checkbox"/> Temp. & Humidity recorder	175H1	1.215E	20/07/2017
<input type="checkbox"/> Temp. & Humidity recorder	175H1	1.215F	20/07/2017
<input type="checkbox"/> Temp. & Humidity recorder	175H1	1.215G	20/07/2017
<input type="checkbox"/> Temp. & Humidity recorder	175H1	1.215H	20/07/2017
<input type="checkbox"/> Temp. & Humidity recorder	175H1	1.215I	20/07/2017
<input type="checkbox"/> Temp. & Humidity recorder	175H1	1.215J	20/07/2017
<input type="checkbox"/> Temp. & Humidity recorder	175H1	1.215K	29/07/2017
<input type="checkbox"/> Temp. & Humidity recorder	175H1	1.215L	29/07/2017

Signature: Date: 2017.07.28


Measuring and Testing Equipment List



Used MTE

Report Number: 50087662 001

Description	MTE Type/model	Internal ID	Next Calibration (DD/MM/YY)
<input type="checkbox"/> Temp. & Humidity recorder	175H1	1.215M	29/07/2017
<input type="checkbox"/> Temp. & Humidity recorder	175H1	1.217	23/05/2017
<input type="checkbox"/> Temp. & Humidity recorder	175H1	1.218	23/05/2017
<input type="checkbox"/> True RMS Multimeter	Fluke287	1.219	05/01/2018
<input type="checkbox"/> Resistance meter	HIOKI 3544	1.237	08/03/2018
<input type="checkbox"/> Swivel connection test device	DMS-NZ	1.255	26/07/2017
<input type="checkbox"/> Heating oven	LGHX-226	1.256	10/01/2018
<input type="checkbox"/> Power cord pulling and torsion tester	DMS702	1.317	26/07/2017
<input type="checkbox"/> Endurance test apparatus for switch	KGS-6B	1.319	08/03/2018
<input type="checkbox"/> High temperature endurance test for switch	HSSG	1.319A	26/07/2017
<input type="checkbox"/> LCR tester	HF2817G	1.321	17/02/2018
<input type="checkbox"/> Switch electric load	YH-8817M	1.322	26/07/2017
<input type="checkbox"/> Switch electric load	YH-8817M	1.323	26/07/2017
<input type="checkbox"/> Protection against spraying/splashing water device	Fig 5 of 60529	1.325	18/04/2018
<input type="checkbox"/> Switch electric load	YH-8817M	1.335	24/11/2017
<input type="checkbox"/> Flammability tester	YH-8920U	1.336	14/10/2017
<input type="checkbox"/> Oven	PC110	1.356	10/01/2018
<input type="checkbox"/> Climate Chamber	SETH-Z-042L	1.357	05/08/2017
<input type="checkbox"/> Climate Chamber	SETH-Z-042L	1.357A	08/03/2018
<input type="checkbox"/> Walk-in Climate Chamber	SETH-Z-130L	1.357B	26/07/2017
<input type="checkbox"/> Data acquisition/switch unit	34972A	1.381B	17/06/2017

Signature: Date: 2017.07.28


Measuring and Testing Equipment List



Used MTE

Report Number: 50087662 001

Description	MTE Type/model	Internal ID	Next Calibration (DD/MM/YY)
<input type="checkbox"/> Data acquisition/switch unit	34972A	1.381C	17/06/2017
<input type="checkbox"/> Data acquisition/switch unit	34972A	1.381F	17/06/2017
<input type="checkbox"/> Data acquisition/switch unit	34972A	1.381G	17/05/2017
<input type="checkbox"/> Data acquisition/switch unit	34972A	1.381H	18/05/2017
<input type="checkbox"/> Data acquisition/switch unit	34972A	1.381K	17/05/2017
<input type="checkbox"/> Data acquisition/switch unit	34972A	1.381L	14/10/2017
<input type="checkbox"/> Data acquisition/switch unit	34972A	1.381M	14/10/2017
<input type="checkbox"/> Data acquisition/switch unit	34972A	1.381N	14/10/2017
<input type="checkbox"/> Data acquisition/switch unit	34972A	1.381S	17/05/2017
<input type="checkbox"/> Electronic scales	BS-30KA	1.382	14/10/2017
<input type="checkbox"/> Oven	1040121209 ST-120B1	1.383	08/03/2018
<input type="checkbox"/> Oven	1040121208 ST-120B1	1.384	08/03/2018
<input type="checkbox"/> DC electronic load	EA-EL 3160-60	1.385	14/10/2017
<input checked="" type="checkbox"/> Test Probe A	DMS-A18	1.390A	25/02/2019
<input type="checkbox"/> Weights	2kg	1.511	28/05/2017
<input type="checkbox"/> Weights	1kg	1.512	28/05/2017
<input type="checkbox"/> Weights	500g	1.513	28/05/2017
<input type="checkbox"/> Wind speed meter/anemometer	Fluke 925	1.514	13/06/2017
<input type="checkbox"/> Pressure gauge	0-4MPa	1.515	17/05/2017
<input type="checkbox"/> AC Power Supply	AFA-11001G-100A	1.600	07/04/2017
<input type="checkbox"/> AC Power Supply	0-50V, 0-100A	1.600A	20/06/2017

Signature: Date: 2017.07.28

Measuring and Testing Equipment List



Used MTE

Report Number: 50087662 001

Description	MTE Type/model	Internal ID	Next Calibration (DD/MM/YY)
<input type="checkbox"/> AC Power Supply	AFA-11001G-50A	1.600B	26/07/2017
<input type="checkbox"/> AC Power Supply	PCR2000M	1.601	24/11/2017
<input type="checkbox"/> AC Power Supply	ANFS030A	1.601A	10/01/2018
<input type="checkbox"/> <u>Oven</u>	<u>ST120B1</u>	<u>1.607</u>	<u>28/09/2017</u>
<input type="checkbox"/> Oven	ST120B1	1.608	28/09/2017
<input type="checkbox"/> Test Probe 18	Test Probe 18	1.611	18/10/2019
<input type="checkbox"/> Electronic Scales	0-100KG	1.615	14/10/2017
<input checked="" type="checkbox"/> Digital display Angle instrument	0-180° ±1°	1.618	23/02/2018
<input type="checkbox"/> Microscope	AM3111	1.655	05/08/2017

Measurement Uncertainty Reference Data

Current Measurement(YOKOGAWA WT310):

(0.005A-20A):±0.41%

Voltage Measurement(YOKOGAWAWT310):

(0.4V-300V): ±0.35%

Power Measurement(YOKOGAWA WT310):

(45Hz-66Hz):±1.20% (0.1W-1W), ±1.21% (1W-3600W)

Temperature Rise Measurement:

(Thermocouple method YOKOGAWA DX230):±3.5°C

(Winding resistance method Agilent 34970A):±3.21°C

Resistance of ground connection measurement(KIKUSUI TOS6200):±0.004 Ω

Leakage Current Measurement(HIOKI3156):±0.008mA

Clearance& Creepage Distance Measurement(Digital caliper):±0.14mm

Closing time of the lower guard of hand-held circular saw:±0.022s

Ball pressure Measurement:±0.042mm

saw: ±0.0011s

Insulation Resistance Measurement(Insulation Resistance Meter HIOKI3453): ±0.027 MΩ

Pull Force Measurement(Digital Force Gauge HP-1K): ±0.29N

Angle Measurement: ±0.7°

Torque Measurement: ±3.47%

Signature: Date: 2017.07.28


Measuring and Testing Equipment List



Used MTE

Report Number: 50087662 001

Description	MTE Type/model	Internal ID	Next Calibration (DD/MM/YY)
EMF Measurement (ELT-400): ±8.8%			
Photobiological safety system measurement:			
(Effective irradiance measurement ES) ±22.74%			
(Near ultraviolet hazard) ±22.74%			
(Retinal blue-light hazard) ±11.06%			
(Retinal thermal hazard) ±11.06%			
(Retinal thermal hazard – weak visual stimulus) ±11.06%			
(Infrared radiation hazard exposure for the eye) ±14.81%			
(Thermal hazard exposure limit for the skin) ±14.81%			
Initial luminous efficacy measurement for CFLs: ±0.67 lm/W			
Temperature measurement for glow-wire tester: 0.3%			
Color coordinate measurement of light source: X:±0.48%;Y:±0.48%			
Air or water Pressure measurement:±0.003 Mpa			
Power Factor(YOKOGAWA WT310)(10Hz-1.2kHz): ±0.005			
Frequency (YOKOGAWA WT310)(45Hz - 66Hz): ±0.07%			
Humidity(175H1): ±2.32%RH (2-80%RH)			
The kinetic energy of cutting line of lawn trimmer: ± 0.006J			
Uncertainty of Evaluation (Caliper): ±0.02mm			
Hi-pot Test (Range:500V-5000V) : ±18V			
Mass: ±0.00024g			

Signature: Date: 2017.07.28