



SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technological
Development District, Guangzhou, China 510663

Telephone: +86 (0) 20 82155555
Fax: +86 (0) 20 82075059
Email: ee.guangzhou@sgs.com

Report No.: GZEM180900516701

Page: 1 of 29

TEST REPORT

Application No.: GZEM1809005167HS
Applicant: Foshan Shunde Shinechef Electric Appliance Co., Ltd
Address of Applicant: No.3 Jinan Road, Changxing Industrial Zone, Jun An Town, Foshan City,
Guangdong Province, China
Manufacturer: The same as Applicant
Address of Manufacturer: The same as Address of Applicant
Factory: The same as Applicant
Address of Factory: The same as Address of Applicant
Equipment Under Test (EUT):
EUT Name: Stand Mixer
Model No.: SC-206, SC-216, SC-206A, SC-216A, SC-206B, SC-216B, SC-206C,
SC-216C. □
□ Please refer to section 2 of this report which indicates which model was actually
tested and which were electrically identical.
Trade Mark: SCHEF
Standards: EN 55014-1:2017
EN 55014-2:2015
EN 61000-3-2:2014
EN 61000-3-3:2013
Date of Receipt: 2018-09-14
Date of Test: 2018-09-19 to 2018-10-29
Date of Issue: 2018-11-06

Test Result :	Pass*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

The CE mark as shown below can be used, under the responsibility of the manufacturer, after completion of an EU Declaration of Conformity and compliance with all relevant EU Directives.



Kobe Jian
EMC Laboratory Manager



The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.





SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch

Report No.: GZEM180900516701

Page: 2 of 29

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2018-11-06		Original

Authorized for issue by:			
Tested By		2018-09-19 to 2018-10-29	
Checked By		2018-11-01	
	Jenny Chen /Project Engineer	Date	
	Cherie Luo /Reviewer	Date	

2 Test Summary

Emission Part				
Item	Standard	Method	Requirement	Result
Conducted Disturbance at Mains Terminals (150kHz-30MHz)	EN 55014-1:2017	CISPR 16-2-1	N/A	Pass**
Disturbance Power	EN 55014-1:2017	CISPR 16-2-2	N/A	Pass
Discontinuous Disturbance (150kHz-30MHz)	EN 55014-1:2017	EN 55014-1:2017	N/A	Pass*
Harmonic Current Emission	EN 61000-3-2:2014	EN 61000-3-2:2014	Class A	Pass*
Voltage Fluctuations and Flicker	EN 61000-3-3:2013	EN 61000-3-3:2013	Clause 5 of EN 61000-3-3	Pass
Immunity Part				
Immunity	EN 55014-2:2015	EN 55014-2:2015	Clause 4.1 of EN 55014-2	Pass*

N/A: Not applicable

* Please refer to Section 6.3, 6.4 & 7 of this report for details.

** The EUT passed Conducted Disturbance at Mains Terminals (150kHz-30MHz) after modification.

Declaration of EUT Family Grouping:

Model No.: SC-206, SC-216, SC-206A, SC-216A, SC-206B, SC-216B, SC-206C, SC-216C.

According to the declaration from the applicant, the electrical circuit design, layout, components used and internal wiring were identical for all models, with only difference on the function and outer decoration.

Model No.	Function
SC-206, SC-216	Mixer
SC-206A, SC-216A	Mixer & Mincer
SC-206B, SC-216B	Mixer & Blender
SC-206C, SC-216C	Mixer & Mincer & Blender

Therefore only one model **SC-206C** was tested in this report.

3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information	5
4.1 Details of E.U.T.	5
4.2 Description of Support Units	5
4.3 Measurement Uncertainty	5
4.4 Test Location	6
4.5 Test Facility	6
4.6 Deviation from Standards	7
4.7 Abnormalities from Standard Conditions	7
4.8 Monitoring of EUT for All Immunity Test	7
5 Equipment List.....	8
6 Emission Test Results	10
6.1 Conducted Disturbance at Mains Terminals (150kHz-30MHz).....	10
6.1.1 E.U.T. Operation.....	10
6.1.2 Test Setup Diagram.....	10
6.1.3 Measurement Data	11
6.2 Disturbance Power.....	13
6.2.1 E.U.T. Operation.....	13
6.2.2 Test Setup Diagram.....	13
6.2.3 Measurement Data	14
6.3 Discontinuous Disturbance (150kHz-30MHz)	15
6.4 Harmonic Current Emission	16
6.5 Voltage Fluctuations and Flicker	17
6.5.1 E.U.T. Operation.....	17
6.5.2 Test Setup Diagram.....	17
6.5.3 Measurement Data	18
7 Immunity Test Results	19
8 Photographs.....	20
8.1 EUT Constructional Details	20

4 General Information

4.1 Details of E.U.T.

Power Supply:	AC 220-240V, 50/60Hz
Rated Power:	For mixer and blender: 1000W, For mincer: 300W
Test Voltage:	AC 230V, 50Hz
Cable:	2 wires x about 1.2m unscreened AC mains cable.

4.2 Description of Support Units

The EUT has been tested as an independent unit.

4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Conducted Disturbance	3.63dB (9kHz to 150kHz)
		3.22dB (150kHz to 30MHz)
2	Disturbance Power	3.78dB
3	Radiated Disturbance	5.0dB (30MHz-1GHz)
		5.0dB (1GHz-6GHz)
4	Temperature Test	0.4 °C
5	Humidity Test	1.3%

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory,
 198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District,
 Guangzhou, China 510663

Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP (Lab Code: 200611-0)**

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

- **ACMA**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.

- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

- **CNAS (Lab Code: L0167)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

- **FCC (Registration No.: 282399)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002.

- **Industry Canada (Registration No.: 4620B-1)**

The 3m/10m Alternate Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Certification and Engineering of Industry Canada for radio equipment testing with Registration No. 4620B-1.

- **VCCI (Registration No.: R-2460, C-2584, G-449 and T-1179)**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co. Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2460, C-2584, G-449 and T-1179 respectively.

- **CBTL (Lab Code: TL129)**

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2005, the Basic Rules, IECEE 01 and Rules of procedure IECEE 02, and the relevant IECEE CB-Scheme Operational documents.

4.6 Deviation from Standards

None.

4.7 Abnormalities from Standard Conditions

The EUT passed Conducted Disturbance at Mains Terminals (150kHz-30MHz) after modification.

4.8 Monitoring of EUT for All Immunity Test

Visual: N/A

Audio: N/A

5 Equipment List

Conducted Disturbance at Mains Terminals (150kHz-30MHz)						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. date	Cal.Due date
					(YYYY-MM-DD)	(YYYY-MM-DD)
EMC0306	Shielding Room	Zhong Yu	8 x 3 x 3.8 m ³	N/A	2016-12-27	2019-12-26
EMC0118	Two-line v-netwok	R&S	ENV216	100359	2018-01-19	2019-01-18
EMC2135	Two-line v-netwok	R&S	ENV216	102259	2018-09-21	2019-09-20
EMC0203	LISN	AFJ	LS16-OPT001	116019831056	2018-01-08	2019-01-07
EMC0506	EMI Test Receiver	Rohde & Schwarz	ESCS30	100085	2017-11-27	2018-11-26
EMC0107	Coaxial Cable	SGS	2m	N/A	2017-07-23	2019-07-22
EMC0106	Voltage Probe	SGS	N/A	N/A	2018-04-04	2020-04-03
EMC2123	8 Line ISN Cat 6	SCHWARZBECK MESS-ELEKTRONIK	NTFM 8158	NTFM 8158 0151	2018-05-29	2019-05-29
EMC2124	8 Line ISN Cat 5	SCHWARZBECK MESS-ELEKTRONIK	CAT5 8158	CAT5 8158-188	2018-05-29	2019-05-29
EMC2126	8 Line ISN Cat 3	SCHWARZBECK MESS-ELEKTRONIK	CAT3 8158	CAT38158-0081	2018-05-29	2019-05-29
EMC2122	ISN S8	SCHWARZBECK MESS-ELEKTRONIK	ISN S8	57	2018-05-29	2019-05-29
EMC2121	ISN S1	SCHWARZBECK MESS-ELEKTRONIK	ISN S1	10	2018-05-29	2019-05-29
EMC2125	2 wires ISN	SCHWARZBECK MESS-ELEKTRONIK	NTFM 8131	8131-198	2018-05-29	2019-05-29
EMC2047	CDN	Elektronik- Feinmechanik	L-801:AF2	2793	2018-09-19	2020-09-18
EMC2048	CDN	Elektronik- Feinmechanik	L-801:M2/M3	2738	2018-08-13	2020-08-12
EMC2062	6dB Attenuator	HP	8491A	24487	2018-04-04	2020-04-03
EMC0167	Conical metal housing	SGS-EMC	N/A	N/A	2018-04-19	2020-04-18

Disturbance Power						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. date	Cal.Due date
					(YYYY-MM-DD)	(YYYY-MM-DD)
EMC0306	Shielding Room	Zhong Yu	8 x 3 x 3.8 m ³	N/A	2016-12-27	2019-12-26
EMC2040	Absorbing Clamp	Beijing Dazhe Co. Ltd.	ZN23201	N/A	2018-01-11	2019-01-10
EMC0303	7m Coaxial Cable	SGS	7m	N/A	2017-6-30	2019-06-29
EMC0506	EMI Test Receiver	Rohde & Schwarz	ESCS30	100085	2017-11-27	2018-11-26
EMC2062	6dB Attenuator	HP	8491A	24487	2018-04-04	2020-04-03
EMC0305	Slide Bar Controller	HD-GmbH	HD50	050/490	N/A	N/A
EMC0103	Slide Bar RP	HD-GmbH	KMS560	560/392	N/A	N/A



SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch

Report No.: GZEM180900516701

Page: 9 of 29

Harmonic Current Emission / Voltage Fluctuations and Flicker						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. date	Cal.Due date
					(YYYY-MM-DD)	(YYYY-MM-DD)
EMC0608	AC Power Source	California	50001iX	56627	2018-03-19	2019-03-18
EMC0607	Power Analyzer	California	PACS	72400	2018-03-19	2019-03-18

General used equipment						
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. date	Cal.Due date
					(YYYY-MM-DD)	(YYYY-MM-DD)
EMC0006	DMM	Fluke	73	70681569	2018-07-20	2019-07-19
EMC0007	DMM	Fluke	73	70671122	2018-07-19	2019-07-18

6 Emission Test Results

6.1 Conducted Disturbance at Mains Terminals (150kHz-30MHz)

Test Requirement:	EN 55014-1:2017
Test Method:	CISPR 16-2-1
Frequency Range:	150kHz to 30MHz
Limit:	
0.15MHz-0.5MHz	66dB(μ V)-56dB(μ V) quasi-peak, 59dB(μ V)-46dB(μ V) average
0.5MHz-5MHz	56dB(μ V) quasi-peak, 46dB(μ V) average
5MHz-30MHz	60dB(μ V) quasi-peak, 50dB(μ V) average
Detector:	Peak for pre-scan (9kHz resolution bandwidth) 150KHz to 30MHz

6.1.1 E.U.T. Operation

Operating Environment:

Temperature: 21 °C Humidity: 53 % RH Atmospheric Pressure: 1015 mbar


Pre-test these modes to find the worst case:

- a: Test the EUT in motor running mode at maximum speed.
- b: Test the EUT in motor running mode at medium speed.
- c: Test the EUT in motor running mode at minimum speed.

The worst case for final test:

- a: Test the EUT in motor running mode at maximum speed.

6.1.2 Test Setup Diagram




6.1.3 Measurement Data

An initial pre-scan was performed with peak detector. Quasi-Peak or Average measurement were performed at the frequencies with maximized peak emission were detected.


Live Line

Level (dBμV)



Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
MHz	dBμV	dB	dB	dBμV	dBμV	dB	
0.156	12.04	9.65	0.10	21.79	58.54	-36.75	Average
0.156	26.22	9.65	0.10	35.97	65.65	-29.68	QP
0.200	7.05	9.64	0.00	16.69	55.91	-39.22	Average
0.200	19.76	9.64	0.00	29.40	63.62	-34.22	QP
0.289	3.34	9.64	0.00	12.98	51.91	-38.93	Average
0.289	15.07	9.64	0.00	24.71	60.54	-35.83	QP
0.435	4.63	9.64	0.00	14.27	47.50	-33.23	Average
0.435	16.43	9.64	0.00	26.07	57.15	-31.08	QP
3.943	3.63	9.69	0.10	13.42	46.00	-32.58	Average
3.943	6.88	9.69	0.10	16.67	56.00	-39.33	QP
9.011	3.58	9.79	0.20	13.57	50.00	-36.43	Average
9.011	11.18	9.79	0.20	21.17	60.00	-38.83	QP

Neutral Line
Level (dBμV)



Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
MHz	dBμV	dB	dB	dBμV	dBμV	dB	
0.162	13.40	9.67	0.00	23.07	58.20	-35.13	Average
0.162	25.32	9.67	0.00	34.99	65.38	-30.39	QP
0.194	8.32	9.67	0.00	17.99	56.20	-38.21	Average
0.194	20.14	9.67	0.00	29.81	63.84	-34.03	QP
0.222	6.66	9.67	0.00	16.33	54.77	-38.44	Average
0.222	15.83	9.67	0.00	25.50	62.74	-37.24	QP
0.410	3.13	9.67	0.00	12.80	48.13	-35.33	Average
0.410	14.76	9.67	0.00	24.43	57.64	-33.21	QP
0.447	4.56	9.67	0.00	14.23	47.21	-32.98	Average
0.447	17.16	9.67	0.00	26.83	56.93	-30.10	QP
7.977	2.60	9.79	0.20	12.59	50.00	-37.41	Average
7.977	6.47	9.79	0.20	16.46	60.00	-43.54	QP

6.2 Disturbance Power

Test Requirement:	EN 55014-1:2017
Test Method:	CISPR 16-2-2
Frequency Range:	30MHz to 300MHz
Limit:	
30MHz- 300MHz	45dB(pw)-55dB(pw) quasi-peak, 35dB(pw)-45dB(pw) average
Detector:	Peak for pre-scan (120kHz resolution bandwidth) 30MHz to 300MHz

6.2.1 E.U.T. Operation

Operating Environment:

Temperature: 21 °C Humidity: 53 % RH Atmospheric Pressure: 1015 mbar


Pre-test these modes to find the worst case:

- a: Test the EUT in motor running mode at maximum speed.
- b: Test the EUT in motor running mode at medium speed.
- c: Test the EUT in motor running mode at minimum speed.

The worst case for final test:

- a: Test the EUT in motor running mode at maximum speed.


6.2.2 Test Setup Diagram



6.2.3 Measurement Data

An initial pre-scan was performed with peak detector. Quasi-Peak or Average measurement were performed at the frequencies with maximized peak emission were detected.

Level (dBpW)



Frequency MHz	Read Level dBuV	Cable Loss dB	Clamp Factor dBpW/dBuV	Measured Level dBpW	Limit Line dBpW	Over limit dB	Remark
34.924	8.97	1.25	2.49	12.71	35.18	-22.47	Average
34.924	13.41	1.25	2.49	17.15	45.18	-28.03	QP
52.616	6.47	1.65	0.49	8.61	35.84	-27.23	Average
52.616	13.27	1.65	0.49	15.41	45.84	-30.43	QP
74.838	8.11	2.01	0.32	10.44	36.66	-26.22	Average
74.838	15.39	2.01	0.32	17.72	46.66	-28.94	QP
87.322	7.30	2.16	-0.25	9.21	37.12	-27.91	Average
87.322	13.40	2.16	-0.25	15.31	47.12	-31.81	QP
111.975	6.48	2.68	0.87	10.03	38.04	-28.01	Average
111.975	10.43	2.68	0.87	13.98	48.04	-34.06	QP
204.231	14.14	3.57	-2.75	14.96	41.45	-26.49	Average
204.231	29.64	3.57	-2.75	30.46	51.03	-20.57	QP

6.3 Discontinuous Disturbance (150kHz-30MHz)

Test Requirement: EN 55014-1:2017

Test Method: EN 55014-1:2017

Frequency Range: 150kHz to 30MHz

Remark:

Not applicable. The EUT belongs to exceptions from the click definition in clause 4.2.3.1,

“4.2.3.1 Individual switching operations

The disturbance from individual switching operations, caused directly or indirectly, manually or by similar activities on a switch or a control which is included in an appliance or otherwise to be used for:

a) the purpose of mains connection or disconnection only;

b) the purpose of programme selection only;

c) the control of energy or speed by switching between a limited number of fixed positions;

d) the changing of the manual setting of a continuously adjustable control such as a variable speed device for water extraction or electronic thermostats, is to be disregarded for the purpose of testing the appliance for compliance with the limits of radio disturbance set out in this standard.

Examples of switches included in this subclause are the on/off switches for apparatus (including foot activated), for instance the switch for an electric typewriter, manual switches for heat and air flow control in fan heaters and hair dryers, as well as the indirectly operated switch in a cupboard, wardrobe or refrigerator, and sensor-operated switches, etc. Switches which usually will be repeatedly operated are not included in this subclause, e.g. for sewing machines, calculating machines, soldering equipment, etc. (see 7.2.3. and 7.3.2.4.c).

Also the disturbance caused by the operation of any switching device or control which is included in an appliance for the purpose of mains disconnection for safety only, is to be disregarded for the purpose of testing the appliance for compliance with the limits of radio disturbance as described in this standard.”

6.4 Harmonic Current Emission

Test Requirement: EN 61000-3-2:2014

Test Method: EN 61000-3-2:2014

Remark:

Since the EUT was belong to exception of clause 7 and Annex C, according to EN 61000-3-2 figure 1, it was deemed to conform to the requirements of this standard without further testing.

“7 Harmonic current limits

The procedure for applying the limits and assessing the results is shown in Figure 1.

For the following categories of equipment, limits are not specified in this standard:

NOTE 1 Limits may be defined in a future amendment or revision of the standard.

– equipment with a rated power of 75 W or less, other than lighting equipment.

NOTE 2 This value may be reduced from 75 W to 50 W in the future, subject to approval by National Committees at that time.

– professional equipment with a total rated power greater than 1 kW.

– symmetrically controlled heating elements with a rated power less than or equal to 200 W.

– independent dimmers for incandescent lamps with a rated power less than or equal to 1 kW.

NOTE 3 See also C.5.3.”

and

No limit applies for all LED lighting equipments with active input power ≤ 25 W except Discharge lighting equipment (refer to 7.3 b))

Kitchen machines as listed in the scope of IEC 60335-2-14 are deemed to conform to the harmonic current limits of this standard without further testing.

Please read clause 7 & Annex C of this standard for reference.

6.5 Voltage Fluctuations and Flicker

Test Requirement: EN 61000-3-3:2013

Test Method: EN 61000-3-3:2013

6.5.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 55 % RH Atmospheric Pressure: 1010 mbar


Pre-test these modes to find the worst case:

- a: Test the EUT in motor running mode at maximum speed.
- b: Test the EUT in motor running mode at medium speed.
- c: Test the EUT in motor running mode at minimum speed.

The worst case for final test:

- a: Test the EUT in motor running mode at maximum speed.

6.5.2 Test Setup Diagram





6.5.3 Measurement Data

Flicker Test Summary per EN 61000-3-3 (Run time)

Test Result: Pass

Status: Test Completed

Parameter values recorded during the test:

Vrms at the end of test (Volt): 230.03

Highest dt (%): 0.32

T-max (mS): 0

Highest dc (%): -0.33

Highest dmax (%): 0.82

Test limit (%): N/A N/A

Test limit (mS): 500.0 Pass

Test limit (%): 3.30 Pass

Test limit (%): 7.00 Pass

7 Immunity Test Results

Test Requirement: EN 55014-2:2015

Test Method: N/A: See Remark Below

There is no need for immunity tests to be performed on this product in accordance with clause 7.2.1 of EN 55014-2 which states:

“Category I apparatus is deemed to fulfil the relevant immunity requirement without testing.”

For further details, please refer to clause 4.1 of EN 55014-2 which states:

“Category I: apparatus containing no electronic control circuitry.


Example: motor operated appliances, lighting toys, track sets without electronic control units, tools, heating appliances UV and IR radiators and apparatus containing components such as electromechanical switches and thermostats.


Electric circuits consisting of passive components (such as radio interference suppression capacitors or inductors, mains transformers and mains frequency rectifiers) are not considered to be electronic control circuitry.”



8 Photographs


8.1 EUT Constructional Details


























--End of Report--